FINAL SCIENTIFIC/TECHNICAL REPORT

Project Title: Hydrogen Filling Station (HFS)

Project Period: June 12, 2003 through December 31, 2009

Recipient: UNLV Research Foundation

Grant Award Number: DE-FG36-03G013063

Working Partners: Proton Energy Systems
UNLV Center for Energy Research (UNLV-CER)
UNLV College of Science Department of Chemistry
Las Vegas Valley Water District (LVVWD)
Altair Nanomaterials Inc.
Hydrogen Solar LLC
National Renewable Energy Laboratory (NREL)
IF LLC
Kell's Automotive (Purchase Order)

Contact: Loni Benard, Administrator, Grants and Contracts
UNLV Research Foundation
8311 W. Sunset Rd. Suite 200
Las Vegas, NV 89113
(702) 895-2833, ext 232
loni.benard@unlv.edu

This report was prepared by the University of Nevada, Las Vegas, Research Foundation (UNLVRF) pursuant to a grant funded by the U.S. Department of Energy, and neither UNLVRF nor any of its subcontractors nor the U.S. Department of Energy nor any person acting on behalf of either:

- (a) makes any warranty or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report; or
- (b) assumes any liabilities with respect to the use of, or for damages resulting from the use of, any information, apparatus, method or process disclosed in this report.

References herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise do not necessarily constitute or imply its endorsement, recommendation or favoring by the U.S. Department of Energy. The views and opinions of authors expressed herein do not necessarily state or reflect those of the U.S. Department of Energy.

TABLE OF CONTENTS

EXECUTIVE SUMMARY	1
PROJECT OBJECTIVES	2
Comparison of Actual Accomplishments with the Project Objectives	3
Summary of Project Activities	5
Development of a Hydrogen Filling Station at the Las Vegas Valley Water District	5
Hydrogen Vehicle Development and Integration	6
Hydrogen Safety – Deployment and Risk Management Workshop	8
Development of a Roadmap for Hydrogen Development in Nevada	9
Photoelectrochemistry (PEC)	10
Hydrogen Solar	11
UNLV-CER	12
Altrair Nanomaterials	13
UNLV Chemistry Department	14
NREL	14
Research for Higher Efficiency PEM Technology	14
PRODUCT DEVELOPMENT AND TECHNOLOGY TRANSFER ACTIVITIES	16
Publications/Presentations	16
Website/Internet Sites that Reflect Results of this Project	20
Networks or Collaborations Fostered	21
Inventions/Patent Applications	21
COMPUTER MODELING	22

FIGURES

Figure 1. Initial design of straight channel flow field	22
Figure 2. Initial CFD domain of the straight channel flow field	23
Figure 3. Final design of straight channel flow field after CFD analysis	24
Figure 4. Final CFD domain of the modified straight channel flow field design	24
Figure 5. Boundary conditions for 2D CFD modeling of the PEM electrolyzer	29
Figure 6. Source and sink terms for multi-physics PEM electrolyzer model	30

PICTURES

Picture 1. Completed Solar Powered Hydrogen Filling Station Located at the Las Vegas Valley Water District	6
Picture 2. Vehicle Fueling Demonstration During the Grand Opening April, 2007	6
Picture 3. The Taylor-Dunn electric vehicle converted to a hydrogen-electric fuel cell vehicle	7
Picture 4. The Polaris Ranger ICE vehicle that was converted to burn hydrogen	8
Picture 5. The Ford V-8 pickup that was converted to a hydrogen ICE vehicle	8
Picture 6. On-Sun Testing Facility installed on roof of UNLV building	12

ATTACHMENTS

Attachment 1.	Final Report “Development of Hydrogen Filling Station at Las Vegas Valley Water District” prepared by Proton Energy Systems dated March 3, 2008	35
Attachment 2.	Final Report “UNLV Vehicle Development Work for the Hydrogen Filling Station” prepared by UNLV-CER dated January 15, 2010	50
Attachment 3.	Final Report “Hydrogen Roadmap Document” prepared by David Haberman of IF, LLC	81
Attachment 4.	Final Report “UNLV-NREL Collaborative PEC Project” prepared by NREL dated February, 2008	102
Attachment 5.	Status Report dated December 22, 2006 from Hydrogen Solar LLC.	132
Attachment 6.	Final Progress Report from Altair Nanotechnologies, Inc. dated September 23, 2008	162
Attachment 7.	Final Report “Research for Higher Efficiency PEM Technology” prepared by Proton Energy Systems dated July 1, 2008	189
Attachment 8.	Final Report “Research for Higher Efficiency PEM Technology - Final Report of Experimental MEA Characterization Test Results” prepared by Proton Energy Systems dated February 12, 2008	205
Attachment 9.	Final Report “Research for Higher Efficiency PEM Technology – Final Report of Experimental Catalyst Characterization Test Results” prepared by Proton Energy Systems dated October 15, 2007	221
Attachment 10.	Final Report “Research for Higher Efficiency PEM Technology – Final Report of PEM Electrolysis Membrane Candidates” prepared by Proton Energy Systems dated December 12, 2007	236

EXECUTIVE SUMMARY:

Hydrogen is an environmentally attractive transportation fuel that has the potential to displace fossil fuels. The Freedom CAR and Freedom FUEL initiatives emphasize the importance of hydrogen as a future transportation fuel. Presently, Las Vegas has one hydrogen fueling station powered by natural gas. However, the use of traditional sources of energy to produce hydrogen does not maximize the benefit. The hydrogen fueling station developed under this grant used electrolysis units and solar energy to produce hydrogen fuel. Water and electricity are furnished to the unit and the output is hydrogen and oxygen.

Three vehicles were converted to utilize the hydrogen produced at the station. The vehicles were all equipped with different types of technologies. The vehicles were used in the day-to-day operation of the Las Vegas Valley Water District and monitoring was performed on efficiency, reliability and maintenance requirements. The research and demonstration utilized for the reconfiguration of these vehicles could lead to new technologies in vehicle development that could make hydrogen-fueled vehicles more cost effective, economical, efficient and more widely used.

In order to advance the development of a hydrogen future in Southern Nevada, project partners recognized a need to bring various entities involved in hydrogen development and deployment together as a means of sharing knowledge and eliminating duplication of efforts. A road-mapping session was held in Las Vegas in June 2006. The Nevada State Energy Office, representatives from DOE, DOE contractors and LANL, NETL, NREL were present. Leadership from the National hydrogen Association Board of Directors also attended. As a result of this session, a roadmap for hydrogen development was created. This roadmap has the ability to become a tool for use by other road-mapping efforts in the hydrogen community. It could also become a standard template for other states or even countries to approach planning for a hydrogen future.

Project partners also conducted a workshop on hydrogen safety and permitting. This provided an opportunity for the various permitting agencies and end users to gather to share experiences and knowledge. As a result of this workshop, the permitting process for the hydrogen filling station on the Las Vegas Valley Water District's land was done more efficiently and those who would be responsible for the operation were better educated on the safety and reliability of hydrogen production and storage. The lessons learned in permitting the filling station and conducting this workshop provided a basis for future hydrogen projects in the region.

Continuing efforts to increase the working pressure of electrolysis and efficiency have been pursued. Research was also performed on improving the cost, efficiency and durability of Proton Exchange Membrane (PEM) hydrogen technology. Research elements focused upon PEM membranes, electrodes/catalysts, membrane-electrode assemblies, seals, bipolar plates, utilization of renewable power, reliability issues, scale, and advanced conversion topics.

Additionally, direct solar-to-hydrogen conversion research to demonstrate stable and efficient photoelectrochemistry (PEC) hydrogen production systems based on a number of optional concepts was performed. Candidate PEC concepts included technical obstacles such as inefficient photocatalysis, inadequate photocurrent due to non-optimal material band gap energies, rapid electron-hole recombination, reduced hole mobility and diminished operational lifetimes of surface materials exposed to electrolytes.

PROJECT OBJECTIVES:

Project Objective 1: Design, build, operate hydrogen filling station

Build, operate and analyze performance of a hydrogen production/filling station (HFS) in Southern Nevada to produce hydrogen by electrolysis of water. Initially, conventional electrical power will be employed followed by solar energy generated (photovoltaic) electrical power.

Project Objective 2: Perform research and development for utilizing solar technologies on the hydrogen filling station and convert two utility vehicles for use by the station operators

Perform various research and development tasks connected with the production of hydrogen using solar technologies. Provide for the enhancement of the hydrogen filling station that is being developed under objective 1. Convert two utility vehicles from gasoline and electric power to hydrogen fuel.

Project Objective 3: Increase capacity of hydrogen filling station; add additional vehicle; conduct safety workshop; develop a roadmap for hydrogen development; accelerate the development of photovoltaic components

Increase the capacity of the hydrogen production /filling station and develop high pressure hydrogen generation components. Adapt a full-sized ICE vehicle for hydrogen fuel use. Equip a duplicate natural gas vehicle with monitoring equipment for comparison purposes. Conduct a hydrogen safety/permitting workshop and develop a roadmap for hydrogen development in Nevada. Accelerate the development and characterization of state-of-the-art photovoltaic components coupled to photoactive oxide films immersed in suitable electrolytes.

Project Objective 4: Perform research on the Proton Exchange membrane

Perform research to improve the cost, efficiency and durability of Proton Exchange Membrane (PEM) hydrogen technology. Research elements focus upon PEM membranes, electrodes/catalysts, membrane-electrode assemblies, seals, bipolar plates, utilization of renewable power, reliability issues, scale, and advanced conversion topics. Continuing support of the HFS in Southern Nevada and discovery and characterization of PEC materials are also included in this objective.

Comparison of Actual Accomplishments with the Project Objectives:

Project Objective 1: Design, build, operate hydrogen filling station

The hydrogen fueling station at the Las Vegas Valley Water District is an operating station, which generates hydrogen fuel from renewable energy resources. The station has been in operation since the spring of 2007. Originally, the station was to be operated utilizing conventional electrical power and phasing in the renewable energy component after the initial operation. However, due to permitting constraints and project delays, the renewable component was introduced at the time the station was commissioned. The station is now generating of 13 kg of hydrogen per day.

Project Objective 2: Perform research and development for utilizing solar technologies on the hydrogen filling station and convert two utility vehicles for use by the station operators

With an initial capacity of 2 kg of hydrogen per day, the station was modified utilizing enhancements developed by Proton Energy Systems to increase the pressure and production of hydrogen. In conjunction with the Las Vegas Valley Water District and the Southern Nevada Water Authority, a solar PV array was designed and built in order to supply renewable electrical power for the hydrogen generation and compression.

Two service vehicles provided by the Las Vegas Valley Water District were modified to run on hydrogen. A Polaris Ranger with internal combustion engine (ICE) was converted using locally developed state-of-the-art in-cylinder injection. A Taylor-Dunn Electruck was also modified with the addition of a PEM fuel cell. The vehicles are now in use at the Las Vegas Valley Water District's Springs Preserve and are using the filling station on a regular basis.

Project Objective 3: Increase capacity of hydrogen filling station; add additional vehicle; conduct safety workshop; develop a roadmap for hydrogen development; accelerate the development of photovoltaic components

The equipment developed under this objective was designed to generate hydrogen at higher capacities, yet increase overall hydrogen generation efficiencies and minimize the overall capital expenditures for a fueling station. As of May 2008, the system has generated approximately 350 kg of hydrogen at 30 barg equating to over 650 hours of runtime.

A third vehicle was supplied by the Las Vegas Valley Water District. This vehicle is a full-sized pickup that has street use by the meter readers. The vehicle uses a V-8 engine modified with the improved direct-injection system compared with the ICE vehicle mentioned in objective 2. This vehicle uses a second design configuration that incorporates the spark plug and the in-cylinder injector in the same assembly. This approach greatly simplifies the installation and hence the conversion requirements from a conventional engine configuration. The conversion approach used on this vehicle is

one of the key developments in the vehicle work in this project. In addition, a very large amount of on-board hydrogen storage is included in this vehicle.

On April 10, 2006 a hydrogen safety workshop was conducted on the UNLV campus. The workshop was attended by 30 professionals from 11 states. The purpose of the workshop was to share information and perspectives on hydrogen safety and risk management.

On June 20, 2006 a road-mapping session was conducted at UNLV with approximately 40 participants. A roadmap was presented that addressed four areas of direction for the future of hydrogen development. The primary conclusion by the participants was that the roadmap must be adapted and championed by a public-private partnership that could be used as a tool for other hydrogen efforts and development activities.

Additional work under this objective included the testing and development of different types of thin film materials that absorb light with enough energy to split water resulting in the development of a photoelectrochemical cell. The many materials that were previously considered as being able to split water were not capable of separating the electrons with holes that matched what was needed to split water. Critical cell working parameters including chemical reactions at electrode surfaces, boundary layer condition, thermal effects, heat and mass transfer and fluid flow characteristics were defined.

Project Objective 4: Perform research on the Proton Exchange membrane with continuing support for the hydrogen filling station and the characterization of PEC materials

The overall goal of this program was to conduct fundamental research to improve the cost, efficiency, and durability of PEM electrolysis. Significant work was accomplished to advance understanding of PEM electrolysis and provide direction for improved efficiency and durability. A large active area test stand and prototype large active area parts were also fabricated in order to begin proving feasibility of larger units in order to decrease the cost of hydrogen in \$/kg.

Under this objective, work continued in the area of the development of the photo-electrochemical cell as described in Objective 3 above. Several tasks involved the development of an iron oxide film suitable for the front electrode of the PEC hydrogen-generating cell. Materials used to coat the front cell needed to be deposited thin enough to allow the unabsorbed longer wavelengths of length to pass through to a back cell so that an electric current could be generated to drive the hydrogen and oxygen evolving reactions. Work performed in this area included the determination and selection of a synthesis route for non-scale Fe oxide and the development of a technique for applying the Fe oxide to both conducting glass and conducting polymer substrates. Testing was also performed on each of the coatings for photocatalytic activity and electrolyte compatibility using solar simulation test equipment.

Additional work in the development of a tandem cell was also performed. The cell is based on enhancement of electron-hole separation and propagation of electro potential through a stack of anodic materials consisting of photo sensitive materials and multi junctions. The tandem cells were developed and tested on an actual solar dish located

at UNLV. Based on availability of continuing funding for this tandem cell, field trial tests will continue to study durability and performance.

This grant also funded the acquisition of a replacement electron analyzer in an existing ultra-high vacuum apparatus located within the UNLV College of Science which is devoted to the study of surfaces and interfaces in photo-electrochemical (PEC) devices. The XPS-UPS equipment was designed, purchased and installed and is operational. This equipment provided for the utilization of a world-wide unique combination of surface and interface spectroscopies to aid in the development of thin films for efficient hydrogen-producing photoelectrochemical (PEC) devices.

Continuing support for the filling station and vehicle development and maintenance was also addressed under this objective.

Summary of Project Activities:

1. Development of a Hydrogen Filling Station at the Las Vegas Valley Water District

The hydrogen fueling station at Las Vegas Valley Water District (LVVWD) is an operating fueling station which generates hydrogen fuel from renewable energy resources. The station, which provides fuel for all types of hydrogen powered vehicles, has undergone three different phases during its tenure. The station has been in operation since spring 2007 and was originally developed with equipment from the first two phases. Initially, the Phase I and II equipment generated just 2 kg H₂/day. The Las Vegas Valley Water District and the Southern Nevada Water Authority provided the solar panels and installation for the station. The station was retrofitted with new Phase III equipment in October 2007 and currently generates over 13 kg H₂/day. The physical size, power consumption and capital cost per kg of H₂ have been reduced significantly between the initial kickoff and the final configuration. Additional storage paid for and installed by the LVVWD will be extremely valuable when additional hydrogen-powered vehicles are added to the vehicle fleet. There have been minimal operational issues and the station continues to serve the end customer. The LVVWD has now assumed all costs associated with the operation and maintenance of the station. UNLV-CER has been monitoring hydrogen production and use and has the right to use the station for research purposes after the completion of this grant. The reports can be accessed at: <http://www.cer.unlv.edu/cer/Research/Systems/HydrogenFillingStation/tabid/340/Default.aspx>

Several key insights were gained from the project, particularly in the high pressure electrolysis phase. The original H₂/water separator design was oriented such that issues occurred due to water entrainment. The integrated separator also made the volume difficult to adjust. It was discovered that the shape and volume of head space is key even at low flow. Further Proton IR&D has explored low cost pressure vessel alternatives that look promising for future projects. In addition, the desired generation pressure for Phase II was not achieved, due to insufficient sealing area. The next phase of high pressure development at Proton will incorporate these insights. Success of these installations depends on cooperation and vested interest in the safety of people and property by all parties.

The complete final report on the development of the hydrogen filling station is included as Attachment 1.

Picture 1. Completed Solar Powered Hydrogen Filling Station Located at the Las Vegas Valley Water District

Picture 2. Vehicle Fueling Demonstration During the Grand Opening April, 2007

2. Hydrogen Vehicle Development and Integration

The object of this phase of the work was to develop three hydrogen-fueled vehicles. Initially a Taylor-Dunn Electrotruk Model ET-150-72 was converted to be a fuel-cell-electric hybrid vehicle. This type of vehicle is considered as a burden carrier or personnel carrier for manufacturing plants looking to haul goods throughout warehouses and plants. This operated quite remarkably for a period of time. However, at one point some modifications of a minor nature were being performed on the vehicle by the Water District personnel and an electrical short was experienced on the fuel cell. As a result of that, it appeared that the fuel cell lost the functionality of one of the cells in the stack. Attempts to find a replacement part through the manufacturer have not been totally successful. The manufacturer claims the unit has been deleted from its offerings and no parts are available for it. Recently we have made some progress with the manufacturer,

and they are now offering some assistance with repairs. We are following up with this possibility. In general, with the exception of the loss of one of the cells and the repairs this requires, the vehicle has performed quite nicely.

A Polaris Ranger was modified to burn hydrogen fuel. In accomplishing this modification, two major efforts were expended. The lesser of the two involved removing the gasoline tank and replacing it with a high-pressure hydrogen storage tank. The other issued involved the conversion of the engine to burn hydrogen. The vehicle is currently being used at the LVVWD and has been running without any problems. UNLV-CER will continue to monitor the vehicle for any changes in performance and make adjustments accordingly. It seems that a major issue with the vehicle is its short range. UNLV-CER is investigating the possibility of adding an additional fuel tank which would double the vehicle's range. However, both the cost of the new tank as well as limited space on the vehicle has influenced this thrust.

Finally a Ford V-8 pickup with ICE was converted to hydrogen. This vehicle is incorporated with a combination fuel injector and spark plug that replaces a conventional spark plug unit and port injection. All of the elements of the vehicle have been competed (including, for example, the fuel storage and delivery system), but the sparking injector has not. It appears that a new design of injector-spark plug unit may solve the problem of a complicated modification procedure that will allow both injection and spark to be accomplished through the same penetration in the engine head. This will greatly simplify the conversion process from gasoline to hydrogen. An early design worked fairly well, but suffered from lifetime problems. Modifications to design lend a great deal of hop that an inexpensive and very functional direct cylinder application will be a reality. The final parts for the new injectors were completed in late December 2009. The next step is to install the new injectors and relocate the necessary parts in order to get the vehicle moving. Once that is complete a proper tune for the Ford will be implemented as well as a data log of performance throughout the process. Although this award ended as of December 31, 2009, UNLV-CER has committed additional funding to complete the work on this vehicle. Once all work is complete the vehicle will be placed in the LVVWD's fleet and continued monitoring will be conducted.

Picture 3. The Taylor-Dunn electric vehicle converted to a hydrogen-electric fuel cell vehicle.

Picture 4. The Polaris Ranger ICE vehicle that was converted to burn hydrogen

Picture 5. The Ford V-8 pickup that was converted to a hydrogen ICE vehicle

The complete technical report on the development and monitoring of these three vehicles can be found in Attachment 2: “Final Report UNLV Vehicle Development Work for the Hydrogen Filling Station.”

3. Hydrogen Safety – Deployment and Risk Management Workshop

In order for the development of the Hydrogen Filling Station to be successful and other hydrogen projects to advance, it was essential that all individuals involved in furthering a hydrogen economy in Southern Nevada be involved and educated in areas relating to hydrogen safety. As a result, a hydrogen safety workshop was held on the UNLV campus on April 10, 2006. Over 30 professionals from eleven states attended the day-long event. Dr. Steven Weiner spoke and participated on behalf of the DOE Hydrogen

program. Representatives from the Clark County Fire Department, the Nevada State Energy Office, the Las Vegas Valley Water district and the City of Las Vegas engaged technical experts who presented hydrogen energy information.

This workshop was a forum for technical and operational experts to share information and perspectives on hydrogen safety and risk management. The major themes that emerged were:

- Hydrogen is safer than gasoline as a transportation fuel.
- The codes and standards affecting hydrogen deployment incorporate a significant cost and time to compliance risk that must be addressed.
- The technology to implement hydrogen energy safely is available, but must be integrated in a manner that incorporates past experience.

4. Development of a Roadmap for Hydrogen Development in Nevada

This project recognized the need for a strategic plan or roadmap for Nevada's alternative/renewable energy future. As a result, a roadmapping session was conducted at UNLV on June 20, 2006. The purpose of the session was to focus on integrating Nevada's combined potential into an approach that had milestones and clearly identified options for policy and stakeholder review. The scope of the session was limited to Nevada and its role within the southwest region. The Nevada State Energy Office was an active participant during the entire forum as well as representatives from the DOE, DOE contractors, LANL, NETL, NREL and leadership from the National Hydrogen Association Board of Directors.

Components of the session were:

- State H2 Readiness Survey
- Industry Posture & Plans Analysis
- H2 Chain Gap & Risk Inventory
- Creation of Likely Transition Scenarios
- Implementation Cost Analyses including the least expensive, second least expensive, second most expensive and most expensive to Nevada scenarios
- Risks and Barriers Identification and Analyses in areas such as technology, supply base, codes and standards, inadequate risk transfer, transition complexity, time to impact, lack of customer champion, bad information, logistics, configuration and installation, costs, too many cooks, wrong leaders, creating a formal coalition, and hydrogen safety
- Survey of On-going Government Activities
- Facilitating Roadmapping Forum with Stakeholders

The key issues that were addressed were:

- Where are we today?
- Why do we want to move toward hydrogen?
- What implementation of hydrogen do we want?
- What are Nevada's objectives?
- Can Nevada attain a useful role even without consensus?
- How much time until Nevada enjoys the benefits?
- Does Nevada have the resources now to push hydrogen?
- Will hydrogen serve us for a long time?
- What specific policies will help hydrogen in Nevada?

The primary conclusion by the participants of the session was that the roadmap should be adapted and championed by a public/private partnership that could be a non-profit corporation lead by a board with divergent interests and backgrounds. It is hoped that the results of this session will become a tool that is used by other roadmapping efforts in the hydrogen community. The states of Texas, South Carolina, Pennsylvania and West Virginia have expressed interest in this approach.

A copy of the final report entitled: "Hydrogen Roadmap Document" prepared by David Haberman of IF, LLC. is included as Attachment 3.

5. Photoelectrochemistry (PEC)

A team was formed that included Hydrogen Solar, Ltd., Altair Nanotechnologies, Inc., the University of Nevada, Las Vegas and the National Renewable Energy Laboratory to pursue research dedicated to the discovery, characterization, test and evaluation of thin film photocatalysts using oxides of iron, titanium and tungsten. Photoelectron spectroscopy, inverse photoemission, and soft x-ray absorption and emission spectroscopy was used to quantify the electronic properties of electrode materials and their interfaces as well as establishing the electronic and chemical structures of electrode interfaces.

In project period beginning 2006/2007 it was determined that the PEC work performed under the HFS project would be integrated with another set of participants under the technical leadership of the University of Hawaii that is pursuing related work. The effort at the University of Hawaii, also under the management of the UNLV Research Foundation, includes participants MV Systems, Inc., Intermatix Corp., the Southwest Research Institute, Duquesne University and the National Renewable Energy Laboratory. It was determined that integration of these two efforts would provide economies of common effort. Therefore the work summarized below reflects the work effort prior to the integration. Continuing PEC work has been reported under the award DE-FG36-03GO13062.

HYDROGEN SOLAR:

Hydrogen Solar worked with UNLV's Department of Chemistry to provide technical assistance and data collection for PEC cell counter electrode development work.

Engineering work with UNLV's Department of Mechanical Engineering was very active. Following is a summary of accomplishments. A detailed technical description of work performed is included in Attachment 5.

- Defined critical cell working parameters including chemical reactions at electrode surfaces, boundary layer conditions, thermal effects, heat and mass transfer and fluid flow characteristics.
- Provided cell working data to assist with modeling critical parameters.
- Provided current details on cell and pipe sizes to assist with modeling.
- Investigated components including electrolyte and material selection.
- Optimized CFD model to determine characteristics of velocity, porosity and pipe diameter modifications.
- Refined the model further to determine temperature gradients and effects of boundary layer conditions and mass/thermal transport.
- Investigated the kinetics of exchange of electrode/electrolyte and electrolyte/membrane interfaces.
- Prepared PEC cells from current materials for individual/dual cell testing at the solar dish site.
- Attempted to define requirements for balance of plant including electrolyte recirculation and monitoring, temperature control (heat sink), gas collection, handling and storage.
- Worked on test parameters including monitoring of water levels, pH, temperature, photocurrent density and gas generation.
- Studied balance of cell systems to manage electrolytes, collect, condition and store hydrogen and manage heat from solar gain.
- Developed a prototype system including balance of plant for installing PEC cells.
- Measured hydrogen generation efficiency in field trials using 4" x 4", 6" x 12" and 10" x 10" PEC cells.

Due to various financial and management reasons, Hydrogen Solar closed their business and all of the equipment that was purchased by Hydrogen Solar for this project was transferred to UNLV. The equipment is being used by UNLV for related research projects.

UNLV-CER:

Fundamental PEC work was performed by UNLV-CER on the development on an on-sun testing device. The testing of PEC type devices under real world conditions is a necessary step in making hydrogen production economically viable. This research determined the effects of various input parameters on the photocurrent produced by cells using a WO₃ type photoanode. The experiments were run on-sun at near Am 1.5 conditions.

To facilitate the on-sun testing, it was first necessary to construct a test platform which would allow for the control and measurement of key parameters. The system was installed on the roof of the Thomas Beam Engineering building and consisted of a climate-controlled instrumentation/control shack a tracking unit including its peripherals. This is shown below.

Picture 6. On-Sun Testing Facility Installed on Roof of UNLV Building

Cells were designed to allow testing of various photoanodes. The finished cells were constructed of $\frac{3}{4}$ " cpvc sheets. The single inlet and outlet were branched into 12 fitting manifolds to provide uniform flow over the anode and cathode. Anode to cathode spacing was varied using spacers of different thicknesses. The proton exchange membrane was held under tension using 316ss clips. The tension ensured that the membrane remained flat against the platinum mesh cathode material. The method of securing the membrane has many advantages over the heat press method previously investigated.

The test facility was designed and constructed. The instrumentation and control systems were tested and were fully functional. The cells were tested on sun and were dimensionally stable under temperature and pressure and did not leak. In addition, the two test units were well matched in internal resistance as well as open circuit voltage. This work was one of the first efforts at on-sun precision evaluation of one of these types of cells.

ALTAIR NANOMATERIALS:

The Altair team focused on the development of an iron oxide film as one promising electrode material for use in a water-splitting solar cell system. It is well documented that thin films of the hematite phase of iron oxide are semiconducting and photocatalytically active. Hematite's stability against dissolution at $\text{pH} > 4$ and the fact that over 30% of visible light has energies greater than the accepted band gap of 2.2 eV have prompted numerous investigations into its use as a photoanode for electrochemical hydrogen production. Thin films of oriented needles or platelets on a conducting glass substrate were found to have better photo-current efficiency than thin films of sintered hematite particles. Additionally, the incident photon to current conversion efficiency doubles as electrolyte pH is raised from 6.8 to 12.0. The photocatalytic properties of hematite have been improved by p-type dopants, such as aluminum, gallium, and indium, which introduce additional holes to the semiconductor and thus enhance conductivity.

The ideal photoanode structure has been determined to consist of several layers of iron oxide crystallites, having a platelet morphology, with an individual thickness of 5-10 nm. This embodiment provides at least one short dimension to cope with the very short electron-hole diffusion lengths in Fe_2O_3 ($\approx 4\text{-}5$ nm), which can be further improved with p-type doping. The total film thickness should be less than 60 nm to accommodate the requirements of the tandem cell design. That is, the front cell (photoanode) coatings of hematite must be deposited thin enough to allow the unabsorbed longer wavelengths of light to pass through to a back cell so that an electric current may be generated to drive the hydrogen and oxygen evolving reactions.

The Altair team was assigned several tasks directed at the development of an iron oxide film suitable for the front electrode of the PEC hydrogen-generating cell. The tasks are listed below:

1. Determination and selection of a synthesis route for nano-scale Fe oxide (20-100nm)
2. Development of a deposition technique for applying the Fe oxide to both conducting glass and conducting polymer substrates
3. Testing of the Fe oxide coating for photocatalytic activity (PCA) using solar simulation test equipment and other characterizations
4. Optimization of the PCA of the Fe oxide coating through doping, coating, particle morphology adjustment, etc.
5. Testing of the Fe oxide coatings for electrolyte compatibility
6. Develop 2 cm x 1 cm ferric oxide-coated glass electrode producing $\sim 3 \text{ mA/cm}^2$ under 1 sun illumination in a suitable electrolyte ($2 < \text{pH} < 12$)
7. Develop flexible conducting substrate materials development for scaled-up electrodes with potential for economical volume production

During the time the Altair team was engaged in this project, they completed Tasks 1 through 5. Details of investigative results are included in the Final Progress Report submitted by Altair Nanotechnologies, Inc., dated September 23, 2008 included as Attachment 6.

The goal of Task 6 was not achieved, i.e. a photocurrent of 3 mA/cm² under 1 sun illumination was not achieved. Currents of nearly 1 mA/cm² were achieved.

Task 7 was not pursued by the Altair team. The results of basic research (Tasks 1 through 5) on the iron oxide films did not warrant any effort spent on this “downstream” development activity.

UNLV CHEMISTRY DEPARTMENT:

This project included funding for equipment which benefited three UNLVRF grant-funded projects for which PEC research was a component of the project. Funding for this equipment was split between these three projects. The equipment replaced an electron analyzer in an existing ultra-high vacuum apparatus located within the UNLV College of Science which is devoted to the study of surfaces and interfaces in photo-electrochemical (PEC) devices. The equipment was deemed essential to the quality of on-going and proposed research in the area of photoelectric chemistry. Development of high-efficiency PEC systems to produce hydrogen directly from water, using only sunlight as the energy source, is a major goal of the DOE Hydrogen Program, and these UNLV-University of Hawaii projects are focused on that goal.

Tasks included the design, procurement, installation and testing of the XPS/UPS equipment at UNLV. The machine has been up and operating and is being used for PEC research at UNLV.

NREL:

NREL's work involved the application of theory, synthesis and characterization toward the use of metal oxide thin-films for photoelectrochemical water splitting. NREL worked together with Hydrogen Solar, Altair Nanomaterials and the UNLV Chemistry Department to optimize PEC performance by catalyzing or chemically modifying their surface and/or evaluation of alternative copants (?) improve electrode degradation and PEC performance. Their objective was to identify, synthesize and characterize designed photoelectrode materials that provided tunable enhanced light absorption and increased catalytic activity for water splitting in order to meet the DOE targets for PEC hydrogen production. For a technical description of work performed and theories, please see Attachment 4.

6. Research for Higher Efficiency PEM Technology

PEM electrolysis for onsite generation of hydrogen from water has been shown to be a clean, attractive alternative to delivered hydrogen for certain applications such as generator cooling, metals heat treatment, semiconductor processing and analytical instrumentation. However, to compete long term as a backup power and fueling option, the electrolyzer cost needs to be reduced. One method of decreasing cost is to increase efficiency, so that the production rate is increased for the same quantities of catalyst and membrane. Another method is through decreasing the capital cost of the components.

Several areas of opportunity were identified as part of this program. The overall goal of this program was to conduct fundamental research to improve the cost, efficiency, and durability of proton exchange membrane (PEM) electrolysis. Additional activities associated with the design, development, and commissioning of a hydrogen filling station are summarized in a separate report.ⁱ Significant work was accomplished to advance understanding of PEM electrolysis and provide direction for improved efficiency and durability. A large active area test stand and prototype large active area parts were also fabricated in order to begin proving feasibility of larger units in order to decrease the cost of hydrogen in \$/kg.

One subset of research tasks revolved around optimization of the membrane electrode assembly (MEA) materials. Catalyst and membrane materials were evaluated vs. the baseline construction and optimized combinations were designed. Fundamental characterization was also performed in order to correlate physical properties with stack performance for better predictability of performance in the future and determine which bench tests were important to incorporate into future screening efforts. Strength and brittleness of the membranes were key issues. The ionic resistance of the cell did not correlate as expected with the membrane thickness of some of the membranes, indicating that either 1) the processing caused significant material changes, 2) equivalent weight had a major impact, or 3) there is another parameter that was not accounted for. Electrochemical screening tests were developed for the catalysts which did show good correlation with initial cell stack voltage, and trends were seen for different metals which provide insight for future catalyst development. The optimal membrane generated approximately 9% improvement in efficiency vs. the baseline, while the optimal catalyst showed a 5% efficiency improvement. The optimal membrane/catalyst combination did not yield a linear combination of the two components, providing about a 10% improvement in efficiency.

Another subset of research tasks involved scale up of the cell stack to a larger active area, including a test stand with capability for large cell testing. One aspect of scale up was to optimize the bipolar plate design, including computational fluid dynamics modeling in order to compare flow distribution and thermal profiles in various designs. Modeling of the large active area bipolar plate design demonstrated improved flow characteristics and uniform temperature gradients vs. the baseline bipolar plate. Large active area cell stack parts were procured and prototype MEAs were fabricated. The fabricated parts were tested and found to be within specification. Possible techniques for manufacturing the bipolar plates were also investigated. Alternate techniques for forming the plates which are recommended for further study include chemical milling, stamping, and vertical milling or machining. These techniques had good tolerance control with reasonable removal rates and lower capital cost than techniques such as laser machining.

Key technical issues associated with the renewable energy interface for PEM electrolyzers were also evaluated. The results of the integration simulations showed that power conversion efficiency for electrolysis can be improved to 95% or better for both direct interface with renewable sources or using the grid as an interconnection. At present and into the near future, the off-grid approach to hydrogen generation is not favorable for large scale hydrogen generation due to the capital cost of PEM based hydrogen generation. The RE-Grid Fixed Capacity hydrogen generator is therefore the most economical approach. Other areas of improvement include optimizing the system

as a whole to determine the optimum cell stack temperature, pressure, and operating current density.

The final task incorporated the work from all these areas into a newly developed electrochemical model to translate the impact of these studies on cost of hydrogen in \$/kg. The model showed that significant cost savings are achievable through implementation of the recommendations included in previous subtask reports and enables projections for future cell stack and system improvements. Incorporation of the above work into the H2A model projects a cost savings of over 50% in \$/kg hydrogen vs. the baseline cost as all the proposed advancements are further proven out and progressed to commercialization. Based on the work accomplished in this program, additional improvements in catalyst performance are possible by continuing to optimize the synthesis conditions and composition. These improvements could enable lower catalyst loadings, decreasing cost. Optimizing the membrane properties based on the information gained is another area of opportunity. Processing changes and changes in surface treatment of stack parts also show promise. These areas have been proposed for further collaboration with UNLV in a follow-on program.

Detailed reports relating to the PEC research including MEA characterization test results, experimental catalyst characterization test results, PEM electrolysis membrane candidates and PEM electrolysis catalyst candidates can be found in Attachments 7, 8, 9 and 10.

PRODUCTS DEVELOPMENT AND TECHNOLOGY TRANSFER ACTIVITIES:

a. Publications/Presentations

- A. Walsh, S.-H. Wei, Y. Yan, M.M. Al-Jassim, J. Turner, M. Woodhouse, and B.A. Parkinson, "Structural, magnetic, and electronic properties of the Co-Fe-Al oxide spinel system: Density-functional theory calculations" *Phys. Rev. B* 76, 165119 (2007).
- C. K. Halford and R. F. Boehm, "On-sun evaluation of photocatalytic generation of hydrogen," NHA Annual Hydrogen Conference 2007. San Antonio, TX
- E. Anderson, J. Friedman, J. Manco, and K. Ayers, "Development of Advanced MEA's for PEM Water Electrolysis," Chapter 15 in Fuel Cells Durability and Performance, 3rd Edition, The Knowledge Press, Inc., Brookline, MA, 2008.
- E.B. Anderson, K.E. Ayers, J. Manco, and E. Styche, "Development of Advanced Catalysts for PEM Water Electrolysis," presented at Hydrogen 2008: Materials Innovations in An Emerging Hydrogen Economy, Cocoa Beach, FL, February 24-27, 2008.
- J. Gardner, R. Fifield, R. Hurt, Y. Baghzouz, and R. F. Boehm, "Design, application, and evaluation of a fuel cell vehicle," NHA Annual Hydrogen Conference 2007. San Antonio, TX.

- J. H. Nie, S. P. Katukota, Y. T. Chen, R. F. Boehm and H. T. Hsieh, "A photo-electrochemical model of solid polymer water electrolysis for hydrogen production from sunlight," Proceedings of 1st Energy Nanotechnology International Conference, ENIC2006-19039, Massachusetts Institute of Technology (MIT), Cambridge, MA, USA, June 26-28, 2006.
- J. H. Nie, Y. T. Chen, K. M. Veepuri, S. Cohen, and R. F. Boehm, "Three-dimensional CFD modeling of bipolar plate PEM electrolysis cell for hydrogen production," FuelCell2007-25308, Fifth International Fuel Cell Science, Engineering & Technology Conference, June 18-20, 2007, New York, NY.
- J. H. Nie, Y. T. Chen, R. F. Boehm, and S. P. Katukota, "A photoelectrochemical model of solid polymer water electrolysis for hydrogen production," *Journal of Heat Transfer – Transactions of the ASME*, 130, 2008, 042409.
- J. H. Nie, Y. T. Chen, S. Cohen, and R. F. Boehm, "Effects of channel layout on three-dimensional convection flow in bipolar plate PEM electrolysis cell," IMECE2007-42360, ASME International Mechanical Engineering Congress and Exposition (IMECE 2007), November 10-16, 2007, Seattle, WA.
- J. H. Nie, Y. T. Chen, S. Cohen, and R. F. Boehm, "Non-uniform velocity distributions in bipolar plate PEM electrolysis cell," FEDSM2007-37299, 10th International Symposium on Gas-Liquid Two-Phase Flows, 5th Joint ASME/JSME Fluids Engineering Conference, July 30-August 2, 2007, San Diego, CA.
- J. H. Nie, Yitung Chen, Steve Cohen, Blake Carter, and Robert F. Boehm, "Non-uniform velocity distributions in bipolar plate PEM electrolysis cell," Proceedings of 5th Joint ASME/JSME Fluids Engineering Conference, FEDSM2007-37299, July 30 - August 2, San Diego, California, USA, 2007
- J. H. Nie, Yitung Chen, Steve Cohen, Blake Carter, and Robert F. Boehm, "Three-dimensional CFD modeling of bipolar plate PEM electrolysis cell for hydrogen production," Proceedings of Fifth International Conference on Fuel Cell Science, Engineering and Technology, FuelCell2007-25308, June 18 - 20, New York, NY, 2007
- Jianfei Wu, Jianhu Nie, and Yitung Chen, "Numerical simulations of three-dimensional fluid flow and coupled heat transfer in bipolar plates," Proceedings of 5th Joint ASME/JSME Fluids Engineering Conference, FEDSM2007-37712, July 30 - August 2, San Diego, California, USA, 2007
- Jianfei Wu, Jianhu Nie, and Yitung Chen, "Three-dimensional fluid flow and coupled heat transfer in simplified bipolar plates," Proceedings of ASME International Mechanical Engineering Congress and Exposition (IMECE 2007), IMECE2007-42360, November 11-15, Seattle, WA, USA, 2007
- Jianhu Nie, Yitung Chen, Steve Cohen, Blake Carter, and Robert F. Boehm, "Velocity and temperature distributions in bipolar plate of PEM electrolysis cell," Proceedings of ASME International Mechanical Engineering Congress and

Exposition (IMECE 2007), IMECE2007-42622, November 11-15, Seattle, WA, USA, 2007

- K. Ayers, E. Anderson, J. Friedman, J. Manco, E. Styche & C. Capuano, "Development of Advanced MEA's for PEM Water Electrolysis," presented at the 2008 Electrochemistry Gordon Research Conference, Ventura, CA, January 6-11, 2008.
- K. M. Veepuri, J. H. Nie, S. Cohen, Y. T. Chen, and R. F. Boehm, "Velocity and temperature distributions in bipolar plate of PEM electrolysis cell," IMECE2007-42622, ASME International Mechanical Engineering Congress and Exposition (IMECE 2007), November 10-16, 2007, Seattle, WA.A (submitted)
- K.-S. Ahn, T. Deutsch, Y. Yan, C.-S. Jiang, C. L. Perkins, J. Turner, and M. Al-Jassim "Synthesis of band-gap-reduced *p*-type ZnO films by Cu incorporation" *J. Appl. Phys.* **102**, 023517 (2007)
- K.-S. Ahn, Y. Yan, and M. Al-Jassim, "Band gap narrowing of ZnO:N films by varying rf sputtering power in O₂/N₂ mixture" *J. Vac. Sci. Technol. B* **25**, L23 (2007)
- K.-S. Ahn, Y. Yan, S.-H. Lee, T. Deutsch, J. Turner, C. E. Tracy, C. L. Perkins, and M. Al-Jassim "Photoelectrochemical Properties of N-Incorporated ZnO Films Deposited by Reactive RF Magnetron Sputtering" *J. Electrochemical Society*, **154** B956-B959 (2007).
- Kwang-Soon Ahn, Sudhakar Shet, Todd Deutsch, Chun-Sheng Jiang, Yanfa Yan, Mowafak Al-Jassim, John Turner "Enhancement of photoelectrochemical response by aligned nanorods in ZnO thin films" *J. Power Sources* (2007).
- Kwang-Soon Ahn, Yanfa Yan, Sudhakar Shet, Todd Deutsch John Turner, and Mowafak Al-Jassim "Enhanced photoelectrochemical responses of ZnO films through Ga and N codoping" *Appl. Phys. Lett.* **91**, 231909 (007).
- M. Campbell, R. Hurt, S. Sadineni and R. Boehm, *A Solar Powered Hydrogen Generation and Filling Station*, Proceedings of the 37th ASES Annual Conference, May 3-8, San Diego, CA, 2008
- Mark Campbell, Sachin Deshmukh, Rick Hurt, Robert Boehm, *Modeling Solar Impacts on Hydrogen Production from Electrolysis*, ASME 2nd International Conference on Energy Sustainability, Aug 10-14, Jacksonville, FL, 2008
- Mauldin R., Hurt R., Baghzouz Y., Boehm R.F., "Light-weight fuel cell-battery hybrid vehicle demonstration project," SPEEDAM, Taormina Italy, May 22-26, 2006.
- Presentation: Embracing the New Era of Solar Hydrogen Production, Feb 2008

- R. Boehm, Y. Baghzouz, R. Hurt, R. Mauldin, E. Bulla, R. Fifield, J. Gardner, "Development of a renewably-based hydrogen generation/utilization system," Paper ISEC20006-99081, International Solar Energy Conference, 2006
- R. Fifield, J. Gardner, R. Boehm, T. Kell, *Use of Direct Cylinder Injection in Hydrogen Engine Conversions*, NHA Annual Hydrogen Conference 2007, March 19-21, 2007, San Antonio, TX
- R. Fifield, J. Gardner, R. F. Boehm, "Conversion and performance analysis of a small utility vehicle operating on hydrogen fuel," ASME Conference Proceedings, ASME Journal of Energy Resources Technology 2007, Hilton Long Beach, Ca. Paper No. ES2007-36106
- R. Fifield, J. Gardner, R. F. Boehm, T. Kell, "Use of direct cylinder injection in hydrogen engine conversions," NHA Annual Hydrogen Conference 2007. San Antonio, TX. Paper No. 3534
- Ronald Fifield, Julian Gardner, and Robert Boehm, "Conversion and performance analysis of a small utility vehicle operating on hydrogen fuel," Proceedings of ES 2007, June 2007, Long Beach.
- S. B. Sadineni, R. Hurt, C. K. Halford, R. F. Boehm, "Reclaiming electrolysis reject water with a solar still," Proceedings of ES2007. Long Beach, June 2007. ES2007-36001
- S. B. Sadineni, R. Hurt, C. K. Halford, R. F. Boehm, "Theory and experimental results for solar still operation," *Energy*, Volume 33, Issue 1, Jan 2008, pp. 71-80. Dec. 2006
- S. P. Katukota, J. H. Nie, Y. T. Chen and R. F. Boehm, "Numerical investigation for hydrogen production using proton exchange water electrolysis cell," COMSOL Multiphysics Conference, Las Vegas, NV, October 26-27, 2006.
- S. P. Katukota, J. H. Nie, Y. T. Chen, R. F. Boehm and H. T. Hsieh, "Numerical modeling of electrochemical process for hydrogen production from PEM electrolyzer cell," ES2007-36108, Energy Sustainability 2007, June 27-30, 2007, Long Beach, CA.
- S. S. Deshmukh and R. F. Boehm, "Mathematical modeling of solar-hydrogen system for residential applications", ASME, International Solar Energy Conference, Denver CO, 2006, ISEC2006-99061
- S. S. Deshmukh and R. F. Boehm, "Review of modeling details related to renewably powered hydrogen systems," *Renewable and Sustainable Energy Reviews*, Volume 12, Issue 9, 2008, pp. 2301-2330.
- S. S. Deshmukh, R. F. Boehm, "Mathematical modeling of performance of a grid connected solar-hydrogen system for residential applications. *J. of Energy and Climate Change*, vol. 1, no. 2, pp. 113 (2006)

- S. S. Deshmukh, Y. Baghzouz and R. F. Boehm, "Design of grid connected-PV system for a hydrogen refuelling station", ASME, International Solar Energy Conference, Denver CO, 2006, ISEC2006-99151
- Y. Baghzouz, M. Popek, R. F. Boehm, R. Hurt, "Hydrogen APU electrical system analysis and bootstrap charging method," NHA Annual Hydrogen Conference, San Antonio, TX, March 19-22, 2007 (Poster)
- Y. Baghzouz, R. Hurt, R.F. Boehm, "Evaluation of a fuel cell for powering the electric load of ICE vehicles," ICCEP, Capri, Italy, May 21-23, 2007
- Y. T. Chen, J. H. Nie, B. F. Armaly, H. T. Hsieh and R. F. Boehm, "Developing turbulent forced convection in two-dimensional duct," *Journal of Heat Transfer – Transactions of the ASME*, 129, 2007, 1295-1299.
- U.S. Navy Naval Facilities Engineering Command, Washington, D.C. – October, 2006
- Danish Secretary of Transport and Energy, Washington, D.C. – November, 2006
- District of Columbia Public Schools Science Department Chairs, Washington, D.C. – December, 2006
- NHA Annual Hydrogen Conference 2007, San Antonio, TX – March, 2007
- National Defense University, Washington, D.C. – March, 2007
- Alternative Fuels Conference, Anaheim, CA – April, 2007
- State of Virginia Department of Environmental Quality, Woodbridge, VA – April, 2007
- National Science Bowl, Bethesda, MD – April, 2007
- U.S. EPA Office of Administration and Resources Management, Washington, D.C. – May, 2007
- DOE Hydrogen Education Initiative at Shell Hydrogen Benning Road Station for Paul Public Charter School, Washington, D.C. – May 2007

b. Website/internet sites that reflect results of this project

UNLV-CER developed various systems to monitor the Hydrogen Filling Station. Data on production, usage, etc. can be accessed at:

<http://www.cer.unlv.edu/cer/Research/Systems/HydrogenFillingStation/tabid/340/Default.aspx>

c. Networks or collaborations fostered

Several collaborative efforts were fostered by this project. The relationship between UNLV and the LVVWD was enhanced with the LVVWD contributing a great deal of cost share and infrastructure (including the solar panels and installation) to help make this project successful. The display on hydrogen fuel that is housed within their Springs Preserve will help to educate the public on the benefits of the “fuel of the future” and help people understand how hydrogen can be utilized to make their homes and cars more efficient and economical.

The PEC work that was performed under this project was integrated with another research project with related work in the period beginning 2006/2007. This action encouraged collaboration with another set of participants under the technical leadership of the University of Hawaii, also under the management of the UNLV Research Foundation and included MV Systems, Inc., InterMatrix Corp., the Southwest Research Institute, Duquesne University and the National Renewable Energy Laboratory. It was determined that integration of these two efforts would provide economies of common effort.

d. Inventions/Patent Applications

Following are the patents that have been filed by participants in this project:

- Proton Energy Systems

System for Dispensing Hydrogen to a Vehicle – A. Kahn, T.M. Maloney, L.C. Moulthrop, M.T. Kowalski and E.J. White – Reported 11/10/2005 – DOE “S” No. 109,467

Gas Venting System – A. Kahn, K.W. Dreier, L.C. Moulthrop and E.J. White – Reported 11/18/2005 – DOE “S” No. 109,468

- Hydrogen Solar LLC

Layer-alternated Anodic Photo Electrodes – Xiaoming He – Reported 1/2006 - DOE “S” No. Research Plan

Photo Electro Anodes Incorporating Dielectric Materials – Xiaoming He – Reported 5/2006 – DOE “S” No. DC PEC Report

Photo Electro Chemical Cell Applying SPE – Xiaoming He – Reported 1/2006 – DOE “S” No. Research Plan – Reported 12/2006 – DOE “S” No. Status Report

COMPUTER MODELING:

- A computer model was created for the Hydrogen Filling Station by UNLV-CER to simulate the energy production and use at the station, as well as how vehicle usage affects the energy and hydrogen balance at the station. The model's outputs included the total power produced by the solar PV array, the amount of hydrogen required by the vehicles, and the amount of energy required by the HFS equipment to refill the tanks at the station. Also, the hydrogen level inside the storage tanks was modeled, to determine the amount of time the station required to return to full capacity after a vehicle was filled. The model's results as shown below correlate well with the experimental data.

Required Hydrogen production	1292.1 kg
Solar Energy Production	34.39 MWh
Solar contribution to Hydrogen Production	33.34%
Hydrogen Produced from Solar energy	430.87 kg
Hydrogen Generation/Compression Efficiency (HHV)	49.3%
Tim Required to Refill Dispenser	2.84 hrs

- Modeling was performed by UNLV-CER to develop a better understanding of electrolyzers. Two sets of CFD studies were performed in this work, and numerical models were developed for each. The first one was a 3D CFD study to obtain nearly uniform flow throughout the flow field. The second involved a 2D CFD study to model the multi-physics of the PEM electrolyzer cell. A description of the work performed follows.

Various types of flow fields have been proposed in the literature and used for improving the transport of species inside an electrolyzer or a fuel cell. The simplest one is being the straight channel flow field and more complicated ones include bio mimicked flow fields. Not many studies have been published on the effects of flow field and its effect on the performance of the electrolyzer. The straight channel type flow field was considered for this work based of simplicity of design. It is more reasonable to start from a simple design and then move to complicated one after good comparison between experimental and numerical model is achieved for the simple design.

Figure 1. Initial design of straight channel flow field

Figure 2 Initial CFD domain of the straight channel flow field

The simple straight channel flow field design is shown in Fig 1. A 3-D CFD model was used to analyze the effect of variation in inlet channel design on the velocity profiles in the straight channels. Fig 2 shows the computational domain of the straight channel flow field.

An assumption was made that the effect of hydrogen and oxygen on the bulk water flow is very small and can be neglected for this analysis. A key reason for this assumption besides its simplifying nature is that the mass and volume fractions of hydrogen and oxygen are very small as compared to water and hence can be neglected for this qualitative analysis. Also due care is taken to assure that the final design should not be complicated and provide dimensional constraints while machining and hence the design is more practical from manufacturing standpoint.

The governing equations for this model are the continuity (equation 1) and momentum (equation 2) equations including the effect of gravity.

$$\nabla \cdot (\rho \vec{v}) = 0 \quad (1)$$

$$\nabla \cdot (\rho \vec{v} \vec{v}) = -\nabla p + \nabla \cdot (\mu \nabla \vec{v}) + \rho \vec{g} \quad (2)$$

The boundary conditions are based upon the velocity at the inlet and outlet. The Reynolds number for the flow rate of 590 mlpm is 1379 (laminar region) at the inlet pipe. For this flow conditions, 3D CFD analysis was performed to obtain the velocity profile inside the flow field. Figs 3 and 4 show the final flow field and CFD flow domain respectively. Further grid independency analysis was performed to make sure the grid size has minimum or no effect on the solution.

Figure 3 Final design of straight channel flow field after CFD analysis

Figure 4 Final CFD domain of the modified straight channel flow field design

CFD model for the PEM electrolyzer

This section provides the details of the CFD model of the PEM water electrolyzer cell. As mentioned before not much work has been done on the CFD modeling of the PEM electrolyzer. It has been a challenge to put together the basic modeling procedure and equations. As a simplified approach, 2D modeling has been performed in this work which can be extended to 3D for industrial applications. This type of tool is particularly valuable to improve the flow physics inside the electrolyzer. Note that this work doesn't contain modeling at the molecular level which can provide the information of reaction kinetics at the interface of catalyst, water and PEM.

The CFD model provides a resolution of the modeling aspects at the macroscopic level inside the PEM electrolyzer cell. The mass, momentum, multiphase, energy and electrostatics (charge transport (protonic and electronic)) equations completely describes the multi-physics of the PEM electrolyzer.

The multiphase equations were used to describe the transport of water (liquid), hydrogen (gas) and oxygen (gas) inside the flow field. Since the multiphase equations are based on volume fraction which is higher on order of magnitude basis as compared to species transport equation that are based on the mass fraction. For example, if water flow rate of 295 mlpm is electrolyzed at 12.5 A in a 25 cm² cell (current density 500 mA/cm²) the volume fraction of hydrogen and oxygen are estimated to be 0.324 and 0.16 respectively, whereas mass fractions for same situation are 0.000026 and 0.0002, respectively. This calculation was performed before making a decision on using a mass fraction or a volume fraction basis for the multi species flow solution inside the electrolyzer cell. Based on the calculations performed above, volume fractions basis was used for representing the multi species flow inside the electrolyzer. This approach is unique in a way that no evidence is found where the volume fraction method was used to solve the physics of PEM electrolyzer. Also the mass source terms are used in the catalyst layers to include for hydrogen and oxygen production and mass sink for water consumption in the anodic catalyst layer.

The electrochemical reaction can be modeled using a simplification of Maxwell's equations that describe electromagnetic fields. Only the electrostatic part of Maxwell's equation is solved to obtain the electrical potential and current density, for both electronic and protonic current, inside the catalyst layer and membrane as a function of heterogeneous reaction that takes place inside the catalyst layers. The reaction rate inside the catalyst layers can be modeled using Butler-Volmer kinetics or its simplified version in the Tafel equations. Since the Butler-Volmer term is a highly non-linear source term, the simplified Tafel equations are used in the current work to provide the model of the reaction rate.

The energy equation is solved to obtain the temperature distribution in the computational domain. It is particularly of interest to predict the temperature inside the membrane and catalyst layer when the electrolyzer operates at high temperature. This is because Nafion when operating beyond 110 °C can degrade or be damaged permanently. Hence, this can affect the lifetime of the PEM electrolyzer cell significantly. Also the heat source terms due to the ohmic losses and electric work are acting in the MEA region of the electrolyzer. The water flowing through the flow fields and porous layer acts as a coolant to remove the heat from the MEA region. Also since there is a porous region between the flow fields and MEA the cooling effect is dependent on the properties of the porous layer. If the porosity of the porous layer is fixed then the only way to cool the MEA region is by increasing the flow rate at the inlet of the cell.

Computational domain, governing equations and boundary conditions

The governing equations for modeling the PEM electrolyzer are provided in this section. Mass conservation for the mixture

$$\nabla \cdot (\rho_m \vec{v}_m) = 0 \quad (3)$$

where ρ_m is the mixture density and v_m is the mass averaged velocity that are given by

$$\vec{v}_m = \frac{\sum_{k=1}^n \alpha_k \rho_k \vec{v}_k}{\rho_m} \quad (4)$$

$$\rho_m = \sum_{k=1}^n \alpha_k \rho_k \quad (5)$$

Here α_m is the volume fraction of phase k.

Momentum equation for the mixture

$$\nabla \cdot (\rho_m \vec{v}_m \vec{v}_m) = -\nabla p + \nabla \cdot (\mu_m \nabla \vec{v}_m) + \rho_m \vec{g} + \nabla \cdot \left(\sum_{k=1}^n \alpha_k \rho_k \vec{v}_{dr,k} \vec{v}_{dr,k} \right) \quad (6)$$

where n is the number of phases and μ_m is the viscosity of the mixture

$$\mu_m = \sum_{k=1}^n \alpha_k \mu_k \quad (7)$$

$\vec{v}_{dr,k}$ is the drift velocity for the secondary phase k

$$\vec{v}_{dr,k} = \vec{v}_k - \vec{v}_m \quad (8)$$

Energy equation for the mixture

$$\nabla \cdot \sum_{k=1}^n (\alpha_k \vec{v}_k (\rho_k E_k + p)) = \nabla \cdot (k_{eff} \nabla T) + S_E \quad (9)$$

Where k_{eff} is the effective thermal conductivity and is given by

$$k_{eff} = \sum_{k=1}^n \alpha_k k_k \quad (10)$$

In the energy equation, E_k is given by

$$E_k = h_k - \frac{p}{\rho_k} + \frac{v_k^2}{2} \quad (11)$$

Where h_k is the sensible enthalpy for phase k. The S_E term in the energy equation is the source term that includes heat sources due the ohmic and electric

work terms. The heat sink term includes energy for phase change of water and entropy change.

$$S_E = I^2 R_{ohm} + \eta R_{an,cat} - \frac{T\Delta S}{nF} R_{an} - h_{phase} \quad (12)$$

Multiphase equation for secondary phase p is given by

$$\nabla \cdot (\alpha_p \rho_p \vec{v}_m) = -\nabla \cdot (\alpha_p \rho_p \vec{v}_{dr,p}) + \sum_{q=1}^n (\dot{m}_{qp} - \dot{m}_{pq}) \quad (13)$$

The homogeneous multiphase form of the mixture model is used to obtain the volume fraction of the different phases inside the cell. This implies that all phases move with same velocity and hence the relative velocity is zero between the primary and secondary phases. The drift velocity for the secondary phases is obtained from

$$\vec{v}_{dr,p} = -\sum_{k=1}^n (c_k \vec{v}_{qk}) \quad (14)$$

where c_k is mass fraction of phase k

$$c_k = \frac{\alpha_k \rho_k}{\rho_m} \quad (15)$$

Mass source terms for the primary and secondary phases that provide the effect of consumption of water and production of hydrogen and oxygen are given below.

$$S_{O_2} = -\frac{M_{w,O_2}}{4F} R_{an} \quad (16)$$

$$S_{O_2} = -\frac{M_{w,H_2}}{2F} R_{cat} \quad (17)$$

$$S_{H_2O} = -\frac{M_{w,H_2O}}{2F} R_{an} \quad (18)$$

The electrochemical reaction in the MEA can be described by electrostatic equations. Two potential equations are solved as a part of the PEM electrolyzer model. One accounts for the electronic charge transport and the other for protonic charge transport within the MEA.

$$\nabla \cdot (\sigma_e \nabla \phi_e) + S_\phi = 0 \quad (19)$$

$$\nabla \cdot (\sigma_p \nabla \phi_p) + S_\phi = 0 \quad (20)$$

where σ is the electrical conductivity (1/ohm-m), ϕ is the electric potential and S_ϕ is the volumetric transfer current (A/m³). The volumetric source terms for the electrostatic equations for the anode and cathode are given by the Butler-Volmer equations.

$$R_{an} = j_{an}^{ref} \left(e^{\alpha_{an} \frac{F}{RT} \eta_{an}} - e^{-\alpha_{cat} \frac{F}{RT} \eta_{an}} \right) \quad (21)$$

$$R_{cat} = j_{cat}^{ref} \left(-e^{\alpha_{an} \frac{F}{RT} \eta_{cat}} + e^{-\alpha_{cat} \frac{F}{RT} \eta_{cat}} \right) \quad (22)$$

Tafel equations for calculating the volumetric source terms are given by

$$R_{an} = j_{an}^{ref} \left(e^{\alpha_{an} \frac{F}{RT} \eta_{an}} \right) \quad (23)$$

$$R_{cat} = j_{cat}^{ref} \left(e^{-\alpha_{cat} \frac{F}{RT} \eta_{cat}} \right) \quad (24)$$

where η_{an} , η_{cat} are given by

$$\eta_{an} = \phi_e - \phi_p - V_{oc} \quad (25)$$

$$\eta_{cat} = \phi_e - \phi_p \quad (26)$$

It is very important to mention that the open circuit potential for fuel cell at the cathode, for the oxygen reduction, is significantly different from the Nernst equation as obtained from the experimental investigation reported in the literature. The most interesting finding was reported which showed an increase in magnitude of open circuit potential with temperature as opposed to that obtained from the Nernst equation. However there is no experimental evidence that the open circuit potential for oxygen evolution is different from the one obtained from the Nernst equation.

The boundary conditions used to obtain the closure for CFD model of PEM electrolyzer is described in this section. To have a proper comparison between the experimental and numerical work, special considerations to obtain the 2D boundary conditions from the actual experimental and 3D CFD studies are outlined.

Inlet boundary

Velocity boundary condition is used at the inlet for the momentum equation. Inlet temperature and volume fraction are specified for the energy and multiphase equation respectively. Note that the volume fractions for the H_2 and O_2 phase are zero and water phase volume fraction is 1 at the inlet. Also the velocity at the inlet is obtained from the 3D CFD model of the water flow only through the PEM electrolyzer. This is important as the 2D model is a simplified version of the actual 3D model.

Outlet boundary

The boundary condition at the outlet is pressure. Besides this, nothing has to be specified.

Wall boundary

A thermally insulated type boundary condition at the outer wall of the domain is specified. Current density is specified at the anode side wall and zero potential is specified at the cathode side wall for the electrostatic equation.

Figure 5. Boundary conditions for 2D CFD modeling of the PEM electrolyzer

Figure 6. Source and sink terms for multi-physics PEM electrolyzer model

Note that the current density obtained from the experimental work is 3D based and has to be modified to account for the 2D area before applying it to the 2D model. Figs 5 and 6 show the location of the boundary conditions and source terms in the 2D model. Also note that the mass, heat and current source terms are volume-based terms and have to be corrected from the experimental values for change in volume before they are applied to the 2D model.

		Other data			
Temperature	Density	Specific	Viscosity	Thermal	
K	kg/m ³	heat	N-s/m ²	conductivity	
		J/kg-K		W/m-K	
O₂					
298.95	1.288657	919.854	2.066E-05	0.02672619	
331.85	1.158236	925.271	2.242E-05	0.02874546	
H₂					
298.95	0.081072	14306.1	8.939E-06	0.1825054	
331.85	0.072896	14401.5	9.563E-06	0.19695508	
H₂O					
298.95	997.2186	4179.34	0.0008754	0.61161295	
331.85	983.5496	4184.74	0.0004757	0.65222	

CFD modeling procedure

The CFD modeling of the complex multi-physics of the PEM electrolyzer is very challenging. The performance of the PEM electrolyzer is at its core dependent upon the reaction kinetics occurring inside the catalyst layer at the tri-phase intersection of membrane, catalyst and water. Also equally important is transport of species (water, hydrogen and oxygen) to and from the catalyst layer from the bulk flow of water in the flow fields. The heterogeneous reaction is modeled using the Tafel equation in this report as a simplified version of Butler-Volmer equation. The procedure used to perform CFD modeling of PEM electrolyzer and compare that with the experimental results is outlined in this section.

1. 3D CFD modeling for one side of the cell is performed to compare the pressure drop obtained from the experiment for a given flow field, porous plate and MEA. The catalyst layer is assumed to be porous. The water flow without any electrolysis is considered for this model for consistency between the experiments performed for the pressure measurement.
2. Input velocity in the 2D model for the PEM electrolyzer is obtained from comparison of velocity between 2D and 3D CFD models for water flow only.
3. 3D to 2D conversions were performed for area and volume based quantities like current density and the volumetric current source, as there is a change in volume in the 2D model compared to the 3D model. This is due to the fact that in the 2D model the depth is considered as unity whereas in 3D model the depth is significantly less than 1 m for this design.

2D CFD multi-physics modeling of PEM electrolyzer is performed using inputs from the above mentioned considerations.

ATTACHMENT 1

DEVELOPMENT OF HYDROGEN FILLING STATION AT LAS VEGAS VALLEY WATER DISTRICT

PREPARED BY:

**PROTON ENERGY SYSTEMS
March 3, 2008**

DEVELOPMENT OF HYDROGEN FILLING STATION AT LAS VEGAS VALLY WATER DISTRICT

Final Report

Prepared by:

Proton Energy Systems
10 Technology Drive
Wallingford, CT 06492

3 March 2008

Prepared for:

University of Nevada Las Vegas Research Foundation
Under Subcontract No. RF-05-HFS-005-A03

Under U.S. Department of Energy, Golden Field Office
Contract No. DE-FG36-03GO13063

Table of Contents

1	Summary	3
2	Introduction.....	3
2.1	Phase I - 2kg/day Renewable Fueling Station	3
2.2	Phase II – Enhance Station w/ High Pressure Electrolysis Fueling.....	3
2.3	Phase III – 13kg/day Renewable Fueling Station	4
3	Approach:.....	4
3.1	Phase I - 2kg/day Renewable Fueling Station	4
3.2	Phase II – Enhance Station w/ High Pressure Electrolysis Fueling.....	7
3.3	Phase III – 13kg/day Renewable Fueling Station	8
4	Results and Discussion	11
4.1	Phase I - 2kg/day Renewable Fueling Station	11
4.2	Phase II – Enhance Station w/ High Pressure Electrolysis Fueling.....	11
4.3	Phase III – 13kg/day Renewable Fueling Station	12
5	Conclusions and Recommendations	12
6	References.....	13

Table of Figures

Figure 1: Phase I - P&ID	5
Figure 2: Phase I - Hydrogen Generator	5
Figure 3: H40RE inside Rittal Enclosure.....	5
Figure 4: Phase I - Equipment installed at Proton Energy Systems	6
Figure 5: Phase I - Equipment installed at LVVWD	6
Figure 6: Phase I and II - Block Diagram	7
Figure 7: Phase I and II - Equipment installed at LVVWD.....	8
Figure 8: Phase II - Hydrogen Generator.....	8
Figure 9: Phase III - Block Diagram.....	9
Figure 10: Phase III - Hydrogen Generator – CAD model	10
Figure 11: Phase III - Hydrogen Generator	10
Figure 12: Phase III - Equipment installed at LVVWD	10

Development of Hydrogen Filling Station at Las Vegas Valley Water District

1 Summary

The hydrogen fueling station at Las Vegas Valley Water District (LVVWD) is an operating fueling station which generates hydrogen fuel from renewable energy resources. The station, which provides fuel for all types of hydrogen powered vehicles, has undergone three different phases during its tenure. The station has been in operation since spring 2007 and was originally developed with equipment from the first two phases. Initially, the Phase I and II equipment generated just 2 kg H₂/day. The station was retrofitted with new Phase III equipment in October 2007 and currently generates over 13 kg H₂/day. The physical size, power consumption and capital cost per kg of H₂ have been reduced significantly between the initial kickoff and the final configuration. Additional storage paid for by the LVVWD is planned at a future date when the Ford F-150 H₂ ICE truck is added to the vehicle fleet. To date, there have been minimal operational issues and the station continues to serve the end customer. The LVVWD has now assumed all costs associated with the operation and maintenance of the station.

2 Introduction

2.1 Phase I - 2kg/day Renewable Fueling Station

The goal of the phase I equipment, developed under the original contract DE-FG 36-03GO13063 and sub-contract RF-05-HFS-005, was to generate up to 2kg H₂/day using renewable energy as the electrical power source. A Proton Energy Systems HOGEN 40RE hydrogen generator and Air Products 100E compressor, storage and dispenser were selected as the basis of the design, with a buffer tank connected between the two systems. The 40RE was originally designed for indoor use only, but one of the project requirements was to make the system compliant with desert-like conditions. In addition, UNLVRF in co-operation with UNLV-CER, LVVWD, and SNWA designed, developed and oversaw the manufacturing of a solar PV grid array at the fueling station in order to supply renewable electrical power for the hydrogen generation and compression.

2.2 Phase II – Enhance Station w/High Pressure Electrolysis Fueling

The Phase II equipment, developed under the same sub-contract, was a demonstration project to show hydrogen generation at substantially higher pressures than the Phase I equipment. By operating at up to 2000 psig instead of 200 psig, the mechanical compression required to store the gas at greater than 6000 psig is an order of magnitude lower and therefore the cost of capital equipment for the mechanical compression is reduced. Proving the feasibility of this technology in fueling applications enables design of future cell stacks to best optimize the cost of the mechanical compression system.

The Phase II equipment involved developing a proof-of-concept high pressure electrolyzer system by Proton Energy Systems which produced up to 0.5kg/day. The prototype mechanical compressor and buffer tank skid were developed by Air Products. The compressor skid and tank were integrated to connect into the existing Phase I Air Products 100E skid.

2.3 Phase III – 13kg/day Renewable Fueling Station

The Phase III equipment, developed under an amendment of the original contract, RF-05-HFS-005-A02, was designed to generate hydrogen at higher capacities, yet increase overall hydrogen generation efficiencies and minimize the overall capital expenditures for a fueling station. All Phase I and II equipment was decommissioned and removed from the site before the Phase III equipment was installed. Unlike Phase I and II equipment, the purge fan and other ancillary equipment for the Phase III equipment can be powered off by incorporating an integrated power-conservation mode when not generating hydrogen. The overall average of hours of standby vs. hydrogen generation is typically 3:1 to 6:1 for normal operation.

The Phase III equipment involved developing a new 30 barg (435 psig) hydrogen generator, a new 30 barg buffer tank and upgrading the Phase I Air Products 100E skid. By generating hydrogen at approximately twice the pressure than the Phase I equipment (435 psig vs. 200 psig), the same mechanical compressor on the 100E can handle the increased capacity of the Phase III generator, despite the increase in throughput of over 6 times vs. the HOGEN 40RE (13 kg/day vs. 2 kg/day). The only modification required to the compressor skid was a larger motor to drive the compressor and additional cooling to remove excess heat from the compressor heads. Currently other stations of the same daily capacity require the next size compressor skid, 200E vs. 100E, which can increase capital costs by over 25%.

3 Approach:

3.1 Phase I - 2kg/day Renewable Fueling Station

The H40RE, a renewable hydrogen generator which generates 40SCF/hr, was selected for the phase I equipment. Initially, the electrolyzer was designed to be directly coupled to the photovoltaic (PV) solar array to allow the highest efficiencies possible through direct current (DC) solar to DC electrolyzer cell stack power. However, the design was later modified to convert the DC power from the PV array to alternating current (AC) for the electrical grid to receive renewable energy credits, and then convert the AC power back to DC for the electrolyzer to generate hydrogen. Even though this method reduces the overall lower efficiency by approximately 10%, it maximizes storage of all renewable energy vs. being constrained to only generate electricity when the storage tanks are not full. This method allows the electrical grid to be a storage means, analogous to a large battery, for power generated from the renewable energy source and to allow generation of hydrogen at any time as required. The renewable interface study performed in Phase IV confirmed this method as most cost effective.¹

A site plan was developed with the end customer in Dec 2003 at Las Vegas Valley Water District. A major design hurdle for hydrogen generation was to protect the electrolyzer and system elements from the harsh ambient conditions. An enclosure was designed to integrate the H40RE and the DI water systems together to withstand the environmental conditions of a hot dry climate. Initial concept designs were completed for the H40RE unit with the use of 3D CAD. Equipment layout, purge airflow, ingress protection, thermal design and seismic requirements were all analyzed. An enclosure from Rittal Corporation was selected from several vendors based on size, cost, flexibility and previous customer-supplier experience. Test plans for each subsystem and for the integrated system were written and a safety/hazard review of the entire

system was completed. The sub-system was built and tested in the winter of 2005. Figures 1-3 show schematics from this phase.

Figure 1: Phase I - P&ID

Figure 2: Phase I - Hydrogen Generator

Figure 3: H40RE inside Rittal Enclosure

The compression, storage and dispensing equipment was specified and procured in the fall of 2004 from Air Products & Chemicals, Inc. A Series 100E integrated fueling system was selected based on matching flow rates of the electrolyzer and compressor, minimizing footprint, and the supplier's experience with hydrogen fueling. A buffer tank was purchased from a current supplier.

The entire system was installed and tested at Proton Energy System's facility in Wallingford, CT during the spring and summer 2005 (Figure 4). Dispensing of hydrogen was successfully performed into a test skid and a test report was generated. In the fall of 2005, the equipment was disassembled, final changes were made, and the system packaged for shipment. The equipment was shipped in December 2005 to the end customer site, LVVWD, and held in storage until the site was completed.

Figure 4: Phase I - Equipment installed at Proton Energy Systems

Due to funding and approval process delays, the site design was modified to include Phase II equipment and not completed until one year later during the winter of 2006 (Figure 5). The equipment from both phases I and II were installed and the site was commissioned during January 2007. Training of end users in the Emergency Response Plan, dispensing of fuel, and vehicle operation was completed during the same time period.² A separate DOE safety review was completed one month later in February 2007.

Figure 5: Phase I - Equipment installed at LVVWD

The station operated for the next six months supporting various vehicles developed by UNLV-CER, including an electric vehicle stripped of its batteries and converted into a fuel cell vehicle and a modified gasoline-powered ICE converted to use hydrogen. During that timeframe, support for the station was completed by personnel at Proton Energy Systems, Air Products and UNLV-CER staff. The equipment was monitored remotely and performance data was analyzed for system reliability, uptime, and overall system health monitoring.

3.2 Phase II – Enhance Station w/ High Pressure Electrolysis Fueling

The Phase II project was kicked off internally in January 2005 and system design efforts were initiated throughout the spring and summer of 2005. The design for high pressure H₂ generation was based on low capacity, high pressure cell stacks designed originally for backup power applications. By designing cell stacks which could perform chemical compression to pressures between 1000 and 6000 psig, the physical size of the station could be reduced and therefore the cost of the mechanical compression required to fill vehicles at greater than 6000 psig could also be reduced.

All of the major subsystems for the advanced fueling capability were designed during the Phase II project. Figure 6 shows the block diagram for Phases I and II. Characteristics of the design which had to be considered included electrolysis, water treatment, operating pressure, outdoor enclosure, mechanical compression, hydrogen storage and integrated system controls.

Figure 6: Phase I and II - Block Diagram

Test plans for each subsystem and the integrated system and a safety/hazard review of the entire system were completed during the fall of 2005. All components and sub-systems were procured, manufactured, and assembled throughout the year and were completed by summer 2006. During the late summer of 2006, each major subsystem was functionally tested at Proton Energy Systems facilities in Wallingford, CT. The entire hydrogen generator system was shipped to the end customer in September 2006. During this time, the mechanical compression and storage system from Air Products was built and tested at their facility and was also shipped to the end customer site. Figures 7 and 8 show the two electrolysis units and the Phase II hydrogen generator, respectively.

Figure 7: Phase I and II - Equipment installed at LVVWD

Figure 8: Phase II - Hydrogen Generator

Due to the delay in construction of the Phase I site, the equipment layout was modified, and both phases of equipment were designed to be placed on the same pad while operating independently. When the site was completed, the equipment was placed and commissioned at the same time as Phase I equipment in January 2006, including completion of training as described in Phase I.

3.3 Phase III – 13kg/day Renewable Fueling Station

The development work for designing a 30 barg outdoor hydrogen generator started in the fall of 2005. The basis for this project began with a HOGEN H6M industrial hydrogen generator and associated chiller designed to operate indoors at 200 psi (~15 barg). It was then modified to meet the higher generation pressure requirements and repackaged into a NEMA4 style enclosure.

First, a detailed design analysis was performed on the cell stack to determine the added mechanical stresses on the design and other effects of operating at the higher pressures. A test

plan and report were generated for the cell stack to determine relief valve settings and safety factors. Once the cell stack became a qualified component, design continued with modification of the balance of plant components for the higher pressures. The hydrogen phase separator and hydrogen dryer were redesigned to meet the higher pressure requirements and prototypes were built and tested. Overall endurance and cyclical testing were performed on key components to verify and validate the design requirements. Figure 9 shows the block diagram for Phase III.

Figure 9: Phase III - Block Diagram

The enclosure for the hydrogen generator was specified and selected in the spring 2006, and mockup of the equipment configuration occurred in late summer. A matching chiller was specified and a vendor chosen. Additionally, a new buffer tank manufacturer was identified and qualified. The design reviews were completed in the fall and PO's were placed for the NEMA4 enclosure, the matching chiller, and the buffer tank. The hydrogen generator was configured during late winter 2006 to spring 2007 and was tested in the summer 2007. The chiller and buffer tank were received in the spring 2007 and validated independently.

The initial approach proposed for Air Products was to upgrade the original 100E compression, storage and dispensing equipment with a 15HP motor, integrated cooler and updated controls in order to meet the increased 13 kg/day flow rate. However, on further analysis, it was determined by Air Products that replacing the original 100E with a separate upgraded 100E skid would allow the turn-up of equipment to occur sooner with fewer program risks.

A site plan was developed with the end customer, LVVWD and engineers contracted by UNLV Research Foundation to keep modification of the site to a minimum. In the span of one month during October of 2007, the Phase I and II equipment were taken off-line, removed from the site, and Phase III equipment was placed and commissioned. Training for end users for the Emergency Response Plan, dispensing of fuel and vehicle operation was completed at that same time.⁵ Figures 10-12 show the CAD model for the hydrogen generator and the final equipment installed at LVVWD.

Figure 10: Phase III - Hydrogen Generator – CAD model

Figure 11: Phase III - Hydrogen Generator

Figure 12: Phase III - Equipment installed at LVVWD

4 Results and Discussion

4.1 Phase I – 2 kg/day Renewable Fueling Station

The program met all of the sub-tasks of the contract and demonstrated a true pathway to zero-emission hydrogen fuel. A hydrogen fueling station was safely designed, and components were specified, tested, approved, installed and commissioned. The test plan overview is shown in Figure 13. The test report⁴ shows the equipment operated within specifications. The equipment was operated as designed for over 6 months and dispensing of hydrogen into vehicles safely occurred. DOE performed a Safety audit of the station after Phase I equipment was installed and their findings approved use of the station as originally intended.

Figure 13: – VER3039 Fueler Test Plan Overview

Several lessons were learned throughout the phases of this contract. In phase I, an important factor was that installation of a hydrogen station requires cooperation and vested interest in the safety of people and property by all parties, including:

- Site owners
- Local authorities
- Emergency responders
- Equipment suppliers

In addition, the installation schedule was found to be proportional to the level of up front coordination and identification of approving entities. In this case, since this type of facility was not previously in existence, the processes and procedures of utilities were unknown at the start and discovery was required as the project proceeded, which required additional time.

4.2 Phase II – Enhance Station w/ High Pressure Electrolysis Fueling

This phase of the program met five out of seven tasks of the contract. The exceptions were Task 6, System Servicing & Maintenance and Task 7, Renewable Power Electronics Interface Analysis. These two tasks could not be completed within the budget requirements of the contract. The system was safely designed, built and tested at Proton Energy Systems in Wallingford, CT per the UNLVII Verification Test Report.⁵ However, when installed at the customer site the equipment was inadvertently powered down and electrical heaters were not powered. A cold temperature evening during that timeframe froze the electrolyzer cell stack and caused damage to system components. Repair and maintenance were implemented, but subsequent operation caused error codes in operation. The equipment was unable to sustain continuous operation after commissioning.

Lessons learned in this phase included discovery that the water management for the H₂ separation was not ideal. An integrated separator design was attempted to lower pressure vessel numbers and system cost. However, the volume and shape were not ideal for cell stack orientation and caused entrained water. As a result, the generation capacity had to be lowered to 7 standard cubic feet per minute (SCFM) to get usable gas. In addition, the generation pressure achieved was 1100 psi, less than the target. Several iterations for high pressure sealing techniques were explored, with the discovery that a larger sealing area is required than was included in the original design. These results have been fed into next phase of high pressure development at Proton. Finally, freeze damage occurred during installation of HGM. Two attempts were made to repair the unit in the field. The compressor skid was determined to be functional by checking it out using bottled gas. The unit was sent to Proton for diagnosis.

4.3 Phase III – 13 kg/day Renewable Fueling Station

This phase of the program met all of the sub-tasks of the contract and again demonstrated a true pathway to zero-emission hydrogen fuel. A hydrogen fueling station was safely designed and components were specified, tested, approved, and installed for commissioning of the station. Outdoor operation for both the electrolyzer and chiller at Proton Energy Systems has included over 6 months testing with temperatures from 0°F to 90°F including all types of precipitation including driving rain, snow and ice. This unit continues to operate at the site.

The verification testing of the 30 barg system was completed, showing a calculated increase in production from 0.539 kg/hr to 0.575 kg/hr, which equates to a 6.5% increase in efficiency for energy consumed per kg of H₂.⁶ The equipment continues to be operated as designed and is dispensing hydrogen into vehicles safely. As of May 2008, the system has generated approximately 350 kg of hydrogen at 30 barg equating to over 650 hours of runtime. The station has been in operation since October with only a software upgrade and minor maintenance expected from prototype equipment.

An additional lesson learned in this phase was that adequate component testing and early approval of cell stack, hydrogen phase separator and dryer components as well as the chiller sub-system verification testing simplified system testing later on. Also, in program schedules for equipment decommission/installation, slack time should be allowed between major events to keep the overall schedule. This allows time to finish earlier tasks which took longer than expected. For example, the site electrical power originally was not meeting specification which required a step-down transformer.

5 Conclusions and Recommendations

The hydrogen fueling station at Las Vegas Valley Water District has been successfully generating 13 kg H₂/day from renewable energy resources, with minimal operational issues over the past 7 months. The current unit is a culmination of a 3-phase project beginning from 2 kg H₂/day, with significant reductions in physical size, power consumption and capital cost per kg of H₂ over the duration of the project.

Several key learnings were gained from the project, particularly in the high pressure electrolysis phase. The original H₂/water separator design was oriented such that issues occurred due to water entrainment. The integrated separator also made the volume difficult to adjust. It was

discovered that the shape and volume of head space is key even at low flow. Further Proton IR&D has explored low cost pressure vessel alternatives that look promising for future projects. In addition, the desired generation pressure for Phase II was not achieved, due to insufficient sealing area. The next phase of high pressure development at Proton will incorporate these learnings. Success of these installations depends on cooperation and vested interest in the safety of people and property by all parties.

6 References

¹ Deliverable Report: Renewable Electronics Interface for PEM Electrolysis: Renewable Energy and PEM Electrolysis and Renewable System Architecture Optimization Study

² Proton Energy Systems Internal Report No. RPT1431, Rev 4 – EMERGENCY RESPONSE PLAN FOR HYDROGEN FILLING STATION

³ Proton Energy Systems Internal Report No. RPT1431, Rev 5 –EMERGENCY RESPONSE PLAN, UNLV PHASE III FILLING STATION

⁴ Proton Energy Systems Internal Test Report No. VER3039 – UNLV Phase I Test Report

⁵ Proton Energy Systems Internal Test Report No. VER3067 – UNLVII Verification Test Report

⁶ Proton Energy Systems Internal Test Report No. VER3085 – UNLV FuelGen12, 30 Barg, Verification Test Report (UNLV Phase III)

ATTACHMENT 2

UNLV VEHICLE DEVELOPMENT WORK FOR THE HYDROGEN FILLING STATION

PREPARED BY:

**UNLV-CER
January 15, 2010**

Final Report

UNLV Vehicle Development Work For the Hydrogen Filling Station

Contract No: 71904645
Subcontract #RF-05-HFS-006
Company: UNLV CER

Submitted by:

R. F. Boehm with assistance from many other personnel
The Center for Energy Research (CER)
UNLV Box 454027
Las Vegas, NV 89154-4027

Submitted to:

The UNLV Research Foundation
Las Vegas, NV

Date Submitted:

January 15, 2010

Overview

As part of the development of the solar-powered-hydrogen filling station, three vehicles (one an electric vehicle and two that were powered by internal combustion engines) were converted to operate on hydrogen fuel. These conversions were performed primarily by students with Center staff oversight. This report gives an overview of some of the details of these conversions. More detailed information can be furnished if desired.

Ford F-250

The Ford F-250 hydrogen conversion has gone through various stages since the implementation of the project. A break down of what have occurred over the past few years are as followed:

An inspection of the Ford was completed by representatives of the DOE. Shortly after this inspection Proton put forth the requirement that each of the fuel systems had to be pressure tested with nitrogen to 110% of the working pressure for 30 minutes, followed by a test to measure the pressure drop over twenty-four hours with the system pressurized to 90% of the working pressure. The Ford's fuel delivery system in the end would meet the required operating standards after testing.

Progress continues on design of the fuel system on the Ford including tank mounting, fuel delivery and injector fabrication. Any seals used in the system are rated for use with hydrogen and appropriate factors of safety are being employed in the design of any structural components.

Fuel Injector/ Sparkplug update as of first quarter 2007:

Design for the injector has been finalized and parts are currently being manufactured. The injector has been broken into 6 categories: housing, ceramics, electrodes, valve, check valve and gas fitting. The Table 1 represents all parts, general description and completion.

Table 1. Parts for Injector/Sparkplug System

<u>Category</u>	<u>Part</u>	<u>Description</u>	<u>%</u>
Housing	Cap (Upper)		100
	Cap (Lower)		100
	Upper	Contains Valve assembly	100
	Mid	Contains Check Valve Assembly	100
	Lower	Encloses lower electrode, screws into head	100
	Nut	Retains Cap onto housing	100
Ceramic	Cap (Upper)		0
	Cap (Lower)		0
	Impact		0
	Mid	Insulates check valve	0
	Lower	Insulates lower electrode	0
Electrode	Upper	Wire connection to spring (through cap)	100
	Mid	Valve Seat and holder for Check Valve seat	0
	Lower	Threaded portion	0
Valve	Impact	All 4 items (design reviewed 04-04-07)	0
	Plunger	Redesign (March 07)	50
	Spindle	Redesign (March 07)	75
Check Valve	Seat		100
	Plunger		100
	Retainer	Retains spring and travel limiter	0
Gas Fitting	Banjo	Captures upper cap on o-ring	75

Items listed as 100% complete or nearly complete comprise the bulk of the complicated and/ or time consuming items to be manufactured (with the exception of the ceramic). Remaining items are expected to no more then a few more full days of working.

We have experimented with two purities of Al₂O₃ (96.0% and 99.8%). The ceramic of 96% purity machined with ease as the manufacture of the material suggested, however, in experimenting with the electrical properties, it was determined to be questionable. Per recommendations from the tooling companies, various tools were purchased to machine the 99.8\$ pure material (harder, denser and better electrical properties). Suitable means to machine this material to desired tolerances was unsuccessful by both CER personnel and shop personnel at Kell's. We are currently awaiting further instruction and advice from the tooling company.

Various fixtures for testing the valve assembly and check valve have been designed. Testing of the valve assembly will consist of a frequency generator as an input signal to the injector controller, a high pressure inert gas (nitrogen) and a mass flow meter. Testing of the valve consists in three parts, 1) reliability and 2) mass flow analysis and 3) high current through the electrode to identify problems arising from the spark. Testing of the check valve and spark will consist of a pressurized, Plexiglass and a spark control module. Testing of the check valve will take place in two parts; 1) the apparatus will be pressurized through the check valve and monitored for leaks and 2) the electrode will be sparked at high pressure comparable to the combustion chamber as to identify any possibility of a short in the insulation.

A rack has been designed and fabricated to hold the bank of five tanks as one modular unit. Work to perform the fuel system conversion will begin in some form within the next week. This will include thorough documentation of the current configuration as well as its disassembly. Also included in the conversion work will be thorough documentation of all modifications made to the factory configuration. The current CNG fuel and spark control tables have been downloaded. The control scheme employed by the Ford Engine Control Module (ECM) is appreciably different than that used on the KAM ECM.

Comprehension of the fuel tables as well as their adjustment for hydrogen is almost completed. Specifically, there are approximately a dozen variables in the computer that are not used in controlling the engine. The time required to comprehend the fuel tables will include not only sorting through the variables but also formulating variable values for the hydrogen fuel table. Much of the hands-on conversion work and programming work will have to take place at the same time.

Work continues on the development of the new model of fuel injector we plan to use for this vehicle. Testing for coil suitability has been completed and the coil seems to work quite well. The impact and insulators have been redesigned as a result of the latest test. It is clear that manufacture of these will not be an issue. Backflow testing of the check valve is complete and the design passed.

The first phase testing of the injector will consist of a separate solenoid (already in hand), lower portion of the injector (check valve), which is also in hand. Assembly of the lower portion with spark leads will be finished by the end of this coming week provided no delays in availability of the machines.

Second phase testing will consist of integrating both the coil design and lower injector (check valve) into the 'final' design. However prior to this step in the testing, a test fixture (already in manufacturing) will be used to evaluate valve sealing. At this time, final remarks regarding coil performance will be made. Preliminary testing and complete assembly is anticipated by the end of July.

Evaluation of the injector will take place on the spare 1-cylinder engine we have at Kells but it needed partial rebuilding because of the new injector placement. The test engine has been completely rebuilt, assembled, etc. The wire harness for the computer system was complete as this report was being written.

The work on the fuel cell is basically complete. Housing for the fuel cell is being designed and fabricated. Its installation in the vehicle will be done as soon as the hydrogen tanks are installed in the back of the truck.

A technical paper summarizing the fuel cell – supercapacitor performance was presented at the International Conference on Clean Electrical Power, held in Capri, Italy, May 21-23, 2007.

The fuel storage is nearing completion on the Ford pickup, which is shown in Figure 1. In Figure 2, the installed fuel tanks can be seen. Most of the hydrogen lines and vent lines have been completed at the end of the period. The major effort that remains is the manufacture of the hydrogen injector/spark plug combinations. One of these has been produced and tested. Work is focusing on this aspect at the end of the period. A major problem we are dealing with is the manufacture of the ceramic insulators for the sparkplugs. Although of less magnitude in required effort, the mounting of the fuel cell auxiliary power system on the vehicle is yet to be completed.

Figure 1. The Ford pickup that is undergoing conversion to hydrogen

Figure 2. The hydrogen fuel tanks mounted in the Ford pickup are shown

The prototype Ford injection unit was completed and tested for spark and operating pressures up to 200 psi. Additionally, thermal and fluid flow analysis was conducted in Fluent to verify correct operation at the desired pressures and engine temperatures. The final design for the injector has been approved and 10 units are currently being manufactured. Currently we are awaiting the arrival of the ceramic material used for the insulating the electrodes; all other parts have been completed. All solenoids used in conjunction with the injectors have been received and are ready for installation in the Ford vehicle.

All drawings and schematics have been completed for the remaining items to be installed on the Ford. The new wiring configuration was determined from factory schematics and instrumentation specifications. An aftermarket timing circuit will be installed that delays ECM turnoff when the key is turned off. The hydrogen leak detection system will no longer shut off the engine, but instead will sound an alarm signaling for the driver to pull over and turn off the engine. Items awaiting installation include the leak detection and alarm system, solenoid valves associated with the injection system, the main solenoid shutoff valve and electrical connections related to the injection system. The fuel plumbing for the new injection system has been fabricated and awaits installation, but this task can only be completed once the corresponding bracket has been fabricated and installed.

The Ford pickup is almost fully converted with the exception of the fuel injectors. We continue to have problems with the ceramic product supplied by the initial vendor we selected. The company continues to claim that they can meet the specs on the items, but when they finally ship, they are no way close to the requirements. We had to select another vendor that appears to be able to hold to the tolerances we need, but only time will tell how they come out.

The final issue relates to the fuel injector/spark plug assembly for this vehicle. One vendor for the ceramic parts required was unable to deliver as required after a long wait for manufacturing. The parts finally received were far outside of specifications. A new vendor was located. After some delay, this vendor finally delivered some parts that are much more like what is required. However, the Ford F-250 is still awaiting some reprocessed ceramic pieces from the new vendor; we had received one of the parts for each cylinder with minor dimensional errors so this was sent back for adjustments.

When we got all the parts together, we tested the injector for leakage through the seams, and check the electrical conductivity and electrical insulation. A pressure test will be setup for it as well. If all goes well then the next step will be to install the injectors and start the tuning process on the engine in the vehicle.

Reprocessed ceramic pieces for the injector/spark plug assembly were received and trial fitting has thus far been successful with minor adjustments and parts matching needed to achieve desired tolerances. Final pieces required for the spark plug electrodes have been designed and machined in-house. To date, ten complete injector assemblies have been assembled and await final assembly with epoxy which will be followed by high pressure

testing. At this time one injector has been fully assembled with epoxy sealant and has successfully been pressure tested to 200 psi.

Final assembly of different subsystems on the truck has taken place. The hydrogen tank master solenoid has been installed along with the individual injector solenoids. We obtained the final electronics required for the conversion and are in the process of building the required wiring circuits and integrating them with the vehicle's stock wiring harness. Once this is accomplished we will be able to pressure test the system, perform high pressure testing on the injector assemblies and proceed with our first test run of the vehicle.

Final assembly of the additional electrical components and circuits that are required for the HICE conversion is near completion. We have built a relay box (see Figure 3) inside the engine compartment which houses a voltage booster used for stepping the voltage from 12V to 24V powering injector solenoids. In addition a timing circuit was installed in order to power the vehicle after the ignition is shut off for 15 seconds. This is required to expend the excess hydrogen gas in the low pressure side of the fuel system and any residual hydrogen in the combustion chamber. The relays will allow the injectors, spark, and all sensors to continue powering the vehicle until all the fuel is expunged. The main solenoid mounted in the bed of the truck will be shut off when the ignition is off; this is to isolate the high-pressure fuel from entering into the injection system at shut off.

Figure 3: Relay Box

A wideband oxygen sensor has been installed and will be used for tuning the vehicle to run on hydrogen. See Figure 4. The sensor indicates what air/fuel ratio the engine is running at. This information allows us to know whether to add or remove fuel from the combustion mixture using the engine control module. Once the engine is properly tuned, the sensor readout can still be used by the operator to continuously monitor the air fuel ratio to make sure it stays within safe limits of operation.

The pressure display unit (see Figure 4) has been installed and will be programmed to read the signal from a pressure sensor installed in the high pressure side of the fuel system. This will serve as a way to monitor the amount of hydrogen left in the storage tanks similar to a fuel level gauge for gasoline.

Figure 4: Cab Display Units

The low-pressure side of the fuel system has for the most part been assembled. Fuel lines were extended from the main line after the fuel pressure regulator that decreases the hydrogen pressure from 5000 psi to less than 1000 psi. We fabricated brackets to locate the individual injector solenoids in the engine bay, though we are in the process of modifying the brackets to better package the solenoids and ignition coils in the tight confines of the engine bay. The injectors were temporarily installed to check fitment and determine routing for hoses from individual solenoids to the injectors. Blow off valves were fabricated and installed in the intake manifold where the stock injectors were located in order to allow for pressure relief in the event of an intake backfire. See Figures 5 and 6.

Three hydrogen sensors along with collectors have been installed on the vehicle. Two are located in the bed of the truck (see Figure 7) and one resides in the engine bay. The sensors will allow detection of hydrogen leaks in the storage system as well as the fuel delivery system. The individual sensors each have an alarm, and we will be using an output from each sensor to trigger a relay and piezoelectric alarm inside the truck cab to alert the operator to an active leak.

We have begun pressure testing the fuel system with high-pressure nitrogen up to working pressure to check for leaks prior to pressurization with hydrogen. We are in the process of testing an epoxy to use for sealing the injector assemblies prior to final installation in the engine. Once installed and all systems are checked over, we will be attempting to start the vehicle and will proceed with tuning the engine via the engine control module using aftermarket software.

Figure 5. Engine

Figure 6: Injection System

Figure 7: Hydrogen Sensor

The task of leak testing of the high-pressure fuel system has been completed. This process involved using high-pressure nitrogen gas to charge the system and allow leak detection without having to be concerned about potential flammability associated with hydrogen. The system was pressurized incrementally up to 5500 psi, fixing any gas leaks as they presented themselves. See Figures 8a and 8b. Once this process was completed with nitrogen, it was repeated with high-pressure hydrogen supplied by the Las Vegas Valley Water District Hydrogen Fueling Station, again repairing leaks as they developed. This process took longer than expected due to issues with the HFS software recognizing the larger fuel capacity of the Ford truck as a potential leakage problem that would inhibit the fueling process. Once this issue was resolved, a filter on the vehicle's low pressure gas regulator failed producing an uncontrollable leak. We were able to obtain the necessary parts to rebuild and reinstall the regulator that now seems to be working properly. Pressure testing using hydrogen has been accomplished up to 4900 psi, just short of the 5000 psi operating pressure due to a limit in the HFS software; we will be working with the HFS technician to remedy this situation.

Figure 8a. N₂ pressurizing test system

Figure 8b. Leak detection pressure relief valve

The injector/spark plug assemblies have successfully undergone leak testing using high pressure nitrogen gas as well (up to 1100 psi) and were subsequently fully assembled and installed in the engine. See Figure 9. In addition new spark plug wires were fabricated, along with new brackets necessary to relocate the engine's ignition coils. See Figure 10.

Figure 9: Injector/spark plug final assembly

Figure 10: Ignition coil relocation brackets

Past experience with the Polaris vehicle showed that the catalytic converters failed during the experimental tuning process; this was most likely due to backfires through the exhaust system. In order to avoid this problem with the Ford truck and to prevent potential exothermic reaction with leftover hydrogen/oxygen gas mixtures in the exhaust system, the catalytic converters were temporarily removed and replaced with straight piping. This will also allow evaluation of raw exhaust emissions without the converters scrubbing out potential NO_x emissions.

Currently, the vehicle's fuel system has been completed to where we can attempt to get the vehicle running which will most likely present another set of problems that we will have to troubleshoot and work through (this includes troubleshooting of fuel system solenoids, ignition system and engine computer parameter adjustment). Our goal at this point is to have the truck running before the end of the month so that we can spend the summer tuning the engine computer operating system and improving drivability. This will involve use of a multi-channel oscilloscope to determine proper injection and ignition timing events. We will also utilize the SCT software to adjust injection timing, air fuel ratios and ignition timing for best torque output that is best accomplished using the chassis dynamometer provided by the Las Vegas Valley Water District. This is assuming proper operation of the injector/solenoid system as designed.

The bulk of the work on the HICE Ford pickup in the final quarter of the project has consisted of troubleshooting the add-on electronics, stock vehicle powertrain control system and the fuel delivery and ignition components.

We initially attempted to start the vehicle but determined that some of the add-on electronics systems were not interfacing with the stock electrical system properly. The decision was made that it would be easier redesign the wiring scheme for the components being added to the stock electronics. A modular system was assembled in such a way that it would be easier to troubleshoot and add/remove electronic components as deemed necessary (Figure 11). After assembly, the wiring and components were checked and rechecked to verify that everything was operating as designed.

Figure 11. Redesigned modular wiring and electronics assembly

At this time we found that the solenoid peak-and-hold driver box was not operating properly and had to be returned to the manufacturer for testing and repair. The manufacturer offered to upgrade some of the components in the driver box to ensure proper operation with the 24 volt system that we are running the solenoids at (typically this driver box is used to drive typical low impedance fuel injectors at 12 volts).

After reinstalling the repaired/upgraded solenoid driver box, we flashed a new program into the vehicle's powertrain control module, using software produced by SCT, which would allow the vehicle to run on hydrogen rather than natural gas. With these changes we were able to start the vehicle on hydrogen for the first time. It ran fairly well though the air fuel ratio was somewhat lean. The figure below (Figure 12) shows the readout on a four channel oscilloscope monitoring the vehicle's crank sensor, cam sensor, fuel injection and ignition signals. At this point the injectors are firing with the stock timing values; these values will be changed to occur during the compression stroke to decrease the probability of backfire during operation.

Figure 12. Four channel oscilloscope readout monitoring crank sensor, cam sensor, injector and ignition signals

The day after our initial startup the engine developed a consistent exhaust backfire during operation. This was traced to two of the injector/spark plug assemblies which developed discontinuity in the electrode, inhibiting the ignition of the air/fuel mixture. The hydrogen would pass through the cylinder to the exhaust where it would accumulate and ignite resulting in the observed backfire. Upon disassembly of the injectors two key observations were made. First, errors in machining tolerances allowed part of the electrode assembly to separate during operation resulting in loss of spark at the electrode tip. This was corrected by adjusting the tolerances and reassembling the injectors. Second, water had accumulated inside the injector housing allowing the electrode to ground to the inside of the injector housing rather than at the electrode tip. The source of the water is not presently known for certain. Considering that the function of the injector assembly is to flow hydrogen from the storage tanks to the engine cylinders without permitting backflow of the cylinder contents, leads us to believe there is moisture present in the hydrogen storage system. We will have to monitor this situation to see if the problem recurs.

While the fuel delivery system was removed from the vehicle we performed compression and leak down testing to rule out problems due to the engine we are using. The compression values and leakdown percentages were found to be within specification considering that the engine in use has more than 136,000 miles of usage.

The engine has been operating fairly consistently since repairs were made to the two problematic injectors mentioned previously. We have since begun the process of data logging (Figure 13) and altering the operating parameters of the powertrain control module (Figure 14) to improve the consistency and performance of the engine. We are

still becoming familiar with the SCT Flash software used for this process but are making good progress. In addition we will be working to adjust the startup and shutdown procedures for the engine due to irregular backfires that occur during these processes.

Figure 13. HICE Ford pickup data logging session using SCT LiveLink software

Figure 14. HICE Ford pickup power train control module programming using SCT Advantage III software

Work then turned to a focus on the data log and optimize parameters in the engine operating software. After several data logging/tuning sessions a persistent backfire developed. The problematic injector/spark plug assembly was identified and removed from the engine for testing. Compared to earlier situations, this time no issues with continuity were detected and resistance through the electrode assembly was measured to be 1.5 ohms (typical for the assembly). The spark function of the assembly was tested outside the engine using the vehicle's ignition system and appeared to be working, yet the backfire would return when the injector was reinstalled. The hypothesis that the injector was not igniting the hydrogen/air mixture in-cylinder during operation was verified by reinstalling the injector, running the engine, observing the backfire, then disconnecting the hydrogen solenoid supplying the same cylinder; when hydrogen was not supplied to the cylinder the backfire would cease to occur. This led us to conclude that with increased pressure in-cylinder, the spark would not jump the gap between the electrode and grounded housing resulting in hydrogen passing through the engine without being combusted and causing the exhaust backfire.

The injector was then disassembled to find multiple cracks in the lower electrode ceramic insulator (Figure 14-a) which would easily allow spark to jump from the inner electrode to the injector's main housing rather than at the end of the injector.

Ford Engine Spark Testing:

The next step was to observe the spark function while under pressure. A pressure chamber with a viewing window was fabricated for this purpose and used in conjunction with a timing circuit (assembled by LVVWD technician, Richard Furniss) that would repeatedly trigger an ignition coil using a +12V power source. The injector with the broken lower ceramic was repaired by replacing the ceramic portion with a new piece and reassembling. The first round of testing compared the repaired injector with an injector that was considered to be functioning properly (had no problems thus far). The testing arrangement is shown in Figure 14-b below.

Figure 14-a. Visible cracking of lower electrode ceramic insulator

Figure 14-b. Spark pressure testing apparatus.

Both were tested by observing the spark at zero psi and when pressurizing the chamber to ~110 psi. The good injector produced spark in both scenarios while the repaired injector produced spark but was erratic at zero and high pressure. The problem injector was again disassembled and inspected; what looked to be a small fracture in the upper ceramic insulator was observed. The insulator was indeed cracked possibly allowing spark to ground to the injector housing as can be observed in a video of the process. Although the crack is very small, spark was seen to be jumping through the ceramic to a grounded probe as the resistance between the electrode and spark plug is increased by increasing the distance the spark had to jump between the two. Thus, the upper ceramic would have to be replaced as well. It was later determined after disassembling the remainder of the injectors that the cracking in the ceramic pieces may be due to incorrect tolerances between the inner electrode and ceramic insulator. With insufficient tolerance between the two, it is likely that the combination of initial loading from assembly, engine vibration and heat cycling is sufficient to cause the ceramic insulator to fail during operation.

An interesting observation was made during spark testing; with the injector and pressure vessel pressurized and observing the spark, if the pressure in the injector housing was released, the electrode in the still pressurized chamber would cease arcing to the injector housing. In other words, when there is a great enough pressure differential between the

injector housing and the end of the electrode the resistance across the gap between the end of the electrode and the injector housing is too great for an arc to occur. This was also observed on a video record. At this point we do not know whether the spark is following a path of lower resistance within the injector housing or if it is unable to reach ground and the coil is unable to discharge.

The question arose as to whether this issue can occur during normal engine operation. Since we are using a direct injection scheme for hydrogen injection, the hydrogen will inject during the compression cycle after the intake valve has closed. During injection, the hydrogen solenoid opens allowing hydrogen to flow through the injector and its internal check valve at a pressure of ~500 psi. As this is happening the piston is traveling upward compressing the air/hydrogen mixture. The hydrogen will continue flowing until the solenoid is shut and the pressure across the check valve in the injector housing is equalized. After this point in-cylinder pressure will continue to increase as the piston approaches top-dead-center. The scenario arises that depending on when the hydrogen injection ends and how much ignition advance is commanded by the vehicle's engine control module, if the cylinder pressure increases high enough above the pressure within the injector housing it is possible that the air/hydrogen mixture will not be ignited due to loss of spark across the electrode/housing gap.

Next we decided to modify the pressure testing apparatus to allow pressurization of only the end of the housing to determine what pressure differential is required for spark to cease to occur. Prior to testing, each injector was disassembled and checked for evidence of cracks in the ceramic insulator; none was found with the exception of the previously mentioned damaged injector (injector #6 in the table below). For this test, each injector was tested by pressurizing the pressure chamber and observing the quality of the spark from the electrode to the grounded housing. The results of this testing is shown in Table 2 below.

Table 2
Testing of hydrogen injector spark quality at varying pressure.

Testing of Injector Spark Quality at Varying Pressure								
	injector #							
test pressure (psi)	1	2	3	4	5	6	7	8
0	good	good	good	good	good	not tested	good	good
10	good	good	good	good	good	not tested	good	good
15	decreasing	erratic	erratic	good	erratic	not tested	good	decreasing
20	erratic	none	erratic	decreasing	none	not tested	erratic	decreasing
25	erratic	none	none	decreasing	none	not tested	erratic	erratic
30	none	none	none	decreasing	none	not tested	erratic	erratic
35	none	none	none	erratic	none	not tested	erratic	erratic
40	none	none	none	none	none	not tested	none	none
decreased spark								
performance at (psi)	15	15	15	20	15	not tested	20	15
failure at (psi)	30	20	25	40	20	not tested	40	40

The results of this testing showed that each injector displayed decreased spark performance at 20 psi or less and failed between 20-40 psi. To put this in perspective, cold cranking pressure for the Ford 5.4L engine was generally near 110 psi and can be expected to increase with an engine at operational temperature and increased load/rpm. As a control, a conventional automotive spark plug (NGK TR6) was tested using the same apparatus. Spark was observed from 0-102 psi using the same testing apparatus. In this case the spark intensity increased with increasing pressure and was most intense at the highest pressure. The results of this testing are of concern but the effects of the spark “blowout” due to the pressure differential across the hydrogen injector have not been directly observed during engine operation.

Ford Injector Redesign:

While we will continue to make adjustments to the current set of hydrogen injectors in order for them to function properly, we are also developing a second design that attempts to solve the following list of potential problems with the current injectors:

- high cost (due to custom ceramic insulators and machining of stainless steel housing and electrode parts)
- cracking of ceramics due to varying tolerances, loading, vibration and heat cycling
- potential for leaks due to hydrogen gas having to flow through the electrode
- potential for spark failure due to pressure differential between combustion chamber and injector housing

We now have the second design nearly completed, and preliminary evaluations have been performed. These units have the beauty of eliminating some of the specialized parts that were difficult to manufacture. They hold great promise and are to be evaluated in the first quarter of 2010.

Concluding Comments on Ford Pickup:

It appears that a new design of injector-spark plug unit may solve the problem of a complicated modification procedure that will allow both injection and spark to be accomplished through the same penetration in the engine head. This will greatly simplify the conversion process from gasoline to hydrogen. An early design worked fairly well, but suffered from lifetime problems. Modifications to design lend a great deal of hope that an inexpensive and very functional direct cylinder application will be a reality.

The final parts the new injectors were completed as of late December 2009. Our next step now is to install the new injectors and relocate the necessary parts in order to get the vehicle moving again. From there we will once again implement a proper tune for the Ford, as well as data log the performance throughout the process.

Polaris ATV

Although this vehicle was developed first, it is listed as second here, but we consider it a step toward the Ford design. Some of the early work is given first, and later in this section we discuss the current status of it.

A Polaris Ranger ATV was modified to burn hydrogen fuel. In accomplishing this modification, two major efforts were expended. The lesser of the two involved removing the gasoline tank and replacing it with a high-pressure hydrogen storage tank. The other issue involved the conversion of the engine to burn hydrogen. It is this latter aspect that is addressed in this report.

The Polaris 2004 2x4 model, 425cc four-stroke single-cylinder engine with a compression ratio of 9.2:1, designed for running on gasoline was received at University of Nevada, Las Vegas in the spring semester 2005. It has the rated power of 25 hp at 4000 rpm.

The engine was received without any throttle body connected to the intake manifold, no catalytic converter connected to the exhaust manifold, or any sensors hooked up. It was a stripped engine for which some necessary parts were machined on CNC machine at Kell's Automotive (machining capabilities of this type were not available at UNLV at the time). Work was performed to set up the engine for a series of dynamometer tests at Kell's. A variety of sensors were installed on the engine to enable sufficient insights to the operating parameters, but the details of these will not be covered here. Work then progressed to the installation of a direct injection system for the hydrogen introduction to the engine cylinder. This will portion of the work will be emphasized here.

To accomplish the latter, the head was modified by drilling a hole in such a way so as to incorporate a fuel injector. A variety of approaches were evaluated, and the first several were unsuccessful for a myriad of reasons.

Typical testing plans for each injector approach, consisted of operating the engine at 1500, 2000, 2500, and 3000 rpm with a load of 50%, 75%, and 100%. During some of the initial test, the action of the fuel injector would malfunction, and that would cause the test to abort.

Figure 15 is a Solid Works representation of the engine with the in-cylinder hydrogen injection with a Hoerbiger (an Austrian manufacturer that has worked with BMW) injector. These injectors could not be made to function correctly for this small engine application, and an alternative was developed.

Figure 15: Engine with in-cylinder hydrogen injection by the use of Hoerbiger injector

A second approach was planned, for in-cylinder fuel injection using a two way normally closed high-pressure-impact-type solenoid valve purchased from Peter Paul. The solenoid valve is simple in construction with only two moving parts. Its exclusive features include a precision stainless steel plunger that supplies the necessary impact force to energize the valve, a Kel-F PIN functioning as a sealing element, that is carefully machined for maximum concentricity and fine finish, and a orifice guide for near perfect alignment, giving a bubble-tight sealing from low pressures right up to maximum pressure rating with the bonus of longer life.

When the valve coil is energized, the plunger is drawn towards the sleeve end stop. The plunger is allowed to accelerate freely for a short distance before it makes contact with the pin shoulder. Upon contact it imparts considerable force on the pin causing it to lift off the seat. A return spring provides the return force, directly on the pin, to seal the orifice when the coil is de-energized. It successfully ran with hydrogen but was also accompanied with pre-ignition, back-firing and knock. Figures 16 and 17 depict the solenoid valve installed on the engine.

Fig. 16: Engine with solenoid valve (red) attached

Figure 17: Engine with solenoid valve attached to the cylinder head

A check valve was needed to reduce the possibility of backfire. This is shown in Figure 18.

Figure 18: Design of the solenoid valve with the check valve

Generally quite good operational characteristics were determined. The engine was installed in the Ranger vehicle along with the other aspects of the conversion. The vehicle has been operated basically for the period since it was converted up to the present. Some adjustments had to be made at a couple points along the way. The engine had some problems operating at full power. A number of diagnostic tests have been performed. Some limitations to the vehicle have been discovered, including quite a short range with the single small tank on the vehicle. Others are mentioned below.

More recently a battery-discharging problem has been discovered. This indicates that the alternator with which the vehicle is equipped cannot meet the electrical demand of the electronic components added when the vehicle was converted. Separate work orders have been put in at the LVVWD for modification of the battery rack to accommodate a larger battery and installation of a small solar panel on the canopy of the vehicle. Provided that the vehicle is parked in the sun when it is not in use, the combination of these two modifications should alleviate the discharging problem.

In a discussion with an applications engineer from Omega, it was discovered that the pressure transducer currently in use on the Polaris is not suitable for use with hydrogen. Its use was the result of a misprint in the data sheet for the transducer. A compatible replacement has been ordered and received. It was installed and operated without problem.

In the meanwhile the Polaris continues to be operated over at the LVVWD. One issue discovered was that the oxygen sensor needed to be reinstalled. This problem was quickly resolved upon discovery.

All of the mechanical components to the Polaris engine have been checked and repaired. We are now exploring in greater detail the timing of the EFI and the actual injection timing. It seems as though there may be a delay between computer signals and when the injection solenoids are actually reacting. We currently have a 4 channel reading from an oscilloscope of the cam pulse, crank pulse, injection pulse, and spark pulse. With this information we are able to fine tune the vehicle and get it running more smoothly. Further testing will continue until further progress is made.

At one point we were oblivious to the fact that the Polaris had developed a recurring problem while in the hands of the technicians at the LVVWD. Now that this has been brought to our attention, we will quickly tend to the situation. The Polaris ATV was not running properly due to improper positioning of the crank sensor. The vehicle would intermittently lose the crank signal which resulted in the spark and fuel cutting out. The problem was resolved by replacing the old sensor and setting it at the specified position. The Polaris is currently running under its own power without any problems.

Another problem was found during acceleration. When the throttle was opened too quickly, the vehicle would go lean and become very unresponsive. That is when we decided to install a throttle position sensor in order to enrich the fuel mixture during quick jabs at the throttle. Unfortunately, the vehicle remained unresponsive to the added fuel. Further inspection will be taken in order to eliminate this problem.

We are currently attempting to optimize the fuel maps in hope of increasing fuel efficiency while maintaining good performance. The Polaris is currently tuned to run lean during idle at an air fuel ratio of approximately 36 (air fuel ratio of 34 is considered stoichiometric for hydrogen). Under maximum load at 4000 rpm, the air fuel ratio is around 32 which is a slight change from the previous air fuel ratio of 28. Although it is difficult to tell whether or not these changes are increasing or decreasing the vehicle's overall performance, our next step will be to put the Polaris on a dynamometer. This will help us see whether the power output is increasing or decreasing to the changes.

The Polaris ATV is currently being used on occasion at the Las Vegas Valley Water District. The vehicle has been running without any intermittent problems, but we will continue to monitor the vehicle for any changes in performance and make adjustments accordingly. It seems that a major issue with the vehicle is its short range. We have investigated the possibility of adding an additional fuel tank, which would double the

vehicle's range. However, both the cost of the new tank as well as limited space on the vehicle has limited this thrust.

As of today the Polaris ATV is still being used by the Las Vegas Valley Water District without any problems. We will continue to monitor for performance changes.

Taylor-Dunn Conversion: Electric Vehicle to Fuel Cell-Electric Vehicle¹

The Vehicle Before Conversion

The vehicle that was converted, an Electruck - Model ET-150-72, is considered as a burden carrier or personnel carrier for manufacturing plants looking to haul goods throughout warehouses and plants (i.e., off-road applications). The vehicle is powered by an electric drive train, and can reach speeds of up to 25 mph, while providing over 40 miles in range. The deck provides nearly 150 cu. ft. of cargo space to carry loads up to 1,500 pounds.

The electric drive system consists of a battery bank, a speed controller, a DC motor and 14:1 differential gear attached to the back wheels. The battery pack, weighing a total of 756 pounds, consists of twelve 6 V batteries connected in series, and each unit is rated at 225 Ah @ C/20, thus the total energy stored at full state-of-charge is around 16.2 kWh. The 72 V source supplies a series-excited DC motor through a solid-state speed controller. The motor specifications are as follows: NEMA rated 72V, 22 hp @ 2820 rpm intermittent duty; 11.5 hp @ 4000 rpm normal duty. The motor speed controller - Curtis PMC 1209 – is a step-down DC-to-DC converter in which the duty ratio of the power transistor is controlled by the position of the accelerator pedal. It manages the current load drawn by the series motor based on the gear, accelerator pedal, and brake pedal of the vehicle. An array of parallel power MOSFET switches pulses the current from the batteries to the motor. The transistors switching frequency is 15 kHz, while the ratio of the on/off times is varied in response to the input demanded by the accelerator.

Conversion to Fuel Cell Hybrid Configuration

Electrical, mechanical and structural modifications were made to the vehicle in order to accommodate the 5.5 kW fuel cell, the hydrogen storage tanks, new set of batteries, and the electrical connection through a boost power converter and associated controls. A block diagram of the power train of the modified vehicle is shown in Fig. 19. Such configuration is referred to a fuel cell series hybrid structure, where the fuel cell is installed for load sharing operation with the battery pack since its maximum power production is well below that of the maximum demand. Information on each subsystem follows.

¹ Much of the information given here appeared in the paper: R. Mauldin, Y. Baghzouz, and R. Boehm, "Light-Weight Fuel Cell-Battery Hybrid Vehicle Demonstration Project," SPEEDAM 2006, IEEE.

Figure 19. Modified Fuel Cell – Battery Hybrid Power Train.

The fuel cell that is purchased and installed in the vehicle is referred as the “H2e” and manufactured by Nuvera. It utilizes a state-of-the-art direct water injection system, which significantly improves reliability and simplifies the balance of plant. All balance of plant and stack parameters are managed by the onboard computer system. A control algorithm that safely starts, monitors, and shuts down the fuel cell under all operating conditions is also implemented in the onboard computer.

Areas critical to fuel cell system operation, such as pressures and temperatures of the supply-side hydrogen and air flows, stack cooling loop, individual cells, stack voltage, are continuously monitored for performance and troubleshooting through a data output terminal. The H2e thermal management unit is composed of a heat exchanger that separates the liquid water from the saturated air, and both condense part the water vapor, and cool down the liquid water to a temperature acceptable for injection into the stack. This heat exchanger is a liquid-air type, which results in hot stream leaving it. The terminal voltage of the H2e drops from 95 V down to 62 V when the load current increases from zero to 130 A. The fuel cell, however, comes with a DC/DC converter that steps this unregulated voltage down to a regulated 48 V supply.

The response time of a fuel cell to a load change is not as fast as the battery system because it needs some time for the flow of hydrogen to adjust to meet the new power demand. But with today’s fuel cells, this time is often adequate to meet the performance requirements of most of the vehicles. In fact, the H2e is ready to deliver up to 2.5 kW within 12 seconds from start-up, and load following from 2.5 kW to 5.5 kW in much less than one second, i.e., nearly instantaneous. The only problem is that there is a significant time delay or warm-up period DT from start-up to a point where it is able to deliver full power. This delay depends on the ambient temperature; for example, DT is nearly 12 minutes at 10°C, but less than 5 minutes at 30°C.

It is important to note that the H2e does not have a current limit capability, which means that if the application tries to draw more than 5.5 kW (or more than 2.5 kW – 45% of full load during the warm-up period of operation), the H2e will open its output contactor and disconnect the load. An analog control output voltage V_c (equal to 5 V and 9 V when the unit is able to generate 2.5 kW and 5.5 kW, respectively) is provided to avoid hard system shut-down.

As stated above, the H₂e fuel cell terminal voltage is a regulated 48 V. On the other hand, the load and battery pack nominal voltage is 72 V. Hence, a DC/DC power converter is placed between the fuel cell and the battery bank to boost the voltage from 48 V to nearly 72 V, and to control the power supplied from the fuel cell under different operating conditions. The power converter used is a 1-quadrant, crystal controlled, double half H-bridge, boost converter with two external filter inductors, and a switching frequency of 31.25 kHz.

The exact value of the output voltage is most critical to load sharing of the fuel cell – battery combination. This voltage can be set to a specific fixed value by simple adjustment of the gain. The converter is also equipped with separate +5V and -5V regulators that are available to the user if a potentiometer is used to vary the output voltage. A specific pin of the control plug which controls the input current limit value is used to limit the fuel cell current in order to avoid overload and hence hard shutdowns which significantly impact the life cycle of the stack. At 100% current limit, the voltage of this pin is 9V. Lowering this voltage (by inserting a resistor) reduces the current limit value in a linear fashion. Finally, a power diode is placed in series with the positive output terminal of the converter to block any current flow back into the converter and fuel cell – that is to prevent cell reversal, and hence damage of the stack.

The original bank of twelve 6 V batteries was replaced with six 12 volt batteries, each rated at 145 Ah. The total capacity of the new bank is 10.45 kWh, i.e., 35% less than the original bank. However, this new battery bank weighs nearly 200 lbs less than the old bank, and frees up the needed space for the installation of the fuel cell and hydrogen tanks.

A load test was conducted on the new battery bank to determine its steady-state voltage drop under different load currents starting from full state-of-charge. We found this to be a nearly constant voltage drop of 80 mV/A. Thus, the static internal resistance of the pack is 0.08 Ω .

Several other modifications have been made to the vehicle in order to accommodate the new power source. These include the following:

- Raising the vehicle bed by 4 inches and modifying the frame to house the fuel cell, hydrogen tanks, and power converter.
- Modifying the fuel cell plumbing (added an accumulator, raised the radiator position relative to base of fuel cell, etc ...)
- Adding an electric pipe heating system to prevent water from freezing during the winter season.
- Adding an instrument panel to display fuel cell parameters, fuel pressure and battery state-of-charge.
- Installing a set of relays that are appropriately timed for the safe start-up and shut-off sequence of the fuel cell system.

The final physical layout of the various subsystems under the bed of the vehicle is shown in Fig. 20. The weight of the modified hybrid electric vehicle is nearly the same as the original pure electric configuration. Meanwhile, the electric energy available at full charge for the motor drive is increased by 3 folds.

Figure 20. The layout of the various subsystems in the vehicle.

The fuel cell – battery hybrid configuration that is implemented in this vehicle allows the control of two parameters at the DC/DC converter that is placed between the fuel cell terminals and the battery terminals. These parameters are: (a) the DC/DC converter output voltage, and (b) the DC/DC converter input current limit, i.e., the fuel cell output current. These parameters define the power generated by the fuel cell.

Ideally, this particular hybrid system works most efficiently when satisfying average driving demand by the fuel cell and peak power demand (or rather the differential between average and peak demand) by the battery bank. The battery bank also acts as an energy storage unit during deceleration and stoppage time. Such operation avoids the wide variation in the fuel input to the stack, and enables a less fluctuating current that is ideal for fuel cell operation.

To accomplish this, first the converter output voltage should be set higher than the battery terminal voltage and the input current limit should be set to a value corresponding to not more 2.5 kW at 48 V, i.e. less than 50 A. This is accomplished by the following steps:

- Adjust the converter gain to the desired value. This way, the fuel cell will act as a base unit that delivers the first amps of load demand and provides some charge to the battery at the same time.
- Insert a resistor between the current limiting pin of the control plug and ground so that the pin voltage reads 4 V (that is 45% of 9 V).
- After the analog control signal output indicates that the fuel cell is warmed up and

ready to deliver full power, remove the inserted resistor above in order to increase the current limit to 100% (or 115 A). This switching is performed automatically by a simple electronic circuit using transistors.

Operational Experience

The fuel cell vehicle operated quite nicely for a period of 2 years. Then during some routine maintenance work at the LVVWD, a dropped tool caused a short between two leads in the system. This, it was later determined, caused one of the cells in the fuel cell stack to fail.

Contact to Nuvera determined that they would not entertain the idea of repairs. They claimed that the particular model of fuel cell in our vehicle was no longer serviceable. Personnel from the CER examined the fuel cell stack and determined a way of shunting the ruined cell which would allow the stack to operate. However, it was also determined that one or more of the electronics boards in the unit may have had a failure. Our personnel were unable to trouble shoot the boards and with the seeming inability to secure service from the manufacturer, it seemed that the vehicle was inoperable. Almost by accident, a later contact with the company indicated that they were able to service the unit. So the three electronics boards were sent to them. They determined that two needed to be replaced. Two new boards were purchased. At this point the engineer who was performing this work for the CER took a job in industry. As this report is being written we are waiting for other personnel at the CER to be freed up to complete the repair.

ATTACHMENT 3

HYDROGEN ROADMAP DOCUMENT

PREPARED BY:

**David Haberman
IF-LLC**

Hydrogen Roadmap Document

**Prepared For University of Nevada – Las Vegas Research Foundation
By David Haberman, IF, LLC**

Preface

The Department of Energy provided funding to the University of Nevada – Las Vegas Research Foundation to investigate hydrogen energy. UNLVRF asked IF, LLC to formulate a plan to move hydrogen forward in Nevada. This document is the deliverable plan from that effort which spanned 2005-2006. IF, LLC is a hydrogen consultancy operated by David Haberman and a team of associates.

1. Introduction

Hydrogen energy is evolving to become a viable candidate to replace gasoline as a transportation fuel. Hydrogen fuel cells can also be used to provide portable power instead of batteries and replace natural gas generators to deliver electricity for stationary applications. Hydrogen is being viewed by every state as a possible magnet for economic development and infrastructure modernization. Unlike the federal programs, states must focus on rallying their existing resources, capabilities and creativity to develop a hydrogen plan which will have a clear return on investment. The purpose of this road-mapping activity is to focus on integrating Nevada's combined potential into an approach that has milestones and clearly identified options (pathways) for policy and stakeholder review. The primary feedstocks and enabling technologies necessary to produce hydrogen fuel are shown below:

Roadmaps for infrastructure conversion and societal transformation are built upon these pathways. The roadmaps consider: consumer markets, resources, industrial capability, transitional scenarios, economic and environmental policies. Often policy follows the local availability of one of the feedstocks shown.

There are four propositional roadmaps considered in this document:

Roadmap I	Using Nevada's abundant solar resource to generate hydrogen and following a clean renewable energy push supported by public policy
Roadmap II	Build upon the on-going investment into large scale nuclear waste storage capability and funding (catalyzing) hydrogen energy use within the modifications to Nevada's infrastructure
Roadmap III	Creating a market driven scenario based upon the vibrant Las Vegas tourist industry served by wealthy (risk oriented) companies that understand the value of uniqueness and publicity
Roadmap IV	Connecting Nevada to regional hydrogen imperatives in a manner that complements the extensive hydrogen investments in California and the idea of building niche capabilities that can serve the entire southwest region.

The document is a work product of IF, LLC submitted to UNLV.

2. Scope

The scope of this project is limited to Nevada and its role within the southwest region. All roadmaps have multiple dimensions of concern and most projects can be “plotted” in the *hydrogen energy space* represented by the figure below:

This diagram illustrates the dimensions of applications, fuel, and critical considerations to be balanced in implementing hydrogen energy. The elements in blue the spectrum of fuel types regarded as “hydrogen” are shown. Pure hydrogen is not the only fuel to be considered and often natural gas; biogas or even solids and liquids with a hydrogen constituent are labeled as hydrogen sources. The elements in green the power applications intersect the fuel types and are shown from one direction addressing the use dimension and the other direction the applications purpose: here divided into defense (including aerospace), or commercial. The elements in red define implementation concerns for each combination of fuel type and application. Most projects can be plotted within this implementation space which is useful when those plots are compared with plots of past projects and businesses – both on-going and failures.

3. Task Plan

IF, LLC implemented an approved task plan which consisted of the following:

- a. State H2 Readiness Survey
This task was designed to engage organizations in Nevada and the nearby region on their posture to contribute to a hydrogen evolution in the state.

Organizations contacted or considered included: City Engines, DRI, ORMAT, UNLV, Honda, APS, Air Products, Sierra Pacific, PARSONS, ARES, Plug Power, Intelligent Energy, City of Las Vegas, Nevada State Energy Office.

An effort was made to reach out to every county commissioner in Nevada regarding interest and capability in participating in the hydrogen energy road-mapping. All responses indicated a strong skeptic that any resources attainable via participation in such an effort would be “sucked into Las Vegas”. There was a lot of interest in small scale, off-grid reliable power but there was no willingness to undertake any technology or reliability risks.

b. Industry Posture & Plans Analysis

The state has capability in renewable energy, hydrogen utilization and analysis but lacks well resourced, risk taking entities which might venture into hydrogen integrated systems aggressively. There are few component and device level manufacturers so the majority of any bill of materials (BOM) in a hydrogen system is sourced from outside the state – most likely the majority of equipment comes from Japan. As a relatively blank canvas there is a lot of potential in Nevada given its tax climate and the availability of cheap land. The state must decide it wants to nurture a specific industry segment which has a high chance of success. The hydrogen engine firms in Reno and Las Vegas are both competent and perhaps are the best start toward a nascent industrial base that is fairly distributed and pertinent. Another strategy is to choose a key enabling technology and attract it to Nevada – preferably one that has dual applicability if hydrogen energy slows down. An obvious choice is solar energy systems that can supply electricity directly at various scales as well as energize hydrogen production reactions. It is likely that Nevada’s hydrogen future will continue to be driven by DOE and out of state players seeking a specialized venue.

c. H2 Chain Gap & Risk Inventory

The construction and operation of the two hydrogen fueling stations in Las Vegas illuminates gaps in available hardware and risks. The Air Products and Chemicals (APCI) project in North Las Vegas cost \$16M (overrun to \$18M) which was cited as a good example of a combination of undesirable characteristics: the hazards, risks and regulatory lessons in its construction were not shared and the advertised costs scare other municipalities which might consider hydrogen energy. The tactic APCI employed of bragging about high cost-share to build influence at DOE has actually prevented any real consideration of a hydrogen infrastructure in Nevada because of the perceived price hurdles. At present Nevada faces extreme gaps and high risks in its ability to apply in-state resources to hydrogen energy projects because of DOE’s dependence on only a few large, influential companies

(non situated in Nevada) to integrate systems. The second station project is the on-going UNLV- Proton – Water District project which will hopefully be far more transparent than the APCI project. If this project shares data appropriately then there is a chance of using this information to assist Nevada's positioning in hydrogen energy by identifying specific technologies, equipment, and /or processes that can be hosted in Nevada and serve a growing in-state, regional and national market.

d. Creation of Likely Transition Scenarios

In discussion with the expert team there were four scenarios which emerged as reasonable and these are discussed in section 5 below. Of note was another failed scenario where in the past Bechtel as an operations contractor for DOE had been managing various hydrogen activities in Nevada and they had all failed to produce any useful results.

It was agreed that a transition scenario dependent on the commitment of any single large empowered commercial interest was doomed to failure because of the dominance of its proprietary interests over any mission responsibility.

e. Implementation Cost Analyses

There is little useful open source literature regarding the costs of implementing hydrogen energy. Most of the DOE projects which involve implementation are cost share and the commercial entity proprietize cost information. There is an effort at the National Energy Technology Laboratory (NETL) to collect, analyze and distribute useful information but this is in the early stages. There are published studies by the National Renewable Energy Laboratory (NREL) specifically examining hydrogen energy, usually by focusing on specific operations: production, storage, fuel cell use. But the industry usually take extreme exception to many of NREL's conclusions citing a combination of the government analyst's naiveté, inflexible analysis techniques and the use of old and incomplete data reflecting mature equipment configurations.

A current systemic failure of hydrogen energy cost analysis is attempting to fit into petro-fuel and petro-energy models which do not permit the valuation of characteristics unique to hydrogen nor recognize the hidden costs of the status quo. A recent RAND forum (December 2005) on the question of hydrogen valuation made the point that costs must be calculated within the context of the use scenario as well as the conduct of commercial transactions. Additionally the return on investments (ROI) associated with properly used opportunity funds on an appropriate scale is missing from current comparative cost analyses on hydrogen energy – given that the opportunity risks of the status quo have been syndicated and mitigated by

over 100 years of applied learning. In regards to the question of Nevada's potential costs of implementing hydrogen energy there is a need for a quantitative analysis using a framework of one or more of the likely transition scenarios. A simplistic initial comparative ranking from least to most expensive might be:

i. Least Expensive To Nevada

Building upon the on-going investment into large scale nuclear waste storage capability and associated transport and security infrastructure is a pragmatic approach to being resource driven. This multi-year, funding could be used to catalyze hydrogen energy use by targeted implementation of hydrogen fuel cells coupled with distributed production serving standby and remote functions currently served by batteries and small generators. The hydrogen production and delivery to support these functions could be over-capacitized to provide transportation fuel to service fleet vehicle use in selected areas. Thus a hydrogen capability serving the current and future priority program is engineered to nurture a single thread hydrogen addition to Nevada's infrastructure. This project would be supported by the federal government in an effort to show some residual benefit to Nevada outside its mandated existence as a waste depository. The success of this, and many similar propositions, will primarily be based on a political calculation on the value of the resultant goodwill in Nevada. In the initial feedback to this report this option was considered politically untenable. The on-going legal issues regarding Yucca Mountain cloud the option of "piggybacking" on this enormous investment. It is still included herein because it was considered in the consensus process.

ii. Second Least Expensive To Nevada

Creating a market driven scenario based upon the Las Vegas tourist industry served by wealthy (risk oriented) casino companies that understand the value of uniqueness and publicity. The proposition is that exposure will generate interest and support which can be monetized into political currency and stock confidence. A relatively small investment by a public-private partnership may have the potential to illuminate hydrogen energy benefits in a manner that does not require companion marketing and pr expenditure because of the venue.

iii. Second Most Expensive To Nevada

Using Nevada's abundant solar resource to power photo-voltaic powered electrolyzers which generate hydrogen can provide hydrogen to high value fuel cell and chemical applications. Given that Nevada imports its hydrogen from California for industrial uses this approach promotes competition with existing industrial gas operations which must use expensive trucking fleets to deliver hydrogen. The concept is that the nurturing of an in-state production capacity will build a growing

operation that pays the cost burden of initial hydrogen energy by taking market share away from H₂ importers. Since this approach follows a clean renewable energy path it will likely be supported by public policy. Also the solar based electricity for the hydrogen production is a valuable commodity thus this would have a comparatively lower risk since it positions the state to serve another renewables market independent of hydrogen. This does require significant investments in baseline solar systems in order to achieve a workable scale. It is possible that the casinos as lead adapters of solar (both thermal and pv) may be the enabling goodwill development.

iv. Most Expensive To Nevada

This approach connects Nevada to regional hydrogen imperatives in a manner that complements the extensive investments in California and the idea of building niche capabilities that can serve the entire southwest region. Specifically this means connecting to the transportation network being established in California, this includes fuel production, dispensing stations and fleet vehicle operations. The value of leveraging California's leadership in hydrogen is to attract hydrogen industry using Nevada's preferential regulatory and tax climate. This is the most expensive approach because it requires capital expenditures in the near term to make substantive capital investments in serving a nascent infrastructure growing out California. It is also the highest risk because it is dependent on the political stability of California's support for hydrogen. The freedom from income tax combined with a less strenuous regulatory environment may tempt organizations targeting California to base in Nevada. Nevada will have to negotiate interstate hydrogen fuel distribution agreements and exemptions from California's carbon regulations to allow H₂ fuel it wants to sell to be labeled renewable portfolio standard (RPS) compliant.

f. Risks & Barriers Identification & Analyses

This is a general overview of the greatest risks and barriers to hydrogen energy development, integration, deployment and profitable use.

i. Technology

At present the technology is operational at a large industrial scale oriented to the production and use of hydrogen as a chemical. In the US the centralized reformation of natural gas is the basis of industrial gas and refinery operations. The use of water as an alternative feedstock requires electrolysis (water-splitting) which is also a mature technology. The primary technical risks are in high pressure (10,000psi) compression and storage of hydrogen gas. Other risks include achieving high efficiencies in the production of pure hydrogen from biomass, from nuclear processes or from coal. The integration of the full energy chain

is also technically risky because the techniques and hardware to connect dissimilar equipment is primarily laboratory or experimental. While hydrogen is a safe fuel there is poor situational awareness (sensor) technology that is hydrogen specific.

ii. Supply Base

There are single source suppliers for many of the key devices and components necessary to integrate a hydrogen energy system. Connectors, reformers, electrolyzers, compressors and dispensers are all manufactured by an extremely narrow supply base. It is likely that many devices and components will be imported from overseas, which in the era of a weak dollar is expensive.

iii. Codes & Standards

The regulatory landscape that references codes & standards (C&S) is evolving constantly and the cost of compliance with many new rules is basically unknown. There is no mechanism to bound the subjective nature of compliance judged by over 44,000 authorities having jurisdiction in the U.S. At present no integrator is sharing his representations to these regulatory authorities so there is little opportunity to build upon the experience of government funded projects. Every hydrogen project must re-invent its compliance strategy and every hydrogen project is under extreme pressure from its equipment suppliers to propertize all lessons learned since they are usually based upon equipment problems. Further C&S development organizations do NOT care what the costs or time to comply suffered by users of their products rather they are concerned with the purity of their process and selling their publications. Nevada faces the same issue as every other state which is to decide which C&S are truly necessary to protect the public.

An important regulatory issue with hydrogen is the qualification of hydrogen fuel within the definitions of the Renewable Portfolio Standards (RPS) which are mandated in different states. This has not been accomplished but is essential to the growth of hydrogen use.

iv. Inadequate Risk Transfer

There is a lack of actuarial information available to insurance companies to judge the risks, hazards and exposure of protecting hydrogen energy systems. To date most all hydrogen energy projects are self insured, bundled within an existing experimental (high risk) policy which protect laboratories or simply operated without outside coverage (e.g. DOD projects). This reality continues because insurance companies have not invested time to create hydrogen energy underwriting capability because they perceive there is not enough demand to warrant the expenditure. Further, most hydrogen energy projects are operated for a limited period of time and it is not deemed worthwhile to suffer the learning curve of a

specialty underwriter. The energy companies and the industrial gas firms who have the actuarial data use it to self insure effectively but have no motivation to share the information. Thus hydrogen energy deployment is restricted and will continue to be the domain of hydrogen chemical players or governments for the foreseeable future.

v. Transition Complexity

All roadmaps make transition assumptions based on the timeframe of the availability of resources, the speed of regulatory easements for using hydrogen and service requirement being addressed by the lead adapters in each particular roadmap. It is likely that financial resources are provided by public-private partnerships and usually funding from government agencies is a long-term adventure. Given that Nevada wishes to accelerate the likelihood of any transition scenario to include hydrogen energy it will adapt a package of supporting policy based incentives which include regulatory relief. Today hydrogen energy is best positioned to serve specific applications such as fleet vehicles, high value electrical backups and remote / uninterruptible power supplies therefore the speed of customer acceptance is a major factor in the pace of a transition.

vi. Time To Impact

Impact is judged using several criteria: accounting, market acceptance, displacing incumbent technology and providers are the major measurements. In hydrogen, to date, cost – price performance has not been achieved in compassion to the status quo. In road-mapping it is essential to poll the stakeholders to collect all definitions of achieving pertinence so these may be reviewed and a time expectation clearly assigned for each. One of the most asked questions about hydrogen is “when” and most of the guesses are made devoid of the underlying definition of which scenario is being judged and what is the threshold of success. One criteria that is universally accepted is retail sales volume and stability.

vii. Lack Of Customer Champion

Hydrogen energy will succeed when a customer judges its value proposition meritorious over the incumbent equipment in a competitive environment. There are few customers, who do not also have an interest in the equipment or fuel supply chain, which are prepared to undertake risking their current operations on hydrogen technology. Government, utilities and academia are currently the best candidate champions for using hydrogen energy technology because they are better informed than most commercial customers and can make adaptation decisions with consideration of missions that extend past fiscal success.

viii. Bad Information

Hydrogen energy suffers from an overabundance of poor quality information. Obsolete or incomplete data posted on the internet assures the propagation of bad information and has a long effective half life of stimulating poor decisions. Recent critics have assembled opinion and half truths into books like the Hype about Hydrogen which have not been effectively answered. Hydrogen safety is still a key question in the public's perception yet the physics of hydrogen in comparison to accepted fuels The DOE Hydrogen Program and its stakeholders have websites which provide significant information that is useful in building awareness.

ix. Logistics

Hydrogen is manufactured from water or biomass or a fossil fuel like coal or natural gas. This production process requires equipment and energy although far less than the exploration, extraction, transport and refining operations of fossil fuel. Hydrogen is a gas and must be compressed or liquefied for transport. These treatments are energy intensive and require equipment that is not comparable to today's liquid hydrocarbon infrastructure. It is usually these intermediate hydrogen processes which are highlighted as a challenge for using hydrogen when compared to the status quo of commercial fuels. Since hydrogen dissipates in air upon release and generates water when combusted it does not have the environmental issues or legacy associated with the fossil energy chain.

x. Configuration & Installation

Since hydrogen energy is in its early stages of commercialization there is a constant concern about employing this technology in a manner that best suits its attributes and highlights its benefits. Since hydrogen advocates propose to replace fossil fuel use in transportation there are expensive paradigms of vertical engines and fueling stations which must be addressed. Hydrogen energy using fuel cells and compressed gas storage often must be mechanized to fit the installation circumstances of the vehicle systems even though that is not optimum for many hydrogen equipment configurations. The initial uses of hydrogen energy in small stationary or portable applications does not present the challenges of packaging that transportation requires. A large group of companies in hydrogen energy desire to prove the functionality of the hydrogen energy chain before undertaking the burden of integration into vehicles. Unregulated installations, such as backup power inside a building or a data center presents an easier initial deployment goal.

xi. Costs

At present hydrogen energy has not advanced past pilot scale use and the equipment manufacture is still in pre-production. This means there is no

scale of economy to achieve efficiency in addressing recurring expenditures or an advanced learning curve which allows experience to benefit future users. The incumbent technologies have a significant cost advantage over hydrogen due to market dominance and therefore unsophisticated cost comparisons between fossil energy and batteries to hydrogen energy are not favorable. Most hydrogen energy companies invest considerable amounts in demonstrating their equipment and the ROI timelines in this nascent industry is well over 10 years in most realistic business plans. The computation of life cycle (cost of ownership) is a method that leads to the quantification of unpriced liabilities of the status quo and results in favorable economic determinations for hydrogen.

xii. Too Many Cooks

Many hydrogen advocacy groups are paralyzed into inaction because of the impossibility of harmonizing proprietary concerns, current policy, public interest, regulatory requirements and promotional demands. The resulting luke warm (consensus) positions kills hydrogen progress with faint gestures which collapse when faced with the aggressive tactics of the incumbents fighting to maintain market control and credibility dominance. This situation triggers irresponsible declarations by many hydrogen advocates that further degrade the industry's position to challenge the status quo.

xiii. Wrong Leaders

Often government officials are assigned to review or consider hydrogen energy as additions to their existing workload – usually associated with economic development. The technical and market complexities quickly overwhelm these officials and they tend to “job out” the hydrogen issue to a consultant or a University. For example; in New Mexico the State hired Los Alamos National Laboratory to prepare a hydrogen plan and surprisingly got a plan that emphasized research and ignored practical business issues. Hydrogen energy specialists are not plentiful but there has been an emergence of hydrogen business councils at the state level. Nevada is served by the Mountain States Hydrogen Business Council based in Santa Fe.

xiv. Creating A Formal Coalition

The difficulty of establishing a roadmap is the desire of certain stakeholders to dominate the process. The incumbent service and equipment providers in hydrogen (industrial gas companies) have ambitions to control the transition away from their market control. Many road mapping efforts have become homogenized into ineffectivity simply because of the industrial gas cartel's efforts to prevent the emergence of a price stabilized H₂ fuel. The facilitators of any state's road-mapping process must illuminate actions and positions designed to

prevent progress toward deployment and publicly assign responsibility so as to blunt the efforts of a few to maintain control.

xv. Hydrogen Safety

A major issue with hydrogen fuel is that it is not as dangerous as fossil fuel but it has to address safety myths (eg hydrogen bomb and the Hindenburg) in the regulatory environment which require a non-recurring expenditure in dispelling the concerns of authorities who have no experience in the area.

g. Survey On-going Government Activities

The Department of Energy – Office of Energy Efficiency and Renewable Energy is the lead government agency for hydrogen energy efforts. DOE has had the public support of the White House over the last administrative term. Extensive information on the hydrogen program is available on the web (www.hydrogen.energy.gov). The Department of Defense has shown considerable interests in hydrogen energy and fuel cell technology specifically. DOD continues to fund significant programs e.g. the funding of \$88M noncompetitively for General Motors to build a hydrogen fueled vehicle. The DOD Defence Logistics Agency-DESC has undertaken an important strategy building effort in recent years which is proceeding to identify the divergent hydrogen projects from different commands and harmonize objectives across the entire department. The Department of Transportation has completed a comprehensive hydrogen survey, conducted by its contractor, the Gas Technology Institute, designed to define all outstanding regulatory considerations for hydrogen fuel use in transportation. At the state government level over thirty states have active hydrogen energy agendas.

h. Facilitate Road-mapping Forum With Stakeholders

The Forum was designed to continually engage all the stakeholders by soliciting comments from all attendees both in a group and in breakout sessions. The UNLV approach was to set the stage with presentations on: experiences from other roadmapping exercises, infrastructure design and engineering, economic implications of hydrogen, policy issues and risks. An important factor is the inclusion of many different types of organizations including NGOs, small business, energy, utilities, car manufacturers, integrators, academia and local government agencies. Most importantly is assigning equal standing to all participants and balancing proprietary interests with social interests.

A central part of the forum process was to divide into four potential roadmap survey groups, each lead by an expert facilitator.

- The solar group was lead by Glen Hamer, former executive director of the Solar Energy Industry Association. NREL and UNLV faculty contributed significantly in this discussion.
- The nuclear group was lead by Steve Mahlon of Entegy, which is leading a nuclear reactor development program to produce hydrogen. Karen Kimball of PARSONS and Gerry Runte of ARES co-facilitated this group discussion.
- The market driven group was lead by Mathew Fairlie, a hydrogen business expert who has contributed significantly to the Canadian and California Hydrogen roadmap.
- The regional group was lead by Alan Grant of BC Hydro and Barb Heydorn of SRI, both are recognized experts in hydrogen energy business and economics respectively.

In the facilitated discussion process all the participants where engaged by asking each attendee to offer perspectives, questions and/or answers. Many of the comments have been factored into the appropriate section of this document but a few are separately noteworthy:

“Leadership is essential to applying the roadmap effectively. Champions must be willing to sell this roadmap to policy makers, regulatory bodies and other stakeholders.”

“Don’t repeat the mistakes of the electric car. Clearly the risk taking nature of industry, utilities and consumers must be balanced or there will be a lot of stranded and half completed projects. Public confidence will take a long time to recover.”

“It is preferential to solve multiple problems at the same time with complementary investments, the nuclear waste storage project will inject \$Billions into Nevada and hydrogen could piggyback on this investment.”

“Timelines for hydrogen transportation penetration are not applicable to the demonstration of hydrogen energy for stationary and portable/emergency applications which are potentially much shorter.

“There must be a level playing field for government subsidies and incentives. It seems that General Motors and the oil companies are blocking most hydrogen pathways simply because they consume hydrogen funds without providing a corresponding commitment to deployment. Lobbying and earmarks are harming the nation’s ability to implement hydrogen energy”

“A clear valuation of the hydrogen economy is still missing. Quantifications of transition scenarios that are realistically scaled must be performed by credible groups.

“Risk management in hydrogen energy is unstructured at best. There is a lack of reliable information available for due diligence, planning and conduct of projects.”

“There is no useful mechanism to obtain, contribute or share information regarding the implementation of hydrogen energy. The NETL hydrogen plan seems to offer a real solution to this problem.”

“It would be useful for all government customers of hydrogen energy projects to require a standard list of data submissions that include safety, reliability, regulatory compliance, insurance representations and operational performance.”

i. Document Roadmapping Forum

This report is the primary documentation of the effort. The presentations given at the forum are important contributions and are posted by UNLV on its website. The initial editorial responsibility for this document was assigned to IF, LLC then transferred to UNLV which will make all publishing decisions since this is a deliverable to DOE.

4. Forum Questions

a. Where Are We Today?

Most of the organizations doing any hydrogen work in Nevada participated in the road-mapping forum. Many indicated a desire to work together but confirmed they had been moving ahead with their own plans given a lack of a unified hydrogen vision. Most attended the road-mapping and the previous hydrogen safety workshop at UNLV expressed a desire to work with a cohesive group that had a sense of fairness and commitment to a level playing field. Many indicated that UNLV's recent meetings: April's H2 Safety workshop and the June 2006 Road-mapping had contributed to a growing sense of community. There are no major companies working in hydrogen energy based in Nevada at this time.

a) Why Do We Want To Move Toward Hydrogen?

Hydrogen energy offers the opportunity to generate fuel and power in-state and stop exporting wealth for energy. Hydrogen is versatile and can be used to serve many applications, including: transportation, stationary, portable applications. Most importantly a hydrogen energy system is transparent will

predicable and controllable costs. There is no feedstock risk because hydrogen can be made renewably from water or biomass. And the vision of the hydrogen economy is a level playing field of suppliers and distributors with broad competition and no monopoly interests or geopolitical concerns. Hydrogen is a clean form of energy and when combusted or used in a fuel cell its byproduct is clean water.

b) What Implementation Of Hydrogen Do We Want?

This is the focus of the alternative roadmaps put forth in this report. Most economists identify transportation fuel as the driving force for change and therefore the transportation goals become paramount. Yet, realistic approaches to participating in a new infrastructure include the realization that Nevada will not be the home to large car manufacturers and therefore must define an achievable role in the hydrogen future. Maximizing return on investment is as important in policy as it is in business and the four roadmaps put forth illustrate different but viable pathways to reasonable and attainable state ambitions for hydrogen. Nevada has the capacity to attract many technology companies, become a lead adapter of renewably generated hydrogen, and an exporter of hydrogen fuel.

c) What Are Nevada's Objectives?

Nevada desires to move toward energy independence and would like to enjoy the economic benefits of producing more fuel in-state for in-state use. Nevada is committed to environmental stewardship and recognizes the negative consequences of the status quo for the environment and public health. Hydrogen offers a clean alternative to growing fossil energy use. Nevada would like to diversify and expand its industrial base and the hydrogen energy sector is still undefined thus holding a large opportunity for growth. Nevada prides itself on being a pro-business state and understands that policy actions to reduce regulatory barriers to hydrogen energy can be stimulating and far reaching because few states have been creative or successful in this area. Nevada understands the relatively inexpensive nature of nurturing a new industry by simply eliminating obsolete or inapplicable rules. It may be possible to brand Nevada as a clean energy state and enjoy the public relations benefits from this added goodwill.

d) Can Nevada Attain A Useful Role Even Without Consensus?

Given that industry involved in supporting the current energy systems (incumbents) will eventually lose profits from Nevada's adaptation of hydrogen energy it is difficult to motivate their support. One of the payoffs for incumbents to become supportive of hydrogen is the calculation that statements of support yield goodwill which can be monetized into their stock price. This is of particular importance in winning over the utilities. Once this

public relations effort begins then there is a certain amount of hesitation to launch frontal attacks on the hydrogen vision. Once the “Nevada Hydrogen Community” is able to recruit a critical mass of hydrogen companies, influential in-state business leaders, utilities, advocacy groups (environmental and public health) and politicians there is adequate credibility to proceed with a state plan. Unilateral efforts, such as connecting the geothermal energy to hydrogen should not be underestimated.

e) How Much Time Until Nevada Enjoys Benefits?

Within one year Nevada can establish a national prominence in hydrogen if its Governor were to announce an intention to: “... support the use of sustainable and renewable energy including hydrogen by committing to government use of this clean fuel...” or declare “... hydrogen is a safe fuel and we welcome its use in Nevada...” Within six months of the passage of state laws to lower implementation barriers (eg requirement for compliance to only applicable C&S) and incentivize hydrogen use by declaring it tax free fuel Nevada would attract existing businesses to establish operations in the state. Within one month of Nevada’s casino industry announcing it will demonstrate the use of hydrogen energy it is likely several new hydrogen businesses would be started in Nevada. These timelines do not correspond to the multi-decade phasing in of hydrogen transportation because hydrogen road-maps must start with the creation of a nurturing environment for applications of technology. Like most disruptive technology hydrogen will take hold quickly where it’s champions feel welcomed.

f) Does Nevada Have The Resources Now To Push Hydrogen?

Nevada’s tourist industry offers a venue of great value for businesses seeking exposure. Nevada’s designation as a nuclear waste depository makes it a multi-decade line item for DOE funding that will include community development and infrastructure modernization tasks. Nevada’s solar environment and inexpensive desert land can host solar energy arrays which make electricity and thermal energy that is ideal for large scale renewable systems. Nevada’s proximity to California makes it an obvious growth area for hosting firms that wish to service the hydrogen highways initiative. The thriving geothermal energy operation in Reno, the imperative to preserve the Tahoe region’s environment and a market for off-grid distributed energy are all driving factors in favor of hydrogen in Nevada.

g) Will Hydrogen Serve Us For A Long Time?

Hydrogen energy is part of a portfolio of sustainable solutions meant to provide balanced service to the State. Given that it will take decades to completely replace the existing oil and natural gas based infrastructure it is likely that hydrogen can become a multi-generational solution. Hydrogen can

serve to build the economic base of the knowledge economy that will help retain talent in Nevada. Hydrogen can serve to diversify the Nevada economy and protect the quality of life in the state.

h) What Specific Policies Will Help Hydrogen in Nevada?

There are many ideas regarding policy actions in support of hydrogen. Usually tax incentives based on nurturing a growing industrial sector are the traditional starting point but hydrogen is still too young to really benefit from this approach. The following specific policies are recommended for Nevada:

- Incentivize the in-state production of hydrogen by exempting the sale of Nevada hydrogen to be used as a fuel from sales tax
- Incentivize the production of hydrogen energy equipment in the State by exempting the sale of all such equipment from sales tax
- Incentivize the development of hydrogen energy projects by setting a time and cost limit on compliance with all regulations pertaining to such projects such that project developers can create firm schedules
- Incentivize the use of hydrogen by customers by declaring officially “hydrogen is amongst the safest fuels available”
- Allow the state insurance commissioner to structure a program that establishes a liability limit for the implementation and use of hydrogen energy in state
- Implement a rule that all insurance companies accredited to sell in Nevada must offer coverage to users of hydrogen energy
- Require that all new fuel dispensing stations include the connectivity to dispense hydrogen fuel
- Offer a special tuition credit at all state universities and trade schools to reimburse students who take classes related to sustainable energy
- Offer a special incentive to companies that produce hydrogen in-state for sale to California and other states

5. Roadmap Highlights

There are four prototypical roadmaps discussed in this section:

a. Solar

There is 1.7 GW of solar electric generation installed and this capability is growing at 35% per year. Grid connected solar creates an early revenue stream

which is essential to most financial backers. Solar thrives in places with government incentives which are primarily overseas. In this scenario Nevada expands its activity in this established market and produces hydrogen for fuel instead of electricity to wheel back to the grid or use directly. The proposition is that transportation fuel is more valuable than electricity. Direct electricity values 50 kw at \$5 in contrast to the equivalent 1kg of fuel (1 gal equivalent of gasoline) resulting from electrolysis. However when the externalities of fossil fuel use are considered \$5 per kg is a sustainably priced transportation fuel while wheeled electricity is heavily discounted. This pathway offers a fallback position to simply selling solar electricity that gets discounted to \$.2 per kw directly in competition to expensive peak rates offered. In this approach local and state governments agree:

- ii. to host more solar installations
- iii. incentivize solar electric use
- iv. reduce regulatory barriers to hydrogen use
- v. qualify hydrogen from solar as RPS certified fuel
- vi. to use hydrogen fleet vehicles
- vii. to incentivize production of hydrogen fuel and equipment in state

b. Nuclear

This is a federal policy coordination challenge whereby Nevada communicates to the Federal Government that amongst the economic incentives necessary to compensate for hosting the nation's nuclear waste is a clean energy system that uses hydrogen. In this scenario the R&D institutions in Nevada will want to be involved in the current nuclear to hydrogen work being conducted by DOE since there may evolve opportunities to connect directly to the operations at Yucca Mountain or other DOE sites. In this approach local and state governments agree:

- viii. to develop a nuclear – hydrogen technical capability in-state
- ix. reduce regulatory barriers to hydrogen use
- x. qualify hydrogen from nuclear generated thermal as RPS certified fuel
- xi. to use hydrogen fleet vehicles
- xii. to incentivize production of hydrogen fuel and equipment in state

c. Market Driven

This is business driven approach which strives to attract hydrogen energy industry by creating a climate that promotes their products and services. The value of market exposure combined with high profile use of hydrogen energy would act as a magnet to bring a broad spectrum of integrators and manufacturers to Nevada. Obviously installation of hydrogen energy applications in the Casinos and convention facilities is the initial objective. The proposition that this access to large scale exposure will be highly valued by industry has been verified in discussions with many industrial executives.

In this approach local and state governments agree:

- i. to incentivize the tourist and convention industry to use hydrogen
- ii. to promote coordination of the clean energy message in branding the state “pro-hydrogen”
- iii. reduce regulatory barriers to hydrogen use
- iv. qualify hydrogen from water (electrolysis) and hydrogen from biomass (gasified) as RPS certified fuel
- v. to use hydrogen fleet vehicles
- vi. to incentivize production of hydrogen fuel and equipment in state

d. Regional

This is a “following” strategy designed to leverage the State of California’s hydrogen activity. In this scenario Nevada reaches out to connect to the “hydrogen highways” of California focusing on the value of expanding the range of hydrogen transportation from Los Angeles and San Francisco to Las Vegas and Tahoe respectively. The success of this approach depends on completion of the California plans or Nevada’s investments would be stranded. While this strategy is lower risk technically since it will likely replicate California’s installations it will also yield less economic benefit to Nevada since most of the hydrogen industry will not be incentivized to move or establish bases in state. California will control much of the pace of hydrogen adaptation and dominate most regional decisions as a result of implementing this roadmap. In this approach local and state governments agree:

- i. to incentivize the tourist and convention industry to use hydrogen
- ii. to coordinate with the State of California & their H2 stakeholders
- iii. reduce regulatory barriers to hydrogen use
- iv. qualify hydrogen from water (electrolysis) and from biomass (gasified) as RPS certified fuel
- v. to use hydrogen fleet vehicles
- vi. to incentivize production of hydrogen fuel and equipment in state

6. Effectiveness and Use of Roadmap

The expert presentations used during the roadmap forum were all posted on the web by UNLV for public use. The Nevada State Energy Office was an active participant during the entire forum and has agreed to review the roadmap for use at the state level. Representatives from DOE, DOE contractors and LANL, NETL, NREL were present and will be propagating the discussions throughout the hydrogen community. Leadership from the National Hydrogen Association Board of Directors attended the meeting as well.

7. Summary

This project yielded the conclusion that there are multiple and concurrent paths toward hydrogen adaptation. It is possible that hydrogen will succeed serving applications and stimulated by policies not yet identified.

UNLV will report on this task to the DOE. UNLV also posts the PowerPoint presentations made during the forum in order to share its contributions to the hydrogen vision. Many of the participants involved in the forum will also propagate the information provided in the forum throughout the hydrogen community. But for the roadmap to have an impact it must be used as a tool by policy makers, stakeholders and champions in a manner designed to build public support for hydrogen transitions. The broad participation of technology, policy and business experts in building this roadmap provides credibility for its application. It is likely that the hydrogen vision will continue to evolve and clearly many will use its potential benefits in service to narrow goals. Yet it is encouraging to see that there is an accommodation for multiple transition failures in the broader picture. Hydrogen energy will “leak out” like the proverbial small molecule seeking freedom regardless of the barriers to implementation.

The primary conclusion by the participants is *the roadmap must be adapted and championed by a public-private partnership*. Usually a non-profit corporation is a good rallying point but it must be lead by a board with divergent interests and backgrounds.

This roadmap will hopefully become a tool for use by other road-mapping efforts in the hydrogen community. If it becomes a standard template for other states or even countries to approach planning for a hydrogen future then it can be considered a success. At present the States of Texas, South Carolina, Pennsylvania and West Virginia have expressed interest in the UNLV approach delineated herein.

The IF, LLC team is available to answer questions and assist with use or adaptations of this document. Please contract David Haberman at ifdhllc@aol.com.

ATTACHMENT 4

UNLV-NREL COLLABORATIVE PEC PROJECT

PREPARED BY:

**NREL
February 2008**

Final Report

Project Title: UNLV-NREL Collaborative PEC Project

Project Period: August 2006-December 2007

Date of Report: February 2008

Recipient: National Renewable Energy Laboratory

Working Partners: Mowafak Al-Jassim, Yanfa Yan, Kwang-Soon Ahn, Muhammad Huda, Aron Walsh, Sudhakar Shet

Contact: Mowafak Al-Jassim, Phone: 303-384-6602, mowafak_aljassim@nrel.gov

DOE Managers: DOE HQ Technology Manager: Roxanne Garland
DOE Field Project Officer: Carolyn Elam

Project Objective: The work involves the application of theory, synthesis and characterization towards the use of metal oxide thin-films for photoelectrochemical water splitting. NREL will work together with the rest of the team members to optimize PEC performance by catalyzing or chemically modify their surface and/or evaluate alternative dopants to improve electrode degradation and/or PEC performance. The objective will be to identify, synthesize and characterize designed photoelectrode materials that provide tunable enhanced light absorption and increased catalytic activity for water splitting in order to meet the DOE targets for PEC hydrogen production.

Background: The direct photoelectrochemical (PEC) splitting of water is a one-step process for the production of H_2 using solar irradiation; water is split directly upon illumination. This direct conversion system utilizes the process where an illuminated semiconductor immersed in aqueous solution, is used to decompose water directly. This type of direct conversion system combines a photovoltaic material and an electrolyzer into a single monolithic device. Light is absorbed in the semiconductor and water is split at the semiconductor surface. The thermodynamic potential for splitting water into hydrogen and oxygen at 25 °C is 1.23 volts. Adding overvoltage losses and some energy to drive the reaction at a reasonable rate we come to a voltage of about 1.6-1.8 volts for water decomposition. In fact, current commercial electrolyzers operate between 1.7 and 1.9 volts. Translating the energy of 1.9 eV into a corresponding wavelength of light, we come to 650 nm, red light, which is in the lowest energy portion of the visible spectra. This means that nearly the entire visible spectrum has sufficient energy capable of splitting water into hydrogen and oxygen. The key is to find the right combination of a light harvesting system and a catalyst that can efficiently collect the energy and direct it towards the water splitting reaction. The simplest PEC based direct water splitting system would consist of an illuminated single gap semiconductor having a bandgap greater than 1.6 electron volts coupled to a surface catalyst immersed in an aqueous solution.

A successful PEC water-splitting semiconducting material needs to meet five primary requirements. 1 - The material needs to be stable in an aqueous electrolyte. 2 - The band gap (E_g)

should fall in the range $1.7\text{eV} < E_g < 2.2\text{eV}$, sufficient to achieve the energetics for electrolysis yet allow maximum absorption of the solar spectrum. 3 - Have a high quantum yield ($>80\%$) across its absorption band to reach the efficiency necessary for a viable device. 4 - Straddle the redox potentials of the hydrogen and oxygen half reactions with its conduction and valence band edges. 5 - Have a pathway to low-cost, high-volume synthesis. While the material properties for a working PEC device are well known, the demands on these material properties for PEC water splitting are stringent, requiring a combination of physical, chemical, structural and economic properties that no currently known material satisfies.

Tasks completed:

A. Synthesis of ZnO-based compounds

A1. Bandgap narrowing by N-incorporation

The effects of N incorporation into ZnO were investigated by first-principles density-functional theory. We predicted that N-incorporation in ZnO may lead to bandgap narrowing. This prediction has been confirmed by synthesizing N-incorporated ZnO thin films using reactive RF magnetron sputtering in N_2/O_2 gas ambient. ZnO:N films with various bandgaps were achieved by varying N concentration, which was controlled successfully by varying the RF powers. The microstructure of the ZnO:N films was characterized by various techniques. Furthermore, the photoelectrochemical properties of these ZnO:N films were measured and compared with those of pure ZnO films. We found that ZnO:N films could provide considerable photoresponse in the long-wavelength region above 600 nm as well as 500 nm, whereas the ZnO films did not show any photoresponse. It indicates that the ZnO:N films could provide more useful photoresponse in the visible light regions than pure ZnO. However, the photocurrent is yet too poor. One of the causes is the poor crystallinity. Thus, our next step will be optimizing our growth conditions to improve the quality of the ZnO:N films.

To understand the effects of N incorporation on the optical properties of ZnO, we calculated the electronic structure of N-incorporated ZnO by first-principles density-functional theory using the super-cell approach. The host super-cell contains 128 atoms. Figure 1 shows the calculated density of states (DOS) of ZnO and ZnO:N. The red curve indicates the calculated total DOS of the super-cell containing pure ZnO (marked by ZnO). The blue curve is the calculated total DOS of the super-cell containing one substitutional N atom (marked by ZnO:N). The dark-yellow curve indicates the calculated partial DOS of the N atom [marked by N(x4)], which is scaled up by 4 times. The valence band of ZnO is mainly derived from O $2p$ orbitals. The N $2p$ orbitals are much shallower than the O $2p$ orbitals. When N atoms are incorporated in ZnO, they introduce an impurity band above the valence band of ZnO. As a result, the valence band maximum (VBM) of ZnO:N becomes shallower due to the mixing between O $2p$ and N $2p$ states. In the meantime, the conduction band remains unchanged, as it is seen in Fig. 4. Therefore, the bandgap is reduced. The position of the VBM depends on the concentration of N atoms. A higher N concentration leads to a shallower VBM, and therefore, a smaller bandgap. Thus, the bandgap of ZnO can be controlled by the concentration of N in ZnO.

FIG. 1. Calculated total DOS of pure ZnO (red curve indicated by ZnO) and ZnO:N (blue curve indicated by ZnO:N) and partial DOS of the N atom (dark yellow curve indicated by N) in ZnO super-cell.

To confirm our theoretical prediction, N-incorporation into ZnO thin films was realized by RF magnetron sputtering, using a Zn metal target in mixed N_2 and O_2 ambient with low O_2 flow rate [$(O_2/(N_2+O_2)) = 5\%$]. F-doped SnO_2 (FTO, $20\text{--}23 \Omega/\square$)-coated transparent glasses were used as substrates. The distance between the target and substrate was 8 cm. The base pressure was below 5×10^{-6} Torr, and the working pressure for all synthesis was 2×10^{-2} Torr. The gas ambient was mixed N_2 and O_2 gas with a gas ratio of $O_2/(N_2+O_2) = 5\%$. Prior to sputtering, a pre-sputtering process was performed for 30 min to eliminate any contaminants from the target. Sputtering was then conducted with different RF powers from 80 and 200 W at room temperature. For comparison, a pure ZnO film was deposited at an RF power of 80 W in pure O_2 ambient, and a pure Zn_3N_2 film was deposited with an RF power of 200 W in pure N_2 ambient. All samples were controlled to have similar film thickness of about 500 nm as measured by stylus profilometry. The structure of the synthesized films was characterized by X-ray diffraction (XGEN-4000, SCINTAG Inc., operated with a Cu $K\alpha$ radiation source at 45 kV and 37 mA) and TEM (FEI Tecnai F20). The UV-VIS absorption spectra of the samples were measured by an n&k analyzer 1280 (n&k Technology, Inc.). To synthesize ZnO:N films with similar thickness, we first determined the deposition rate for different RF power. We found that the deposition rate increases linearly with the increase of RF power. However, the gas ambient has a great impact on the deposition rate. We found that the deposition rate of ZnO:N films grown in mixed N_2 and O_2 ambient is much higher than that of ZnO films grown in pure O_2 ambient, even though the same RF power was used. On the other hand, the deposition rate of the ZnO:N films grown in mixed N_2 and O_2 ambient at 200 W is similar to that of the Zn_3N_2 films grown at 200 W. The enhancement of the deposition rate in N_2 -containing ambient could be due to the nitridation of the Zn metal target surface, because the Zn nitride is more conductive than the ZnO, leading to much higher sputtering yield.

FIG. 2. X-ray diffraction curves of pure ZnO, Zn_3N_2 , and ZnO:N films grown at different RF powers. * indicates the oxynitride intermediate phase.

Figure 2 shows X-ray diffraction curves of ZnO, Zn_3N_2 , and ZnO:N grown at different RF powers. It is seen that the ZnO film exhibits poor crystallinity, due to the room-temperature sputtering process. The ZnO:N film grown at 80 W shows better crystallinity than the pure ZnO film, despite at faster deposition rate. It may be due to the significant change in the chamber ambient. For pure ZnO growth, the ambient is pure O_2 gas. For ZnO:N growth, the ambient is mainly N_2 with only 5% O_2 . When the RF power was increased to 100 W, the crystallinity again became poor. The peaks belonging to ZnO, seen in the XRD curve of the ZnO:N grown at 80 W, disappeared. When the RF power was further increased to 200 W, the film became Zn_3N_2 -like. It is also noted that when the growth ambient was changed into mixed N_2 and O_2 , a small peak, indicated by *, appeared. This peak shifted to lower angle as the RF power increased, indicating increased N concentration. These peaks indicate the form of zinc oxynitride films. The X-ray diffraction data reveal that the sample grown at 200 W became polycrystalline Zn_3N_2 -like.

The microstructure of the zinc oxynitride films was investigated by TEM. We found that the zinc oxynitride films have an intermediate ordering structure. Figure 3(a) shows a high-resolution TEM image obtained from a ZnO:N film grown at an RF power at 120 W. The grains sizes are very small, in the range of a few nanometers. Nano-probe X-ray energy-dispersive spectroscopy [Fig. 3(b)] revealed that these small grains are indeed zinc oxynitrides, with high N concentration.

FIG. 3. (a) High-resolution TEM image of a zinc oxynitride film deposited at an RF power of 120 W. (b) Nano-probe X-ray energy-dispersive spectroscopy obtained from the zinc oxynitride grains.

Figure 4(a) shows the relative absorption coefficients for the ZnO:N films grown at different RF powers. The absorption coefficient was assumed as $\alpha \propto -\ln T$ to evaluate the bandgap energies of the films. The direct electron transition from valence to conduction bands was also assumed for the absorption coefficient curves, because both of the ZnO and Zn₃N₂ films are known as direct-bandgap materials.¹ The optical bandgap for the direct electron transition is described by the following equation:¹

$$(\alpha h\nu)^2 = \beta(h\nu - E_g) \quad (1)$$

where $h\nu$ is photon energy, E_g is the optical bandgap, and β is the edge width. According to this equation, $[(-\ln T)(h\nu)]^2$ was plotted against the photon energy $h\nu$, as shown in Fig. 4(a). The optical bandgaps of the films were also determined by extrapolating the linear portion of each curve in Fig. 4(a) to $[(-\ln T)(h\nu)]^2 = 0$. They are 2.9 ± 0.07 eV (RF power = 80 W), 2.31 ± 0.10 eV (RF power = 100 W), 2.15 ± 0.12 eV (RF power = 120 W), 1.76 ± 0.14 eV (RF power = 150 W), and 1.55 ± 0.14 eV (RF power = 200 W). The bandgaps are 3.28 ± 0.04 eV and 1.52 ± 0.13 eV for

pure ZnO and Zn₃N₂, respectively. It clearly shows that the bandgap decreased with the increase of RF power.

FIG. 4. (a) Relative absorption coefficients of pure ZnO, Zn₃N₂, and ZnO:N films grown at different RF powers. (b) Optical absorption spectra of the ZnO:N films grown at different RF powers.

Figure 4(b) shows the absorption spectra of ZnO:N films grown at different RF powers. To eliminate the effect of the substrate, the absorbance was calculated by the following equation:³

$$A=1-R(\text{ZnO})-T(\text{ZnO})/T(\text{substrate}) \quad (2)$$

where R and T are the measured reflectance and transmittance, respectively. The absorption spectra show that the light absorptions are successfully shifted into visible regions with the increase of RF power. Therefore, we demonstrate that RF power could be used effectively to control the N concentration in ZnO thin films.

Nitrogen incorporated ZnO was photoelectrochemically characterized to the extent that the few samples allowed. Photocurrent spectroscopic data was collected on nitrogen lean materials. Where a signal could be detected from this technique it was transient in nature, diminishing over the time of analysis. Determination of transition type and energy from this data was complicated

by the instability of the signal. Direct and indirect transition plots of the photocurrent data appear as Figure 5. The samples by photoelectrochemistry appear to show an indirect transition.

Figure 5: Direct (left) and indirect (right) transition plots of pure ZnO and ZnO:N.

Current potential curves taken under chopped illumination revealed the ZnO:N materials to be n-type. The films deposited at a higher RF power contained more nitrogen and exhibited no response to chopped illumination. The ZnO:N sample that was deposited at 100W RF power had the greatest n-type response to chopped illumination (Figure 6). Illuminating the surface of this ZnO:N electrode immersed in pH 6 buffer with approximately 6 suns yielded only $1 \mu\text{A}/\text{cm}^2$ of anodic photocurrent at a bias of +.7V vs. SSC.

Figure 6: Chopped light I-V of ZnO:N (100W RF) in pH6 buffer.

Mott-Schottky data was collected on only one ZnO:N sample and revealed p-type conductivity with a doping density around $5 \times 10^{18} \text{ cm}^{-3}$ in the darkness. The x-intercept of the same M-S plot taken in pH6 buffer revealed a flatband potential of about 1.6 V vs. SSC. The same sample under illumination had a $3 \times 10^{19} \text{ cm}^{-3}$ doping density and 3.3 V flatband potential. The positive

shift of the flatband potential with illumination is a characteristic of n-type conductivity. The contradictory indicators of p and n-type conductivity suggest a compensated material.

A2. Bandgap narrowing by Cu incorporation

ZnO:Cu films were deposited using a reactive RF magnetron sputtering system followed by post-annealing at 500 °C or 600 °C in air for 2 hrs. Conducting transparent FTO (20-23 $\Omega/\square$)-coated glass was used as the substrate to allow PEC measurements. The distance between the Zn metal target and the substrate was 8 cm. Cu chips (2×5 mm²) were dispersed uniformly on the Zn target as the dopant source. The concentration of Cu was controlled by varying the numbers of Cu chips from 4 to 12. The base pressure was below 2×10^{-6} Torr and the working pressure was 2×10^{-2} Torr. Prior to sputtering, a pre-sputtering process was performed for 30 min to eliminate possible contaminants from the target. Sputtering was then conducted at a RF power of 100 W at room temperature. Pure O₂ gas was used as the sputtering ambient to suppress the formation of oxygen vacancies and enhance the formation of Cu doping. All of the deposited samples were controlled to have a similar film thickness of about 500 nm as measured by stylus profilometry.

The UV-VIS absorption spectra of the samples were measured by an n&k analyzer 1280 (n&k Technology, Inc.). Because our ZnO:Cu thin films were deposited on conducting substrates, electrical property analysis by Hall effect measurements were not possible. Instead, the electrical properties were measured by Mott-Schottky plots, which were obtained by AC impedance measurements. The AC impedance measurements were carried out with a Solartron 1255 frequency response analyzer in a three-electrode cell. The ZnO:Cu films were used as the working electrode, whose active surface area was about 0.25 cm². Pt mesh and Ag/AgCl in saturated KCl solution were used as counter and reference electrodes, respectively. The relative potential vs. NHE is about 0.197 V. A 0.5 M Na₂SO₄ aqueous solution was used as the electrolyte. An AC amplitude of 10 mV and frequency of 5000 Hz were used for the measurements taken under dark condition. A simple equivalent circuit model of resistance and capacity in series was used for analysis of Mott-Schottky plots.

Fig. 1 XRD of ZnO:Cu films.

Figures 7(a) and (b) show x-ray diffraction curves for as-grown and 500 °C-annealed ZnO:Cu films, respectively. The number n of ZnO:Cu(n) indicates the number of Cu chips dispersed on Zn target for the depositions. All the as-grown films had a short-range ordered,

amorphous-like structure. After post-annealing, the films exhibited polycrystalline structure, with a main peak at 34.4° corresponding to the (002) plane. We also found that the grain sizes are smaller in 500°C -annealed ZnO:Cu films than in 500°C -annealed pure ZnO films. It is seen that there are no peaks corresponding to metallic Cu or its compounds, indicating no obvious phase separation in as-grown and 500°C annealed ZnO:Cu films. We found, however, CuO phase start to form when ZnO:Cu films were annealed at 600°C . Figure 7(c) shows the comparison of XRD curves obtained from ZnO:Cu(10) films annealed at 500 and 600°C . The diffraction peaks at 35.58° and 38.63° , corresponding to $(\bar{1}11)$ and (111) of CuO phase, are only seen in ZnO:Cu(10) films annealed at 600°C .

Fig. 8. optical absorption of an as-grown ZnO film and ZnO films annealed at 500 the 600 $^\circ\text{C}$.

It is known that the Zn-O bonding energy is considerably low, only about 159 kJ/mol. Annealing at high temperature can enhance dramatically the formation of O vacancies in ZnO. To reveal the annealing effects, we measured the optical absorption of pure ZnO films annealed at different temperatures. Figure 8 shows the optical absorption of an as-grown ZnO film and ZnO films annealed at 500 the 600 $^\circ\text{C}$. It is seen that the optical absorption of the film annealed at 600 $^\circ\text{C}$ exhibit dramatic change: its absorption extends into regions of much longer wavelength, due to the formation of a high concentration of O vacancies. This significant structural change at this annealing temperature should help the formation of the CuO phase. Our results suggest that the annealing temperature should be lower than 600 $^\circ\text{C}$ to avoid the formation of CuO phase.

Figures 9(a-c) show AFM surface morphologies ($1 \times 1 \mu\text{m}^2$, height: 251 nm) of the 500 $^\circ\text{C}$ -annealed ZnO, ZnO:Cu(4), and ZnO:Cu(12), respectively. The grain size of the annealed pure ZnO film was much larger than those of the annealed ZnO:Cu films, which is in good agreement with the XRD results. Figure 9(d) shows grain size and root-mean-square (rms) surface roughness of the annealed films as a function of the number of Cu chips. The surface roughness was slightly decreased from 20 nm to 15.5 nm with the increase of the Cu chips.

FIG. 9. (a-c) AFM surface morphologies ($1 \times 1 \mu\text{m}^2$, height: 251 nm) of the 500 °C-annealed pure ZnO, ZnO:Cu(4), and ZnO:Cu(12). (d) Grain size and root-mean-square (rms) surface roughness of the 500 °C-annealed films as a function of the number of Cu chip.

Figures 10 (a) and 10(b) show XPS spectra of Cu $2p_{3/2}$ for as-grown and 500°C-annealed ZnO:Cu films with different Cu chips (4, 10, and 12), respectively. The position of the C 1s peak was taken as a standard reference with a binding energy of 284.3 eV. The measured Cu concentration in ZnO:Cu films increased from 3.0 to 9.8 at% with the increase of Cu chips from 4 to 12. Cu can have various bonding states, such as Cu^0 , Cu^{1+} , and Cu^{2+} . The Cu^{2+} has a binding energy of 933.7 eV and, in particular, it is known to produce strong, broad Cu 2p satellite peaks at the higher binding-energy region (940–945 eV) related to the presence of Cu 3d hole states. On the other hand, the Cu^0 and Cu^{1+} states have no satellite peaks. It is seen that there are no Cu^{2+} satellite peaks for both the as-grown and annealed ZnO:Cu films, indicating that Cu atoms exist in either the Cu^0 or Cu^{1+} states. The Cu^{1+} state in ZnO acts as an acceptor state. Unfortunately, the Cu^0 and Cu^{1+} states have very similar $3p_{3/2}$ values of 932.7 and 932.5 eV, respectively, which make it very difficult to distinguish them by XPS. As discussed later, this peak can be assigned to the Cu^0 state in the as-grown sample and Cu^{1+} state in the annealed samples from optical absorption measurements

Figures 11(a) and 11(b) show the optical absorption spectra of as-grown and 500 °C-annealed pure ZnO and ZnO:Cu films, respectively. To eliminate the effect from the FTO substrate, the absorbance was calculated by the following equation:

$$A = 1 - R(\text{film}) - T(\text{film})/T(\text{substrate}) \quad (1)$$

FIG. 10. XPS of

where R and T are the measured reflectance and transmittance, respectively. The as-grown and 500 °C-annealed pure ZnO films showed similar optical absorption spectra and could absorb only light of wavelength below 450 nm, due to its wide bandgap nature. Figure 11(a) shows that the absorption of the as-grown ZnO:Cu films extend into the infrared region. These absorptions may only be explained by the metallic Cu states. Because the depositions were carried out at room temperature, the ZnO:Cu films were not fully crystallized, as shown by the XRD curves. It is very likely that Cu atoms may not be fully oxidized, leaving metallic Cu in the as-grown films. The metallic Cu atoms are responsible for the absorption in the infrared region. This strongly suggests that the peaks in XPS shown in Fig. 10(a) correspond to the Cu^0 states. However, the 500 °C-annealed ZnO:Cu films did not absorb the photons in the infrared region. XRD revealed that recrystallization occurred during the annealing process. It is very likely the metallic Cu atoms were activated to occupy Zn sites during this process and the metallic Cu atoms changed their states from Cu^0 to Cu^{1+} . As a result, the optical absorption moved to shorter wavelength region, because there is no more metallic Cu-induced absorption in the infrared region. Therefore the peaks in Fig. 4 (b) can be assigned to Cu^{1+} states.

FIG. 11. Optical absorption of ZnO:Cu.

Figure 12 shows absorption coefficients of the 500 °C-annealed pure ZnO and ZnO:Cu films derived from Fig. 11(b). The optical bandgap cannot be modeled by a simple direct or indirect transition. Our theoretical study has shown that Cu 3d orbital is much shallower than Zn 3d orbital. When a Cu atom occupies a Zn site in ZnO, it introduces two main effects: (1) The strong d-p coupling between Cu and O moves O 2p up, which narrows the fundamental direct bandgap. (2) Cu 3d orbital creates impurity bands above the ZnO valance band. The transitions from the impurity bands to conduction bands are usually mixture of direct and indirect. Thus, for heavily doped ZnO:Cu thin films, their optical bandgap contains two parts, the direct fundamental bandgap and the mixed impurity bandgap. The direct optical bandgap can be described by the following equation:

$$(\alpha h\nu)^2 = \beta(h\nu - E_g) \quad (2)$$

where $h\nu$ is photon energy, E_g is an optical bandgap, and β is the edge width. The absorption coefficient (α) was calculated by the following equation:

$$\alpha = -\frac{1}{d} \ln\left(\frac{T}{1-R}\right) \quad (3)$$

where d is a film thickness. The direct optical bandgaps of the films were determined by extrapolating the linear portion of each curve in Fig. 12 to $(\alpha h\nu)^2 = 0$. The measured optical bandgap for pure ZnO films annealed at 500 °C was 3.26 eV, which is consistent with the results reported elsewhere.¹³ The direct optical bandgaps measured for ZnO:Cu films annealed 500 °C gradually decreased from 3.16 to 3.05 eV with the increase of the number of Cu chips. These bandgap reductions are mainly caused by the moving up of the valance band. Furthermore, the impurity bands cause additional bandgap reduction as shown by the absorption tails below the 3.0 eV. In these cases, it is difficult to give defined bandgaps, as shown in inset of Fig. 12.

The Cu^{1+} states indicate that annealed ZnO:Cu thin films should be p-type. To confirm the p-type conductivity, Mott-Schottky plots are measured and shown in Fig. 7. Mott-Schottky relationships on n-type and p-type semiconductors are expressed according to the following equations;

$$\frac{1}{C^2} = \left(\frac{2}{e_0 \epsilon \epsilon_0 N_d}\right) \left((E - E_{fb}) - \frac{kT}{e_0}\right) \quad \text{for n-type} \quad (4a)$$

$$\frac{1}{C^2} = \left(\frac{2}{e_0 \epsilon \epsilon_0 N_a}\right) \left((-E + E_{fb}) - \frac{kT}{e_0}\right) \quad \text{for p-type} \quad (4b)$$

where C is the depletion layer capacitance per unit of surface area, N_d and N_a is the donor and acceptor densities, respectively, ϵ_0 is the permittivity of vacuum, ϵ is the dielectric constant of the semiconductor, E is the electrode potential, E_{fb} is flat-band potential, and kT/e_0 is the temperature dependent term in the Mott-Schottky equation. Figure 13(a) shows the Mott-Schottky plot of the 500 °C-annealed pure ZnO film. It has a positive slope in the linear region of the plot, indicating the n-type semiconductor according to equation (4a). Assuming the dielectric constant of the samples as approximately 8.5,²⁶ the donor concentration of the annealed ZnO film could be evaluated from the slope of the linear part, which was $2.3 \times 10^{16} \text{ cm}^{-3}$. Figure 13(b) shows the Mott-Schottky plot of the 500 °C-annealed ZnO:Cu(12) film, which had a negative slope indicating p-type behavior. It indicates that the Cu^0 metallic states were activated into the form of Cu^{1+} substitutional acceptor states by the post-annealing process at 500 °C, because the Cu^0 metallic states can not result in the p-type semiconductor.¹² In a similar manner, all other 500 °C-annealed ZnO:Cu films in this experiment showed negative slopes (not shown here). To confirm p-type conductivity, open-circuit voltage (OCV) and photoelectrochemical (PEC) characteristics for the 500 °C-annealed pure ZnO and ZnO:Cu films were also investigated (not shown here). The OCV value of the ZnO:Cu films increased with light illumination, whereas the OCV value of the pure ZnO decreased with light illumination. Moreover, the PEC characteristics

FIG. 12. Absorption co-efficient of ZnO:Cu

of the ZnO:Cu films under chopped light illumination showed p-type photocurrent at negative voltage (-0.5 V), whereas the pure ZnO film did not show any photoresponse at -0.5 V. These investigations confirm that the 500°C -annealed ZnO:Cu films are p-type semiconductors. The acceptor concentrations of the films were evaluated from the slope of the linear part in Fig. 13(b) with the equation 4(b). Figure 13(c) shows the carrier concentrations of the 500°C -annealed ZnO and ZnO:Cu films. The acceptor concentrations of the 500°C -annealed ZnO:Cu films were increased from 1.8×10^{19} up to $2.8 \times 10^{20} \text{ cm}^{-3}$ with the increase of the Cu chips as expected. Our preliminary results indicate that the ZnO:Cu films are not very stable in Na_2SO_4 solution under illumination. Further thorough investigation on PEC properties under the illumination and the stability of the ZnO:Cu films will be carried out and will be published elsewhere.

In conclusion, ZnO:Cu films were synthesized on the FTO substrates by using a reactive RF magnetron sputtering with different number of Cu chips on the Zn metal target followed by post-annealing process. We found that post-annealing at 600°C caused the formation of CuO phase in the ZnO:Cu films, whereas 500°C -annealed films did not. XPS and optical absorption indicated that some of the Cu in as-grown ZnO:Cu films are metallic. They can be converted into Cu^{+1} acceptor states by post-annealing at 500°C in air. Mott-Schottky plots and optical absorption measurements revealed that both p-type and bandgap significantly reduced ZnO thin films were synthesized successfully by heavy Cu-doping. However, we found that ZnO:Cu samples are not very stable in aqueous solutions.

A3. Aligned ZnO nanorods

We have synthesized pure ZnO and ZnO:N films at different temperatures. In addition to the enhancement of crystallinity, we further find that deposition in pure Ar ambient produces polycrystalline ZnO films, whereas deposition in mixed Ar and N_2 ambient leads to the formation of single crystal ZnO nanorods aligned along the c-axis at temperatures above 300°C . ZnO:N films with aligned nanorods grown at 500°C exhibit significantly enhanced PEC

FIG. 13. MS plots of ZnO:Cu

response, compared to polycrystalline ZnO thin films deposited at the same temperature. Our results suggest that the deposition ambient can be used to control the morphology of ZnO thin films and aligned single crystal nanorods can be potentially beneficial for PEC performance.

Two sets of samples were deposited. One set was deposited in mixed Ar/N₂ gas ambient. This set of sample is referred to as ZnO(Ar/N₂). The second set of samples was deposited in pure Ar ambient and is referred to as ZnO(Ar). ZnO targets are used in these depositions. Transparent conducting FTO (20–23 Ω/□)-coated glass was used as the substrate to allow PEC measurements. The distance between the ZnO target and substrate was about 10 cm and the substrates were rotated to enhance deposition uniformity. Substrate temperatures were controlled by irradiative Hg lamps and indirectly measured by thermocouple located below substrate holder. The base pressure was below 1×10^{-6} torr and the working pressure was 5×10^{-3} torr. The chamber ambient was either pure Ar or the mixed Ar and N₂ with gas flow ratio of $N_2/(Ar+N_2) = 5\%$. This low N₂ gas flow ratio was used to obtain similar deposition rate (~ 4.7 nm/min) with the ZnO(Ar) films, because the deposition rate can also have influence on the film crystallinity. Prior to sputtering, a pre-sputtering cleaning was performed for 20 min to eliminate possible contaminants from the target. Sputtering was then conducted at an RF power of 200 W. All the deposited samples were controlled to have similar film thickness of 1 ± 0.05 μm as measured by stylus profilometry.

We first see how the presence of N₂ in the ambient can promote the formation of aligned nanorods in ZnO thin films at substrate temperature higher than 300 °C. X-ray diffraction curves were observed for the ZnO(Ar/N₂) films and ZnO(Ar) films deposited at different substrate temperatures. We found that the crystallinity of ZnO films increases gradually with the increase of substrate temperatures in both cases. With the increase of substrate temperature to 500 °C, the (0002) peak of the ZnO(Ar/N₂) film was enhanced greatly. With the increase of substrate temperature, the N concentration decreased rapidly and disappeared at temperatures above 300 °C. ZnO(Ar/N₂) films grown at temperatures below 200 °C exhibited random orientation and larger (0002) FWHM values than the ZnO(Ar) films grown at the same temperatures. This is because high concentration of N is incorporated in the ZnO(Ar/N₂) films at these temperatures. It is known from recent reports that incorporated N atoms can deteriorate the crystal structure and modify growth mode. However, the (0002) FWHM values of ZnO(Ar/N₂) films increase rapidly when the substrate temperatures are above 300 °C because no significant N can be incorporated at these temperatures. At substrate temperature above 300 °C, ZnO(Ar/N₂) films exhibit much smaller FWHM values than the ZnO(Ar) films. The rapid growth of the FWHM values indicates either increased crystallinity or formation of nanorods or nanowires along the c-axis.

The formation of aligned ZnO nano-rods were confirmed directly by FE-SEM. Figures 14 (a) and (b) show top-views of the ZnO(Ar) and ZnO(Ar/N₂) films, respectively, deposited at substrate temperature of 500 °C. It clearly shows that there was not nanorod structure in the ZnO(Ar) film, whereas the ZnO(Ar/N₂) films at 500 °C exhibited vertically aligned, single crystal hexagonal like nanorods with flat (0002) surfaces. No metal clusters were found at the end of the nanorods, indicating that the growth mechanism is not the catalyst-assisted vapor-liquid-solid (VLS) growth. Recently, catalyst-free ZnO nanorods/nanowires have been synthesized by various chemical and physical techniques such as plasma-enhanced chemical vapor deposition, metalorganic vapor-phase epitaxy, pulse laser deposition. The nanorod

structures provide high surface areas and superior carrier transport (or conductivity) along the c-axis, which may lead to increased interfacial reaction sites and the reduced recombination rate. Therefore, the aligned nanorod films deposited at 500 °C should lead to enhanced PEC response.

Fig. 14. SEM of (a) ZnO film grown in Ar and (b) ZnO grown in mixed Ar and N₂ ambient

Fig. 15. Photocurrent-voltage curves of (a) ZnO(Ar/N₂) nanorod and (b) ZnO(Ar) films, deposited at 500 °C under (red curve) continuous illumination, (black curve) dark condition, and (blue curve) light on/off illumination with an UV/IR filter. Electrolyte and scan rate were 0.5 M Na₂SO₄ mild aqueous solution and 5 mV/s, respectively.

We now investigate the PEC responses for the ZnO films deposited in different ambient. Figures 15(a) and (b) show photocurrent-voltage curves of the ZnO(Ar/N₂) and ZnO(Ar) films deposited at 500 °C, respectively, under continuous illumination (red curve), dark condition (black curve), and light on/off illumination (blue curve) with an UV/IR filter. Both ZnO films show very small dark currents up to potential of 1.4 V. The photocurrents under light on and off conditions are the same as the under illumination and dark currents, respectively, because of the small dark currents. It is seen that the ZnO(Ar/N₂) nanorod film deposited at 500 °C exhibit much higher photocurrents than the ZnO(Ar) film deposited at the same substrate temperature.

To see the effects of substrate temperature on PEC response, we measured photocurrent at 1.2 V potential for ZnO(Ar/N₂) and ZnO(Ar) films under continuous illumination with UV/IR filter. Figure 16 shows the measured photocurrents as a function of the substrate temperature for the ZnO(Ar/N₂) and ZnO(Ar) films. At low substrate temperatures (below 300 °C), the photocurrent

of ZnO(Ar/N₂) films are similar to that of ZnO(Ar) films, though these ZnO(Ar/N₂) films have smaller bandgaps than ZnO(Ar) films. For these ZnO(Ar/N₂), the low crystallinity should be responsible for the small photocurrents. However, the photocurrent increases for ZnO(Ar/N₂) films as the substrate temperature increases. The ZnO(Ar/N₂) film deposited at 500 °C exhibits the best photoelectrochemical response, more than two times higher than the ZnO(Ar) films deposited at the same temperature. The enhancement can be attributed to the aligned nanorod structure along the c-axis and additional light absorption in the long wavelength regions.

Fig. 16. Photocurrents measured at 1.2 V as a function of the substrate temperature for the ZnO(Ar/N₂) and ZnO(Ar) films.

In conclusion, in the last quarter, we have investigated the structural properties, optical absorption, and PEC responses for ZnO deposited at different temperatures by sputtering the ZnO target in pure Ar gas and mixed Ar/N₂ gas ambient. We found that the presence of N₂ in the growth ambient help to promote the formation of aligned nanorods and impurity bands at high substrate temperature of 500 °C, resulting in a significantly enhanced PEC response, compared to ZnO(Ar) films deposited in pure Ar gas ambient. Our results suggest that deposition ambient can be used to produce desired properties of thin films and aligned nanorods may help to improve PEC performance.

A4. Bandgap narrowing by Ga, N co-incorporation

We have applied a different approach to enhance the incorporation of N into ZnO films, i.e., Ga and N co-doping. The Columbic attraction between Ga and N is expected to result in reduced formation energies and thus increased N concentration. In addition, co-doping will introduce effectively charge compensation and thus suppress harmful recombination. We have synthesized ZnO:(Ga, N) thin films by dispersing Ga₂O₃ powders in Zn targets. ZnO:(Ga, N) thin films with reduced band gap and increased crystallinity have been successfully synthesized. These films exhibited greatly enhanced photocurrent comparing to all ZnO thin film synthesized by now. The co-doping method should be applicable to other wide gap metal oxides for band gap reduction.

ZnO:(Ga,N) films were prepared using a reactive RF magnetron sputtering, followed by post-annealing at 500 °C in air for 2 h. Conducting transparent FTO (20–23 Ω/□)-coated glass was used as the substrate to allow PEC measurements. The distance between the Zn metal target and substrate was 11 cm and the substrates were rotated to enhance deposition uniformity. Ga₂O₃ powders (0.007 g) were dispersed uniformly on the Zn target of 3" in diameter as the Ga co-

dopant source. Working pressure was 2×10^{-2} torr. The sputtering ambient was mixed N_2 and O_2 with an oxygen gas ratio $O_2/(N_2+O_2) = 2.5\%$. Sputtering was conducted at a RF power of 100 W at room temperature (RT). For the comparison, a pure ZnO:N films was deposited under the same conditions without Ga_2O_3 . This ZnO:N film was annealed at 500 °C [referred to as ZnO:N(1)]. Another ZnO:N film was sputter-deposited at the substrate temperature of 500 °C [referred to as ZnO:N(2)]. All of the samples were controlled to have similar film thickness of about 500 nm as measured by stylus profilometry.

Figure 17 shows the XRD curves for ZnO:N(1), ZnO:N(2), and ZnO:(Ga,N) films. The ZnO:N(1) film is found to exhibit the oxynitride structure. Its crystallinity is very poor, due to the high concentration of N incorporated in the film. Its crystallite size, estimated according to the Scherrer equation, is approximately 16 nm. ZnO:N(2) film exhibits much better crystallinity (crystallite size: 29 nm) than ZnO:N(1) due to higher substrate temperature. However, XPS results indicate that almost no nitrogen is present in the ZnO:N(2) films grown at 500 °C, indicating that the nitrogen can not be incorporated in ZnO films at high substrate temperatures. The co-doped ZnO:(Ga,N) film exhibits significantly enhanced crystallinity (crystallite size: 40 nm). It may be attributed to the Ga source of the Ga_2O_3 . The ionic radius of Ga^{3+} is close to that of Zn^{2+} in the substitutional site and the Ga oxide source provides more oxygen during the sputtering process, leading to the decreased oxygen vacancies and therefore better crystallinity. The similar effect of Ga oxide source on the crystallinity of ZnO has been also reported by other group. The ZnO:(Ga,N) film is found to contain N, but the concentration is much lower than that of the ZnO:N(1) film. It indicates that the oxygen induced from the Ga_2O_3 source can suppress N incorporation, because of the high chemical activity of oxygen.

Fig. 17. XRD of three samples: ZnO:N(1), ZnO:N(2), and ZnO:(Ga,N)

Figure 18 shows the optical absorption coefficients for the samples mentioned above. The direct electron transition from valence to conduction bands was assumed for the absorption coefficient curves, because both of the ZnO and Zn nitride films are known as direct-bandgap materials. The optical bandgaps of the films were determined by extrapolating the linear portion of each curve. The bandgap of the ZnO:N(2) film grown at 500 °C is 3.27 eV, which is corresponding well to the bandgap of the pure ZnO. The ZnO:N(1) film exhibited the significantly decreased bandgap of 1.75 eV, due to the high concentration of the N. The co-doped ZnO:(Ga,N) film exhibited lower bandgap (3.19 eV) than the ZnO:N(2) film grown at 500 °C. However, this bandgap was much higher than that of the ZnO:N(2) film, due to much less N concentration. The bandgap

reduction is due to the moving up of the valance band mixed with the N states. The N incorporation also generates an impurity band above the valance band of ZnO, leading to an additional bandgap reduction and the absorption tail. The impurity band can enable light absorption in the long-wavelength regions, as shown in inset of Fig. 18.

Fig. 18. Optical absorption coefficients of the ZnO:N(1) film, ZnO:N(2) film grown at 500 °C, and the ZnO:(Ga,N) film, respectively. Inset shows the optical absorption curves.

Figure 19(a) shows Mott-Schottky plots of the ZnO:N(1) film, the ZnO:N(2) film grown at 500 °C, and the co-doped ZnO:(Ga,N) film. All samples exhibit positive slopes, indicating n-type semiconductivity. The donor concentrations of these films are estimated from the slopes of the Mott-Schottky plots to be approximately 9.93×10^{17} , 2.1×10^{17} , and 2.43×10^{17} /cm³ for the ZnO:N(1) film, the ZnO:N(2) film grown at 500 °C, and the ZnO:(Ga,N) film, respectively. It is interesting to note that the co-doped ZnO:(Ga,N) film exhibited similar donor concentration to the ZnO:N(2) film grown at 500 °C, despite the substitutional N₂ molecules. It may be attributed to the compensation effect of the Ga and/or the decreased oxygen vacancies. Figure 19(b) shows the calculated depletion width (*W*) values with the potential for the samples from Fig. 19(a). It shows that the ZnO:(Ga,N) film and the ZnO:N(2) film grown at 500 °C exhibited significantly larger *W* values, compared to the ZnO:N(1) film, due to their lower donor concentration.

Fig. 19. (a) Mott-Schottky plots of the ZnO:N(1) film, ZnO:N(2) film grown at 500 °C, and the ZnO:(Ga,N) film, respectively. (b) W values with the potential, estimated from Fig. 3(a).

Figure 20(a) shows the photocurrent-voltage curves of ZnO:N(1), ZnO:N(2), and ZnO:(Ga,N) films under the illumination with an UV/IR filter. The inset in Fig. 4(a) also shows the enlarged photocurrent-voltage curves. It clearly shows that the ZnO:(Ga,N) film exhibited significantly increased photocurrents, comparing to the other films. At the potential of 1.2 V, the photocurrents are 484, 55, and 38 μAcm^{-2} for the ZnO:(Ga,N), the ZnO:N(1), and ZnO:N(2) films, respectively. To investigate the photoresponses in the long-wavelength region, a green color filter was used in combination with the UV/IR filter, as shown in Fig. 20(b). The ZnO:N(2) film grown at 500 °C exhibited no clear photoresponse, due to its wide bandgap. The ZnO:(Ga,N) film exhibited much higher photocurrent than the ZnO:N(1) film, despite much less light absorption. It indicates that the high recombination rate between the photogenerated electrons and holes is present in the ZnO:N(1) film, due to its poor crystallinity and small W value. On the other hand, the co-doped ZnO:(Ga,N) film exhibited remarkably increased crystallinity and good W value, in addition to the reduced optical bandgap [comparing to the ZnO:N(2) film grown at 500 °C or pure ZnO], resulting in greatly enhanced photoresponse. So far, the Ga to N ratio is not yet optimized. With further optimization, we should be able to make ZnO:(Ga,N) films with p-type conductivity and even more enhanced PEC properties.

Fig. 20. Photocurrent-voltage curves of ZnO:N(1), ZnO:N(2), and ZnO:(Ga,N) film, respectively, under the illumination (a) with an UV/IR filter and (b) with the combined green and UV/IR filters. Insets show the enlarged photocurrent-voltage curves. Scan rate of 5 mV/s was used.

References:

- 1 M. Futsuhara, K. Yoshioka, and O. Takai, *Thin Solid Films* **322**, 274 (1998).

- 2 F. K. Shan, B. I. Kim, G. X. Liu, Z. F. Liu, J. Y. Sohn, W. J. Lee, B. C. Shin, and Y. S. Yu, *J. Appl. Phys.* **95**, 4772 (2004).
- 3 K. Keis, L. Vayssieres, H. Rensmo, S. E. Lindquist, and A. Hagfeldt, *J. Electrochem. Soc.* **148**, A149 (2001).
- 4 Yanfa Yan, M. M. Al-Jassim, Su-Huai Wei, *Doping of ZnO by group-IB elements*. Applied Physics Letters, 2006. **89**: p. 181912-181914.

B. Theory

B1. Theory on WO₃: electronic structure and oxygen site doping

The University of Hawaii (UH) team has been working on WO₃ based materials for PEC water splitting. WO₃ is easy to make and generally provide good photocurrent. However, its bandgap of 2.6 eV is a little too large to absorb photons in the full visible regions. Thus, bandgap reduction of WO₃ is also necessary. Like in other metal oxides, N is a potential candidate for bandgap reduction. Therefore, it is needed to theoretically study the effects of N-incorporation in WO₃. Furthermore, the conduction band minimum (CBM) of WO₃ is a little too low to drive H reaction. For spontaneous water splitting, the CBM of WO₃ needs to be shifted up. UH has tried to incorporate Mo in WO₃ to shift up the CBM. However, it is not known if the incorporation of Mo would indeed shift up the CBM. Therefore, we also studied theoretically the effects of Mo-incorporation in WO₃. The approach used in this study is the first-principles density-functional theory, where total energies of the systems are calculated self consistently.

FIG. 21. Calculated band structure for WO₃ with a N_O atom. Left: spin up, right: spin down

The structure of WO₃ used in our study is the room temperature monoclinic structure. Various configurations for N-incorporation, such as substitutional, interstitial, split interstitial,

dimers and trimers, have been considered. Figure 21 shows calculated band structures for a supercell containing a substitutional N atom (N_O). The left panel is for spin up states and the right panel is for spin down states. It is seen that the inclusion of N_O atom has caused the spin polarization. In the left panel, N-induced states are close to the top of the valence states of WO_3 . In the right panel, N_O induced band is inside the bandgap. The overall effects for a N_O atom would be introducing an impurity band above the valence band of WO_3 .

We found that interstitial N atoms (N_i) can also introduce impurity bands. However, the location of the impurity bands induced by N_i is different from that induced by N_O . To show the difference, we show in Fig. 22 the partial density of states (PDOS). The left panel is the PDOS for N_O . The right panel is for N_i . We see that in both cases, the spin up and down DOS for the N atom is different, revealing that the N atoms are spin polarized. In the N_O case, the up and down DOS for O atoms away from the N_O atom is the same. In the case of N_i , fully occupied impurity bands are formed just above the original valence bands, as can be seen the relative positions of N_i p-bands (orange DOS) and that of p-bands of oxygen atom (green DOS) situated far from the N atom, shown in figure 9 (right panel). This also shows the O atom bonded to the N_i atom has obvious difference in spin up and down DOS (see the purple DOS in the right panel) due to induced exchange splitting from nitrogen atom. In addition to this partially occupied N_i -induced impurity bands are formed very close to the CBM of WO_3 which results in a further bandgap reduction from the fundamental WO_3 gap.

FIG. 22. Calculated PDOS for WO_3 with a N_O atom (left) and a N_i atom (right)

Thus, overall our calculations suggest that N-incorporation in WO_3 should result in bandgap reduction. To see the effect directly, we have calculated the optical absorption coefficient for pure WO_3 and a WO_3 super cell with a N_O atom (equivalent to about 6 % N). Figure 23 shows the calculated optical absorption coefficient. The bandgaps were corrected by simply opening the gaps to experimentally observed gaps. It is seen that the substitutional N atom results in extra absorption in the low energy range, indicating reduced bandgap. Higher density of nitrogen doping shows increasing absorption at the lower energy range.

FIG. 23. Calculated absorption coefficient for pure WO₃ (left) and WO₃ with a NO atom (right)

For Mo-incorporation in WO₃, we have considered a Mo atom occupying a W site. To look at the effects induced by Mo-incorporation, we have calculated PDOS of O, W, and Mo atoms. The upper panel in Fig. 24 shows the spin up and spin down p-DOS of an O atom bonded to the Mo atom and an O atom away from the Mo atom. It is seen that they are almost the same. Because the VBM of WO₃ is mainly derived from O 2p states, the results indicate that Mo-incorporation would not affect the position of VBM. Because the CBM of WO₃ is mainly derived from W d states, we have calculated PDOS for both W and Mo atoms, as shown in the lower panel in Fig. 24. It is seen that the edges for the W d-state and the Mo d-states are exactly the same. Thus, Mo-incorporation in WO₃ would not shift up the CBM of WO₃.

FIG. 24. Calculated PDOS for O atoms (upper) and W and Mo atoms (lower)

In conclusion, our first-principles density functional theory calculations suggest that N-incorporation in WO_3 should result in reduced bandgap leading to enhanced absorption in visible light regions. Mo-incorporation in WO_3 may not be able to shift up the CBM.

B2. Theory on WO_3 : cation site doping and co-doping

We explored the effects of doping with more possible impurities. Our plan was to introduce transition metals who have shallower d orbitals than W 5d, so that the coupling between these transition metals and O 2p orbital may help for band gap reduction. In our calculations, we have considered Ta and Hf. In addition, co-doping such as Ta-F, Re-N as well as N-H has also been investigated.

In case of a Ta atom substitution two facts need to be considered, firstly it has only one less 5d electron compared to W atom, and secondly it differs in electronegativity by 0.86 Pauling from W atom. So substitution of Ta in place of W would create extra ionicity in the crystal, and would remove the degeneracies from the bands edges. Hole states are present on top of the valence band, as can be seen clearly from the atomic DOS plot (Figure 25). Band gap was found to be 1.21 eV and 1.12 eV for spin up and down band respectively. Here the reason for the band gap reduction, for example, in the spin down channel is that the valence band was raised in energy by 0.1 eV. The valence band edge consists of O-p bands which is near the Ta atom, as expected. Interestingly, onset of DOS of d-bands from both W and Ta atoms starts almost from the Fermi energy, whereas for WO_3 it starts from below 0.7 eV from the Fermi level. This indicates some d-character at the upper part of the valence band. However, the conduction band minimum remained almost the same, in fact went down a little, by less than 0.09 eV. It is interesting to note that, the Ta-d bands were formed about 0.6 eV behind the conduction band edge. This gives indication that with optimal Ta substitution, conduction band could also be raised a little. Similarly, an Hf atom has 1.06 Pauling less electronegativity and two 5-d electrons less than W atoms, and one should expect a greater change in the WO_3 structures. For example, exchange-splitting in the O-p bands bonded to the Hf-atom is higher, as a result the hole states are broader in the spin-down band. Here also in the conduction band, Hf-d band formed about 1 eV behind the W-d band which constitutes the conduction band edge. However, the band gap reduces to 1.23 eV and 1.07 eV respectively for spin up and down bands. So, spin up band gap increases and spin down band gap decreases a little compared to the Ta substitution. Higher exchange-splitting in Hf substitution is responsible for this. Here also, valence band went up and CBM went down by almost the same amount as Ta atom substitution. Both of these two metal substitution cases result in magnetic states due to charge mismatch between W, Ta and Hf atoms. However, as we can see that in these cases exchange-splitting is much smaller than the band width, hence the resultant magnetic moments could be non-ferromagnetic. Overall, magnetic moments in these cases would not add any extra factor to optical absorption.

Fig. 25. Calculated PDOS of WO_3 containing (a) a substitutional Ta atom and (b) a substitutional Hf atom.

Addition of an extra nitrogen atom as an interstitial impurity added to the substituted Ta or Hf atom creates interestingly different situation. In case of Ta the band gap is almost non-existent for the majority spin, whereas for the minority spin there is a gap of 1.12 eV. This situation could be an example of half-metal. In case of Hf there is a gap of 0.60 eV and 0.86 eV for the majority and minority spin, respectively. Because of the impurity bands due to the extra N atom and the structural deformation, there is a splitting of valence bands for both type spin. In case of Hf, there is a greater exchange splitting of N-p bands, 0.8 eV, which is large compared to the corresponding band width. Also, though the collective valence band's up-ward shift is significant, conduction band shift is very small. Similar situation occurs when an extra O atom is used as interstitial instead of N atom. One point is worth to note here is that, in case of Hf (Ta), the extra O (N) has a half-filled, narrow and high DOS at the Fermi level for the minority (majority) spin. This type of behavior at Fermi level usually causes further electronic relaxation. This issue will be treated in greater details elsewhere. Interestingly Ta+N and Hf+O in WO_3 make it a half metal and p-type materials, respectively. Other two combinations, Ta+O and Hf+N, have full filled valence bands. In general, substitution of metal atoms may help to shift the band gaps when the substituted metal can add some ionicity to the system, however, adding interstitial impurity to it gives some extra control on its conductivity.

We would now discuss co-doping in WO_3 to avoid the charge mismatch situation. We have seen in the preceding discussion that single anion or cation substitution creates unsaturated bonds which contribute to several distortions in the band structures. Only in the case for Mo substitution, the overall band shapes were undistorted, but unfortunately it did not raise the band edges at higher energies. As a first example of codoping, if in case of N substitution one W atom bonded to N atom is replaced by Re atom, then the Re-N would be isovalent to W-O.

As expected from the DOS plot (Figure 26 mainly composed of W-d band, came down a little by about 0.10 eV. The minimum band gap, 1.03 eV, in this case is indirect at ($B \rightarrow \Gamma$). Similarly in case of a Ta atom substitution, if another F atom is substituted for O, then Ta-F would again be isovalent to W-O dimer. Here band gap is direct at Γ point and is 1.21 eV, little less than WO_3

band gap. The valence and conduction band edges both have upward shift by 0.2 eV and 0.1 eV, respectively. F atom p-band did not contribute to the valence band maximum, rather started from 0.6 eV below the Fermi level and hybridize mainly with the d-bands. Similar to Re-N doping, the conduction band minima has mainly the W-d character. Ta-d band starts at energy that is 0.20 eV higher. Overall the Re-N and Ta-F co-doping has similar band behavior, except for Ta-F where there should be some local ionic character due to large mismatch in their electronegativity.

Fig. 26. Calculated total DOS of WO₃ containing (a) Re-N pair and (b) a Ta-F pair.

Similarly, an O atom can be substituted by an N atom with one H atoms attached to it. The NH molecule then would be isovalent to O, and the charge mismatch would be avoided. The relaxed N-H distance, substituted for oxygen, was found to be 1.05 Å. Here, due to the presence of an extra electron, provided by the hydrogen atom, the partially filled N-2p band at Fermi level is now completely filled. The ionic nature of the N-H bond is clear from the fact that the N 2p band near the Fermi level is not hybridized with the H-1s band (see Fig. 27). Here, this N 2p DOS is slightly detached, about 0.10 eV, from the rest of the valence band. This is counter intuitive, as one would expect that occupation by an electron would in general lower the energy of a band. Opening a gap would only suggest that the resulting structure might be distorted significantly, at least locally. H-s band has negligible contribution to the upper part of the valence band. From the projected charge distribution, one can see that W atoms closer to the NH loose some charges due to higher electro-negative effect produced by it. This suggests an upward lifting of the conduction band. It was indeed found that the upward shift in energy for the valence and conduction band edges are significant here, 0.60 eV and 0.4 eV respectively. The band gap in this case was found to be 0.89 eV, which is 0.42 eV less than the undoped WO₃. It is interesting to compare that, as discussed earlier, only N substitution did not move the conduction band minima, whereas the valence band minima was raised only by 0.2 eV with the lowest band gap of 1.04 eV. One of the main feature of this present configuration is that hydrogen atom did not bonded with the W atom, as N did, rather it reaches out for the O atom on the other chain, and the O-H distance is 1.81 Å. This distortion is responsible for the little gap opening at top part of

the valence band. The valence band edge is consists of the O-p and N-p bands. The presence of the Hydrogen atoms with nitrogen do not act the same way an oxygen atom would do. This is because, though O atom and NH are isovalent, in case of NH it is more electronegative than O atom. As a result, NH compound attract more electrons from W atoms and the ionicity of the N-W bonding increase. This extra ionicity is responsible for the conduction band's upward shift.

Fig. 27. Calculated total DOS of WO₃ containing a substitutional N-H pair.

In conclusion, in the last quarter, we have studied the effects of transition metal in WO₃. We found the incorporation of Ta and Hf can lead to the up-shift of VBM of WO₃, but the effects to CBM are smaller unless enough Ta and Hf are incorporated. We have also studied the effects of co-doping in WO₃. We found co-doping can lead to enhanced impurity-incorporation, and specially N-H codoping has significant effect on the CBM.

B3. Theory of CoAl-oxides and ZnO:GaN

Background: Recently, Woodhouse *et al.* have reported very interesting behaviors for the Co-Fe-Al oxide spinel system. With reported optical band gaps of between 1.1eV and 1.65eV for Co₃O₄ and 0.14eV for low temperature Fe₃O₄, these two binary oxides have limited application in the PEC splitting of water. On introducing Al, the Co-Fe-Al oxide spinel system can exhibit optical band gaps of between 1.6 eV and 2.0 eV and generate a strong p-type photocurrent, which is ideal for PEC splitting of water and good PEC properties. In addition, other interesting behavior is found. For example, when the experiment is repeated without the Fe precursor the photocurrent in the sample is reduced threefold, indicating that Fe does have an important role to play. X-ray diffraction revealed that the lattice constants of the materials are very similar within a large compositional range, which is very close to that of Co₃O₄. Unfortunately, although it is thought that the active material is Co and Al rich, further insight is restricted by the limited amount of information available about the properties of these spinels. For ZnO, our recent experimental results have shown that band gap reduction of ZnO using N alone cannot lead to significantly improved photocurrent. We found that the incorporation of high concentration of N can result in reduced band gap of ZnO and enhance photon absorption. However, the charged N atoms are effective recombination centers, which kill the photo generated electron hole pairs. In addition, we found it is difficult to incorporate N in ZnO at high temperature just by sole N dopant. To overcome these problems, we calculated the effects of co-doping ZnO with Ga and N.

With a view to providing a better basic understanding of these Co, Al and Fe containing oxides, we have calculated the electronic structure of nine stoichiometric spinels in both the normal and inverse structures, including the hypothetical Al_3O_4 compound. Calculations are performed using gradient corrected density functional theory with the Co and Fe 3d states treated with on-site correction for Coulomb interactions (DFT+U). In this study we have calculated the electronic structure of three binary and six ternary Co, Fe and Al containing oxide spinels. The trends in the calculated lattice constants agree well with the available experimental data. Preference for the octahedral spinel sites are found in the order $\text{Fe} < \text{Co} < \text{Al}$. The electronic band gap of Co_3O_4 is shown to remain largely unchanged as Al is substituted into the lattice forming Co_2AlO_4 . Stoichiometric Fe_3O_4 is found to be semi-metallic due to the partial occupation of the octahedral Fe 3d conduction band. For Fe_2AlO_4 , the coupling between the octahedral Fe sites is broken, resulting in a finite band gap. For both CoAl_2O_4 and FeAl_2O_4 an increase greater than 1eV is observed in the band gaps as the octahedral sites are replaced by Al. However, the unsatisfied valence state of Fe in FeAl_2O_4 results in partial occupation of the conduction band. From the stoichiometric, defect-free systems studied, CoAl_2O_4 has been preliminarily identified as having a direct electronic band gap close to the range suitable for photocatalytic activity in the splitting of water. However, future work is needed to assess the effects of intrinsic defects, extrinsic dopants, and local disorder on the electronic structure and resulting optical transitions of this system.

The calculated structural and electronic properties of each spinel studied, including the hypothetical Al_3O_4 , are summarized in Figure 28. While the Co and Fe 3d states have been shown to be active in determining the electronic and magnetic properties of these spinels, Al makes little contribution to the valence density of states. As such, when a ternary oxide is formed with majority Co and minority Al composition (Co_2AlO_4), Al occupies only half of the available octahedral sites, but it is the remaining octahedral and tetrahedral Co sites that determine the properties. Hence, the electronic band gap is largely unchanged from Co_3O_4 to Co_2AlO_4 . Increasing the Al composition of the ternary oxide to CoAl_2O_4 results in a loss of the octahedral Co sites, and as such, the band gap is increased as the octahedral Co 3d contribution to the CBM is no longer present. Conversely, Fe_3O_4 is semi-metallic due to the partial occupation of the conduction band. In Fe_2AlO_4 , Al occupies half the octahedral sites, breaking the Fe 3d coupling along the octahedral chain. This results in the opening of a small band gap for Fe_2AlO_4 . For FeAl_2O_4 only the tetrahedral Fe sites remain and the band gap is largely increased, similar to CoAl_2O_4 ; however the d^6 configuration of Fe on the tetrahedral sites results in partial occupation of the conduction band. The two ternary oxides formed from Co and Fe both result in small, but finite band gaps. Interestingly, considering the properties of the binary oxides, the Fe rich spinel Fe_2CoO_4 has a larger calculated band gap than the corresponding Co rich oxide Co_2FeO_4 . In addition, experiment indicates that Co_2FeO_4 is not chemically stable at temperatures below 1170K, while Fe_2CoO_4 is. Binding energies of Co_2FeO_4 and Fe_2CoO_4 calculated from the total energies of Co_3O_4 and Fe_3O_4 indicate that both these stoichiometric materials are energetically unstable. However, this may be a consequence of the small unit cells employed in our calculations which cannot fully account for the cation disorder which occurs in the real materials.

Fig. 28. A schematic summary of the calculated structural and electronic properties of the three binary and six ternary Co-Fe-Al spinels. The experimental lattice constants are indicated in parenthesis. The lowest electronic transitions of both the normal (N) and inverse (I) structures are shown.

The qualitative trends of the calculated band gaps indicate that spinels formed from aluminum rich cobalt oxides would be best suited for application in a p-n photoelectrolysis system for hydrogen production from water. As noted in the introduction, Woodhouse *et al.* identified a Co and Al rich spinel containing small amounts of Fe to be an active p-type material with an optical band gap of less than 1.9eV. Our results suggest that the band gap of CoAl_2O_4 is too large to be directly considered, but Fe doping of this material or local cation disorder may reduce the band gap further, as the lower bandgap of the inverse spinel structure would suggest. It is also possible for an active material to lie in the Co_3O_4 to Co_2AlO_4 range if doping or a high concentration of defects can make the fundamental gap larger and more direct. Future efforts should concentrate in detail on these regions and the effect of intrinsic defects, local cation disorder and Fe doping on the electronic structure and optical properties of these systems.

Publications:

1. Kwang-Soon Ahn, Yanfa Yan, Sudhakar Shet, Todd Deutsch John Turner, and Mowafak Al-Jassim
Enhanced photoelectrochemical responses of ZnO films through Ga and N codoping
Appl. Phys. Lett. 91, 231909 (007).

2. Kwang-Soon Ahn, Sudhakar Shet, Todd Deutsch, Chun-Sheng Jiang, Yanfa Yan, Mowafak Al-Jassim, John Turner
Enhancement of photoelectrochemical response by aligned nanorods in ZnO thin films
J. Power Sources (2007).
3. A. Walsh, S.-H. Wei, Y. Yan, M.M. Al-Jassim, J. Turner, M. Woodhouse, and B.A. Parkinson,
Structural, magnetic, and electronic properties of the Co-Fe-Al oxide spinel system: Density-functional theory calculations
Phys. Rev. B 76, 165119 (2007).
4. K.-S. Ahn, Y. Yan, and M. Al-Jassim,
Band gap narrowing of ZnO:N films by varying rf sputtering power in O₂/N₂ mixture
J. Vac. Sci. Technol. B 25, L23 (2007)
5. K.-S. Ahn, T. Deutsch, Y. Yan, C.-S. Jiang, C. L. Perkins, J. Turner, and M. Al-Jassim
Synthesis of band-gap-reduced *p*-type ZnO films by Cu incorporation
J. Appl. Phys. **102**, 023517 (2007)
6. K.-S. Ahn, Y. Yan, S.-H. Lee, T. Deutsch, J. Turner, C. E. Tracy, C. L. Perkins, and M. Al-Jassim
Photoelectrochemical Properties of N-Incorporated ZnO Films Deposited by Reactive RF Magnetron Sputtering
J. Electrochemical Society, **154** B956-B959 (2007).

ATTACHMENT 5

STATUS REPORT

PREPARED BY:

**HYDROGEN SOLAR
December 2006**

UNLVRF Subcontract #RF-05-HFS-004 Status Report

December 22, 2006

Xiaoming He, Ph D
Principal Investigator

Hydrogen Solar LLC
350 Sunpac Ct.
Henderson, NV 89015
Phone: 720 579 7600
xiaoming.he@hydrogensolar.com

Executive Summary

This document aims to provide a status report summarizing UNLVRF subcontract work, Subcontract #RF-05-HFS-004-A01, assigned to Hydrogen Solar LLC.

Hydrogen Solar LLC is a subsidiary of Hydrogen Solar Ltd, a UK based research firm. It has been carrying on the subcontract work in Henderson, Nevada since the beginning of fiscal year 2006. Record setting PEC photo current density has been produced from the Henderson lab despite ground-up facility construction and team building.

Various delays occurred throughout the entire year. In particular, since mid-year, a number of major events altered the course of action significantly, as indicated by the director of Hydrogen Solar LLC in his letter to UNLVRF on December 11. So far, over 80% of the subcontract work has been conducted based on track records and has reached satisfactory outcomes according to the contract defined tasks.

Task Schedule

Task Number	Task Description	Originally Planned Completion Date	Revised Planned Completion Date	Actual Completion Date	Percentage Complete	Progress Notes
5.1	Apply discovery, characterization, test and evaluation to enhance electrode materials	12/01/06	12/01/06		80%	No further progress
5.2	Develop flexible conductive substrate materials	07/01/06	07/01/06		80%	No further progress
5.3	Model and simulate dynamics of thermal and fluid flow in Tandem Cells	09/01/06	12/01/06		90%	On track
5.4	Field test Tandem Cell and array	12/01/06	12/01/06		65%	Delayed due to scaling for new cells

Clearly, according to the schedule, a significant portion of the task work remains whereas time is running out. It is impractical to reach a conclusion at this point unless extended time is granted.

Collaboration with Subcontract Partners

Fruitful discussion and creative work were ongoing in collaboration with Dr. Heske's group until mid-July when James Wilkie, CEO of Hydrogen Solar at the time, began to intervene in operations. However, active research work within HS Henderson Lab continued despite limited analytical means and lab construction. In fact, spectroscopic data collected from Heske's group shed some light on the HS Henderson Lab's research activities and encouraged further progress. Nevertheless, no conclusions were drawn due to the incomplete project.

Working with Altairnano was nearly impossible due to strained relations between Hydrogen Solar and Altairnano, which is a known issue within the working group. No samples from Altairnano were received nor were samples from Hydrogen Solar delivered to Altairnano although attempts to resolve this issue were undertaken.

In collaboration with Hatchett's Group, HS Henderson Lab has provided technical assistance and data collection for PEC cell counter electrode development work. In particular, an investigation of electrode scaling factors was proposed to Dr. Hatchett's group in order to carry out PEC cell engineering work with Dr. Boehm's group. The issues were addressed in the Monthly Report by Hydrogen Solar LLC, and in the past months, efforts were made to obtain larger sized counter electrodes for engineering data collection.

Engineering work with Dr. Boehm's group has been very active throughout the entire year regardless of limited materials. Novel cell designs and practices were undertaken both at the College of Engineering, UNLV and HS Henderson Lab. Numerous technical issues were challenged in overcoming technical barriers associated with the Subcontract work:

- Defined critical cell working parameters including chemical reactions at electrode surfaces, boundary layer conditions, thermal effects, heat and mass transfer and fluid flow characteristics.

- Provided cell working data to assist with modelling critical parameters

- Provided current details on cell and pipe sizes to assist with modelling

- Investigated components including electrolyte and material selection

- Optimized CFD model to determine characteristics of velocity, porosity and pipe diameter modifications

- Refined the model further to determine temperature gradients and effects of boundary layer conditions and mass/thermal transport

- Investigated the kinetics of exchange of electrode/electrolyte and electrolyte/membrane interfaces

- Prepared PEC cells from current materials for individual/dual cell testing at the solar dish site

- Attempted to define requirements for balance of plant including electrolyte recirculation and monitoring, temperature control (heat sink), gas collection, handling and storage

Worked on test parameters including monitoring of water levels, pH, temperature, photocurrent density and gas generation

Studied balance of cell systems to manage electrolytes, collect, condition and store hydrogen and manage heat from solar gain

Developed a prototype system including balance of plant for installing PEC cells

Measured hydrogen generation efficiency in field trials using 4"x4", 6"x12" and 10"x10" PEC cells in Henderson

Ongoing Engineering Project

Numerous literatures have proved that materials such as Nafion, FTO, WO_3 , and Pt gauze are durable for years in water. However, an integrated engineering of these basic materials for solar water splitting in a PEC cell is a daunting challenge due to fundamental PEC issues such as inefficient photocatalysis, poor material interface or defective contact, rapid hole-electron recombination, inadequate hole mobility and poor operational durability of device.

Due to the material durability advantage, a decision was made in September to focus on FTO/ WO_3 /SPE/Pt for full scale engineering work. PEC cells consisting of the materials were fabricated in small sizes. The tests were then conducted in pure water under 1.5 AM condition and the results were compared to a typical electrolyzer. While investigating device durability, engineering work was underway for scaling up. Shown below are a cross section view of a generic cell configuration designed by Hydrogen Solar LLC, cell layouts designed by UNLV and engineering work ongoing at Hydrogen Solar Henderson Lab.

Cell Configuration Cross Section View

Courtesy of UNLV PEC Cell Design

Hydrogen Solar Henderson Lab Engineering Work in Progress

Scaling Table				
Cell	Exposure Area (in ²)	Total Photo Current (mA)	Photo Current Density (mA/in ²)	Scaling Loss %
1x1.5	0.16	1.1	6.88	0.00
1x3	2.88	15.2	5.28	23.23
4x5	18.58	40.1	2.16	68.60
6x10	34.13	59	1.73	74.85

Tests were conducted under 1.5 AM illumination condition using 1.2V bias voltage
Deionized water was used for the PEC testing

Thus far, larger devices have not displayed similar behavior compared to smaller ones. More than 60% losses upon scaling have been observed and no conclusion has been drawn with the limited data. The inconsistency of this engineering issue is perhaps due to a complex problem associated with material integration and scaling factors. Given the circumstances, two aggressive approaches have been undertaken to resolve this issue:

1. Optimization of cell configuration by manipulating cell construction materials and cell parameters to allow a better mass transportation of ionic species in the PEC device
2. Improvement of material integration on the photo electro anode by modifying the layout of conductive pathways and enhancing contact interfaces

These critical technical challenges may address fundamental PEC device engineering issues associated with the PEC performance at a larger scale. Specifically, a rational solution to this is a means to reaching a successful completion of the Subcontract.

Status of Deliverables

The listed points show deliverables status with team effort as defined by the Subcontract:

1. Photocatalytic materials of enhanced performance

This needed collaboration with CH&AN, but was partially done without the involvement of Altairnano. The deliverable is intact if more information is available from partners.

2. Catalyst preparations suitable for conductive substrates

This needed collaboration with DH&AN, but was partially done without the involvement of Altairnano. The deliverable is intact if more information is available from partners.

3. New and more conductive Tandem Cell working electrodes

*This needed collaboration with DH&AN, but was partially done without the involvement of Altairnano. The task was shifted away from the original target largely due to transparency problems of the flexible conductive substrate developed at Hatchett's Lab. An agreement was made between HSLLC and David Hatchett at the beginning of the year to explore the potential of the material for counter electrode applications. Therefore, David could continue his research program and receive financial support from the fund. This plan was brought to Bob P. in one of my earlier documentation, **Year 2006 Research Plan Summary**, as shown in Appendix A*

Thus, Hydrogen Solar Henderson Lab developed test cells to examine counter electrodes produced from Hatchett's Lab at UNLV. Two samples were received in June. One sample is a black carbon doped polyimide (BCDP) and the other is a Pt coated BCDP. It was found that PEC cell with BCDP did not show significant photo current. However, the one with Pt-BCDP displayed photo activity comparable with platinum gauze. The drawback of the Pt-BCDP was the delamination of coated Pt after testing in our standard test cell. Improvement was made later on and test results were reported in the Hydrogen Solar Monthly Report.

4. Scaled-up Tandem Cell working electrodes

The scale-up of working electrodes is ongoing. Technical assistance was offered to scale-up counter electrodes in order to evaluate the working electrode. It is currently awaiting a large counter electrode from DH.

5. Ability to numerically model the performance of the Tandem Cell

Collaboration was successful and outcomes were meaningful. The deliverable is completed at UNLV.

6. Use of the numerical model to design cell configurations

Modeling results have been adopted for cell configuration designs and engineering work for proof of concept is ongoing with BB. The deliverable is intact..

7. Tandem Cell with optimized working parameters

*Work with BB is ongoing. For details, refer to the section **Ongoing Engineering Project**.*

The deliverable is intact if time permits.

8. A prototype system with balance of plant for Tandem Cell field trials

Work is still ongoing with BB. The deliverable is intact if time permits.

9. Field trial data for current/optimized Tandem Cell including performance and durability

*Work is still ongoing with BB. For details, refer to section **Ongoing Engineering Project**.*

The deliverable is intact if time permits.

It must be pointed out that limited cash flow, delayed equipment deliveries, numerous delayed operation permissions and extended facility construction work resulted in multiple project postponements. One example of these problems is the case regarding QE instrument for IPCE mapping. The availability of this equipment is critical to time constrained Subcontract deliverables. However, it was not ready for delivery from the supplier until November 27, as shown in Appendix E, even though the vendor was aware of the severe negative consequences of the delay.

The Henderson Team, as its track record shows, has demonstrated exceptional competence. Despite all difficulties, the subcontract work carried out thus far has shown significant progress as manifested in the reports by HS Henderson Lab. Hopefully, this progress can reach a successful completion if a time extension can be implemented. The Henderson Team is committed to doing its best to make contributions and will distinguish itself for its integrity, dedication and excellence.

Appendix A

Year 2006 Research Plan Summary # RF-05-HFS-004-A01

Principal Investigator
Xiaoming He Ph. D.
Hydrogen Solar LLC
Henderson, Nevada 89015

This Research Plan Summary facilitates the implementation of UNLV Research Foundation Subcontract Amendment # RF-05-HFS-004-A01. It lays out a state-of-the-art Tandem Cell design based on the most advanced technologies in reaching the goals as defined in the Subcontract. As a comprehensive plan, this summary demonstrates one of Hydrogen Solar's latest concepts of the Tandem Cell as an illustration, along with a description of fabrication processes, testing and characterization instrumentation and facility infrastructure suitable for higher magnification studies.

A brief but systematic approach for materials, films, cell configurations and array structures is provided supporting the proposed design concepts. Comprised of collaborations with the UNLV, associated with external research institutions and industrial partners, a clear path for the next generation of the Tandem Cell is underlined. In accordance with these efforts, Exhibit I showing the new cell design, and Exhibit II displaying Phased Deliverables, Phased Instrumentation and Phased Lab Functionalities are presented to project the progress of the research plan.

The scope of work as presented in this plan is consistent with that defined in the Subcontract. The facility infrastructure and R&D capacity at Hydrogen Solar is being installed now to enable leading edge capabilities for the working group under UNLVRF leadership. The proposed cutting edge technologies and creative lab structure will provide a center of excellence environment for this Earmark Project to succeed in this most challenging renewable energy program.

1. Novel Tandem Cell Design

a. Stacked Anodic Electrode

The conceptual design of the HS cell is based on enhancement of electron-hole separation and propagation of electro potential through a stack of anodic materials consisting of photo sensitive materials and multi junctions. The novelty of this new cell structure as shown in Exhibit I is a stack of anodic materials featuring:

Novel film stack for anode in the Tandem Cell is consist of photo active materials including conductive materials or junctions between metal oxides and clear characterization of structure at nanoscale

The junctions and conductive materials may or may not fuse with crystalline boundaries

The stack may have a sacrificial layer in contacting with an electrolyte

The stack materials may include but will not be limited to Fe_2O_3 , WO_3 , TiO_2 , CdSe etc. The key emphasis will be on enhancing the performance of Fe_2O_3 possessing the highest theoretical efficiency potential.

b. Anodic and Cathodic Zone Separation

This cell is capable of performing dynamic electrolyte flow operation. A membrane such as proton exchange membrane is favorable for mass and charge transfers. In addition to gaseous product separation, the cell allows different residence time between the anode and cathode zones. Thus fluid flow differential become part of measurable cell operations.

c. Cell

Ionic transportation in the new cell design is a significant advantage over a monolithic cell where a restriction of ion transportation is an inherent shortcoming. This new conceptual cell may improve heat balance, minimize electrode poisoning, increase cell life time and make the cell efficiency more sustainable.

Transparent conductive polymer suitable for high temperature process ($>500^\circ\text{C}$) is highly desirable to fabricate photo electrode upon depositing photo active materials. Nontransparent conductive polymer, on the other hand, holds potentials for cathodic material development and membrane modification.

d. Cell Modeling and Testing

Low cell flow restriction and row module are basic features as a result of the new cell design. Therefore, the array will be capable of operating in a wide range of process window suitable for field operation under variety weather conditions.

2. Enabling Technologies

a. Fabrication

Emphasis will be given to low cost fabrication techniques such as spray pyrolysis which can produce films covering large areas at low cost. This approach is deemed as being essential to move towards industrial exploitation at large scale. Some other techniques will also be explored in case they do offer higher efficiency and also to improve controllability and understanding of carefully controlled “model materials”. In this context, a number of advanced film technologies will be evaluated. Medium cost process such as APCVD and PECVD etc. will be explored to control film quality when a necessary application is needed. ALD will be deployed to challenge the most critical issues such as surface and interface phenomena for identifying conductive pathway, refining bandgap, enhancing electron-hole separation and carrier multiplications.

Film enhancement techniques will be extensively deployed using Rapid Thermo Process (RTP) and wet process such as Self Aligned Monolayer (SAM), anodization, electroplating etc. Junction construction and modification will be intensively investigated and developed using doping and diffusion techniques. In

addition, variety of practical techniques will be employed when an integrated process is needed.

In supporting the film processes, a facility capable of maintaining clean room condition will be in place. This condition will be handled in a mini environment at an affordable level.

b. Characterization

Physical property of PEC materials will be extensively investigated in collaboration with UNLV using X-ray, UV photoelectron spectroscopy (XPS and UPS), inverse photoemission (IPES), X-ray emission (XES) and absorption spectroscopy (XAS). Cross sections will be examined by using SEM, TEM and SIMs at UNLV and other National Lab facilities. In addition, surface morphology characterization will be carried out using AMF and STM at UNLV. Conventional techniques such as BET surface area measurement will be utilized in understanding electrode catalytic natures.

c. Testing

Spectrometer with calibrated irradiance measurement lines up with field sunlight and an 1.6 KW solar simulator for quantitative PEC and Tandem Cell tests. Along with that, sunlight data bank will be established for data comparison with simulation. I-V data acquisition using Keithely SourceMeter and Multimeter will allow extensive studies of PEC at μA accuracy. IPCE will quantitatively define spectral response of PEC material in a bandwidth of 5 nm range. Sunlight positioner allows array test operating under a consistent illumination condition under Nevada Insolation Level.

Offline analysis using UV/Vis and GC/MS and inline monitoring system will allow all gaseous species generated from the test cells to be clarified up to ppb level. These analytical instruments not only provide product quality control but also system improvement.

3. Modeling and Engineering

In collaboration with UNLV, FEMLAB modeling will enable optimization of critical cell working parameters and further refinement to incorporate flow rate, temperature and boundary layer effects. Engineered cell, cell module and array will be tested in field. New balanced system will be in place after debugging and troubleshooting.

4. Collaborations

This is a growing research project under the leadership of UNLVRF. Broad collaboration with chemistry department, college of engineering at UNLV and industrial partner, Altairnano, will create a productive environment and lead to a new generation of technologies.

5. Deliverables

photocatalytic materials of enhanced performance (Work with CH&AN)
 Catalyst preparations suitable for conductive substrates (Work with DH&AN)
 New more conductive Tandem Cell working electrodes (Work with CH&AN)
 Scaled-up Tandem Cell working electrodes (Work with CH&AN)
 Ability to model numerically the performance of the Tandem Cell (Work with BB)
 Use of the numerical model to design cell configurations (Work with BB)
 Tandem Cell with optimized working parameters (Work with BB, CH, DH)
 A prototype system with balance of plant for Tandem Cell field Trials (Work with BB)
 Field trial data for current/optimized Tandem Cell including performance and durability (Work with BB)

Exhibit II

Phased Deliverables for Earmark Project #RF-05-HFS-004-A01												
Deliverables	Jan	Feb	Mar	Apr	May	June	July	Aug	Sep	Oct	Nov	Dec
1 photo catalytic materials of enhanced performance (Work with CH&AN)												
2 Catalyst preparations suitable for conductive substrates (Work with DH&AN)												
3 New more conductive Tandem Cell working electrodes (Work with CH&AN)												
4 Scaled-up Tandem Cell working electrodes (Work with CH&AN)												
5 Ability to model numerically the performance of the Tandem Cell (Work with BB)												
6 Use of the numerical model to design cell configurations (Work with BB)												
7 Tandem Cell with optimized working parameters (Work with BB, CH, DH)												
8 A prototype system with balance of plant for Tandem Cell field Trials (Work with BB)												
9 Field trial data for current/optimized Tandem Cell including performance and durability (Work with BB)												

Phased Instrumentation Plan for Earmark Project #RF-05-HFS-004-A01												
Deliverables	Jan	Feb	Mar	Apr	May	June	July	Aug	Sep	Oct	Nov	Dec
1 photo catalytic materials of enhanced performance (Work with CH&AN)	Planning Sampling	T PEC	T PEC	T PEC	T PEC	T PEC	T PEC	T PEC	T PEC	T PEC		
2 Catalyst preparations suitable for conductive substrates (Work with DH&AN)	Planning Sampling	TMP	TMP	TMP	10x MP	10x MP	10x MP					
3 New more conductive Tandem Cell working electrodes (Work with CH&AN)	Planning Sampling	MSTT	MSTT	MSTT	ITEG MSTT	ITEG MSTT	ITEG MSTT	ITEG MSTT	ITEG MSTT	ITEG MSTT	ITEG MSTT	ITEG MSTT
4 Scaled-up Tandem Cell working electrodes (Work with CH&AN)	Planning Sampling	T PEC	T PEC	T PEC	10x PEC	10x PEC	10x PEC	25x PEC	25x PEC	25x PEC		
5 Ability to model numerically the performance of the Tandem Cell (Work with BB)	Planning Sampling	TR	TR	TR	TR							
6 Use of the numerical model to design cell configurations (Work with BB)	Planning Sampling	TRC	TRC	TRC	TRC	TRC	TRC	TRC	TRC			
7 Tandem Cell with optimized working parameters (Work with BB, CH, DH)	Planning Sampling	EFT	EFT	EFT	EFT	EFT	EFT	EFT	EFT			
8 A prototype system with balance of plant for Tandem Cell field Trials (Work with BB)	Planning Sampling	ET	ET	ET	ET							
9 Field trial data for current/optimized Tandem Cell including performance and durability (Work with BB)	Planning Sampling	CT	MT	MT	MT	MT	MT	MT	MT	AT	AT	AT

RotVap, USBath, CR, AB, HP, Ductless Hood, Oven, DB Coating, Solar Simulator, Field Test Basics

Chemical Bench, SC, FS, GM, Field Test I, Resistance/Thickness, IPEC, GC/MS/, UV/Vis, BET

RTP, Diffusion, ALD, LPCVD, HP, etc.

T PEC Token PEC preparation and testing
 TMP Token middle plate preparation and test
 10x MP 10 x 10 cm middle plate preparation and test
 MSTT Material screen and token test
 ITEG MSTT Integrated material screen and token test
 10x PEC 10 x 10 cm PEC
 25x PEC 25x 25 cm PEC
 TR Testing and Remodeling
 TRC Testing, Remodeling and Construction
 EFT Engineering and Field Testing
 ET Engineering and Testing
 CT Cell Testing
 MT Module Testing
 AT Array Testing

14

Appendix B**UNLVRF Subcontract RF-05-HFS-004-A01****Quarter II Report**

Reporting Period: 04/01/06 to 06/31/06

Organization	Org. Type	Contact
Hydrogen Solar, LLC	Industry	Name: Dr. Xiaoming He Title: Principal Investigator Address: 350 Sunpac Ct. Henderson, Nevada Tel: 702-579-7600 or 702-287-7415 Fax: 702-558-7602

Summary**Facility Upgrade Update**

The Henderson Lab started with a simple warehouse style facility. After having made significant improvements, this ground-up laboratory is now equipped with a basic setting for operations dealing with gas, liquid and solid materials. It supports fabrication of PEC electrodes and cells, testing of PEC activities under sunlight or a simulator and characterization of PEC film and photo electrodes. Further improvement is underway to provide a clean room environment where more reliable film processes can be performed to generate accurate and reproducible experiment results. An economic modular clean room is coming for installation. Other facility components, which meet high standard material fabrications, have been ordered and will be in place for multifunctional operations.

Equipment Update

In order to conduct the subcontract with limited cash flow, the Henderson Lab has been making use of the most creative and cost effective approaches to compose the Lab. In addition to acquiring surplus equipment from a broad range of vendors, in-house made equipment was a significant addition to the construction of a multifunctional lab. Rapid Thermal Process (RTP) and a programmable heating plate are in place for material processing and flexible modifications can be performed based on the requirements of an experiment. Low cost APCVD has been designed and detailed work has been laid out with accredited suppliers. Also, an automated durability test system has been designed and part of the system has been in place for testing. Part of the equipment supporting systematic handling of gases, liquids and solids has been installed to serve the contract work. Currently, nearly 70% of the equipment budget still remains for laboratory upgrades in order to facilitate the subcontract work (Table 1).

Test Program Update

Round-Robin Test programs have been the focus for improving PEC test reliability. Henderson Lab has made multiple critical contributions to improve solar simulator PEC testing methodology and to provide reliable testing results. In particular, sunlight PEC testing methodology developed at the Henderson Lab has been demonstrated as a practical alternative to verify simulator test results. Additional work with Guildford Lab is ongoing.

Fabrication Capability Update

The Henderson Lab is currently capable of producing from 1 cm² size tokens to 100 cm² size PEC testing electrodes and cells. Techniques to produce cells with illumination area of 625 cm² are underway for development. Process development includes condensed phase operations and gas phase operations. Along with thin layer deposition, this lab has developed propitiatory techniques handling nano level structural manipulations and shallow junction doping. CVD and other deposition processes are in progress to be deployed.

Progress by Tasks

Task 5.1

PEC film enhancement was a substantial portion of the research work during the second quarter. The photo activity of a novel anodic material developed at the Henderson Lab achieved new records of photo current density when applying a film stack consisting of an aluminum substrate, doped dielectric material which grows on the substrate by electrical process, and a photo active WO₃ nano crystalline material. A systematic investigation was ongoing to understand the experiment outcome. The proof of High Efficiency PEC Anode (HEPA) design concept was undertaken systematically. The following highlights the main activities in the Henderson facility:

Efforts made:

- Developed methodology to improve processes for fabrication of photo electrode
- Designed and constructed equipment to enhance film performance
- Exercised fabrication of electrode and cell scale-ups
- Designed durability testing matrixes
- Designed durability testing electrodes and testing cells
- Designed testing system including gas generator, purifier, analytical, storage and end-user units
- Outlined new sets of equipment suitable for practical operations
- Coordinated and conducted analytical and characterization work including SEM, EDX, and TEM
- Collaborated surface and interface characterizations to set up a baseline for systematic PEC enhancement research activities
- Designed new PEC anodic electrode

Major achievements:

- New PEC film stack (HEPA) generated photo current density exceeding 8 mA/cm² under 1.5 AM illumination condition
- High resolution SEM demonstrated the nanostructure of the stack PEC material
- TEM exhibited boundary structures
- EDX displayed location specified material composition
- X-ray diffraction demonstrated disordered Al diffraction pattern generated at the Al-W interface
- Observed gas evolutions both on the cathode and the anode when testing a larger

PEC cell with a 20 cm² illumination area

Major technical issues confronted:

- Material stress control
- Substrate bowing control
- Dust control
- Shallow junction doping control
- Heating and annealing temperature control
- Film cracking and flaking
- Poor repeatability and durability
- Limitation of process monitoring and control
- Lack of quick in-house characterizations

In collaboration with Heske's group at UNLV, Hydrogen Solar Henderson Lab has prepared and delivered a number of photo electrode samples for surface and interface analyses. The goal of this experimentation in the second quarter is to tune up the analytical equipment in Heske's Lab and optimize sample preparation recipes at Hydrogen Solar.

HS's samples are WO₃ based nano crystalline materials which can be deposited on a conductive glass or pretreated metal substrates. Technically, it is difficult to deposit a thin film with 1-3 nm thickness for interface analysis without major deviation from a nano crystalline structure. However, the DEPO-Recess based wet process may provide a way to shape an ultra thin layer while retaining the structural integrity of a desired interface. The first set of experimentations was to provide an optimized process to produce meaningful results and create a baseline for further electrode characterizations.

Additional samples have been delivered recently to Professor Heske's Lab based on the observation that the WO₃ photoelectron response signal in the previous samples was not strong enough to draw any conclusions from an interface analytical perspective. In addition, moisture and carbon contamination were issues. Having reviewed the facts, additional cleaning steps were added including ultra sonic treatment in IPA/Acetone bath and 550C baking on a hot plate for sample preparation.

IPCE analysis in combination with band gap mapping was actively under evaluation in order to further understand the new PEC material performance. The instrument for conducting the IPCE work will be received in the Henderson Lab and installed for the subcontract work.

Task 5.2

Producing flexible conductive material is another task for improving Tandem Cell functionality. Counter electrodes using flexible material present a number of advantages for cell structure optimization and cost reduction. Working with Hatchett's research group at UNLV, Hydrogen Solar developed test cells to examine samples. One sample is a black carbon doped polyimide (BCDP) and the other is a Pt coated BCDP. The PEC performance test was conducted under standard test conditions in 1M MSA using

FTO/WO₃ photo electrode. It was found that PEC with BCDP did not show significant photo current. However, the one with Pt-BCDP displayed photo activity comparable with platinum gauze. The drawback of the Pt-BCDP is the delamination of coated Pt after testing in our standard test cell. Currently, Hatchetts' group is looking for alternative methods for depositing Pt onto BCDP or modifying the BCDP itself.

Further work on the project has been identified as loading effect and surface area effect are proposed for further investigations. The Henderson Lab is waiting for any improved testing samples.

Task 5.3

New ideas were developed while working with Professor Boehm's research group. The convective and diffusive transport together with the electrochemical reactions in the cathode and anode inside the PEC cell were proposed to be investigated using the CFD techniques by Boehm's group. By using the general CFD package (such as FLUENT or FEMLAB), a comprehensive non-isothermal computational model for PEC cell system will be provided. The model allows parallel computing, thus making it practical to perform well-resolved simulations for large computational domains. Distributed heat generation associated with the electrochemical reaction in cathode and anode will be simulated in the developed model. The developed numerical model will solve for the electric and ionic potentials in electrodes and membranes, and the local activation over potential distribution will be resolved, rather than assumed uniform, making it possible to predict the local current density distribution more accurately.

Meanwhile, cell design in conjunction with engineering development at UNLV has made significant progress. Applying the new PEC material, this new design is to seal the backside of the electrode while promoting ion flux inside of the cell. Larger photo electro anodes incorporating tungsten trioxide on electrochemical treated aluminum substrate were fabricated and tested with significant success. Cells with 20 cm² illumination area have been tested and similar I-V test results were obtained in comparison to smaller electrodes. Gas evolutions on both cathode and anode were observed. More groundwork was laid out with Bob Boehm's group and further engineering effort was underway.

Task 5.4

This task oriented activity is a Hydrogen Solar Guildford Lab based operation. Given the existing technology developed in the Guildford Lab, a test rig suitable for testing 25x25 Tandem Cells has been designed and built and is ready to operate at the Solar Dish site by the UNLV engineering research group. More test cells will be delivered from the UK Lab in the third quarter to further the effort.

Tabulated Progress by Tasks

5.1	Apply discovery, characterization, test and evaluation to enhance electrode materials
5.1.1	<u>crease photoelectrode current density:</u> Fabricated a low bias voltage and highly active PEC film stack reaching 0.5 V-5mA/cm ² in 1.0M MSA under simulated AM1.5 global solar illumination (Figure 1) Fabricated doped Metal-Dielectric-WO ₃ film stacks with photocurrent density exceeding 8 mA/cm ² in 1M MSA under simulated AM1.5 global solar illumination. (Figure 2) Observed gas evolution on both cathode and anode when testing 4x5 cm ² photo electrodes (Figure 3)
5.1.2	<u>characterize electrode:</u> Samples were analyzed at UNLV, Harry Reid Center. SEM, TEM and EDX (Figure 4, 5, 6, 7, and 8)
5.1.3	<u>fundamental physical chemistry of electrode and interface:</u> Samples were sent for surface and interface analyses at Heske's Lab, See Heske's quarterly report and Figure 9
5.2	Develop flexible conductive substrate materials
5.2.1	<u>characterize polymeric conductive substrates:</u> PEC testing cell setup for new counter electrodes (Figure 10), Delamination was observed on the Pt coated flexible counter electrode (Figure 11) IV test results (Figure 12)
5.3	Model and simulate dynamics of thermal and fluid flow in Tandem Cells
5.3.1	<u>odel and simulate dynamics of thermal and fluid flow in Tandem Cells:</u> New approaches have been proposed to conduct CFD by UNLV. See Progress Summary
5.4	Field test Tandem Cell and array
5.4.1	<u>Prepare Tandem Cells from current materials for individual/dual cells testing at the Solar Dish site</u> A test rig has been developed that will allow two cells to be evaluated simultaneously at the Solar Dish site.
5.4.3	<u>Define requirements for balance of plant including electrolyte recirculation and monitoring, temperature control, gas collection, handling and storage</u> New cell design applying metal substrate anodic film stack is ongoing in a joint effort at UNLV and HSLLC
5.4.5	<u>Define test parameters and test data required including monitoring of water level, PH, temperature photocurrent density, gas generation and insulation levels</u> Progress was made on defining test parameters including temperatures, fluxes, flow rates of the gases generated and the electrolyte streams and PH of the electrolytes both at inlet and outlet.
5.4.6	<u>Prepare an array for testing at the Las Vegas Valley Water Authority site</u> No progress to report
5.4.8	<u>Periodically perform in-depth measurement on the test cells including IV, electrolyte</u> No progress to report

Supporting Tables and Figures

Figure 1: The photo electro anode was made with a 1.26 cm² illumination area and tested under simulated 1.5 AM global solar illumination. The test was conducted in a standard testing cell with 1.0 M MSA

Figure 2: The HEPA photo electro anode was made with a 0.785 cm² illumination area and tested under simulated 1.5 AM global solar illumination . The test was conducted in a standard testing cell with 1.0 M MSA.

Figure 3: The photo electro anode was made with a 20 cm² illumination area and tested under simulated 1.5 AM global solar illumination. The test was conducted in a standard testing cell with 1.0 M MSA. Gas evolutions on both cathode and anode were observed.

Figure 4: SEM

Figure 5: TEM

Figure 6: TEM

Figure 7: EDX and SEM indicating location specific composition of the electrode.

Figure 8: SEM and EDX show part of interface structure and composition after cleaving the anodic film stack consisting of Al-Diel- WO_3

Figure 9: XPS survey spectrum of a WO_3 thin film surface supplied from Hydrogen Solar. Data was quoted from Heske's Quarterly Report to HFS

Figure 10: Two electrode mode test cells

Figure 11: Delaminated BCDP-Pt

Photo electrode: WO_3 coated on FTO

Counter electrode:

BCDP: Black Carbon Doped Polyimide

BCDP-Pt: Pt coated BCDP

Pt gauze as a control counter electrode and cell front side is made of quartz

Test was conducted in 1.0M MSA under 1.5AM solar simulator illumination

Figure 12: Photoelectrochemical test of flexible counter electrode in 1.0M MSA under simulated 1.5 AM global solar illumination. WO_3 on FTO was served as photo electro anode

Table 1: Equipment Spending Update	
Equipment Type	Amount \$
Dual Axis Solar Tracker	2,339.48
Custom Stand for Solar Tracker	1,018.24
Measurement System	21,650.00
Compression Molder	3,313.00
Saws, Drills, Compressors, Etc	6,000.00
Stainless Steel Hood	1,200.00
Special Order Tool	1,069.08
Resistivity Measurement	13,616.08
Special Lighting.	951.95
Special Order Tool	959.52
Custom Cleanroom	9,686.45
Total Equipment Spending Update	61,803.80
Total Approved Equipment Spending	191,400
% Remaining Equipment Spending	67.71

Acknowledgement

This work has been greatly supported by UNLV and UNLVRF, particularly characterizations at the Harry Reid Center. It is greatly appreciated in fact that the detailed information ranging from EDX, SEM and TEM made this challenging project highly productive.

Appendix C

Facility after Upgrading

Appendix D

Activities for Month Terminating 12/11/2006

Brian Morriseau
Senior Engineer

Hydrogen Solar LLC
350 Sunpac Ct.
Henderson, NV 89015
Phone: 720 579 7600
BDM@hydrogensolar.com

Warping and breakage of large glass plates during annealing of tungsten oxide layers.

Contacted major US and worldwide manufacturers of ITO and FTO conductive glass including PPO, AFG, Dow Corning, GE, etc. None were very cooperative, and most that had potentially viable products (resistance less than 8ohm-cm) required minimum orders of 20,000 square feet and would not supply samples. Contacted numerous smaller manufacturers and second-tier suppliers with similar results. In this case, most were contract manufacturers that made product to customer specification and thus had no stock on hand. I therefore initiated a conference call with sales and technical engineering staff of Pilkington to discuss the issue. They agreed to supply free of charge a minimum of 24 sheets of 30x30cm conductive glass with thickness of ~3.2mm as opposed to the 2.3mm thick glass currently used. In addition, they will send an approved annealing profile that will meet all the requirements of heat treatment for the tungsten oxide layers while also eliminating any residual stress in the glass. I was not able to receive this data by e-mail as I have lost access to MS Outlook due to hard drive failure. Re-initialization would require assistance from HS Ltd., which was not forthcoming. The instructions will arrive with the glass.

Conductive grid

Made several trips to screenprinters to arrange application of gold grid to remaining 6 conductive glass sheets. The process went well. There is a small undetermined quantity of solvent-thinned Ferro gold paste left, probably enough for 1-2 more small batches. It seems that 50g of paste is sufficient to coat about 40 sheets of glass under the current conditions. However, I noticed possible pigment contamination of the remaining paste. The printers do not charge for set up, but there is a possibility of cross-contamination unless great care is taken in the cleaning of the equipment, which is not feasible under the current system of preparation in small batches. It would be much preferable to pay a set up fee and treat a comparatively large batch of samples at once. This is impossible under present restrictions. Although it costs only \$6 to coat each sheet, the set up fee alone is greater than the imposed \$50 maximum spending limit. Neither will it be possible to replace the conductive ink. Although Ferro states that they will sell as little as one gram at \$30/gram, about 5g (partially recoverable) is required simply to prime the printing

apparatus. A 100g jar of Ferro gold paste was sent to HS Ltd. Earlier in the year, which they promised to return; however, after months of delay and many broken promises, they sent back instead a Johnson-Matthey product, GBV 9995AS 10P. A telephone call to the manufacturer revealed that this material is NOT conductive and is in fact a gold coloring used to decorate porcelain dishes, and completely useless for the current application. Johnson-Matthey staff stated that they do not make a suitable conductive gold paste. There is a quantity of much less expensive silver paste on hand which has superior conductivity but does not seem to perform well in the application, possibly due to ionic mobility during the annealing process.

Microporous separator material

Since comparison of cell performance with traditional liquid electrolytes versus solid polymer electrolyte is a means of evaluating efficiency, I contacted a number of manufacturers of microporous separator materials. After examining data sheets for numerous materials and speaking with several technical support representatives, I selected a product from Polypore/Daramic/Celgard group, the world's largest manufacturer of battery separators. They quickly responded with a 20 square foot free sample. Although only .025mm thick, this material is very strong, compatible with aqueous acids, and rejects the passage of gases. The surface is treated with a wetting agent to prevent entrained air from hindering the exchange of dissolved ions. Tests should be conducted to ensure that the wetting agent is not electroactive at operating potentials, but considering the intended application, this will probably not be an issue. Open porosity is only 37%, but the "electrical resistance" listed at .040ohm-cm² is excellent. Of course this is a misnomer; in-house tests confirm that the electrical resistivity is actually quite high. The number quoted is actually the ionic resistivity.

ATTACHMENT 6

FINAL PROGRESS REPORT

PREPARED BY:

**ALTAIR NANOTECHNOLOGIES, INC.
September 2008**

Final Progress Report

Project Title: Hydrogen Filling Station

Date of Report: September 23, 2008

Recipient: Altair Nanotechnologies, Inc.

Award Number: DE-FG36-03GO13063

Contact: Bruce Sabacky, Altair Nanotechnologies

Objective

The overall project objective was to develop a photoelectrochemical cell for the direct splitting of water into hydrogen and oxygen using solar radiation as the energy source. To this end the project evaluated a variety of semiconductor materials to serve as cell electrodes.

Background

The development of the hydrogen economy requires the production of hydrogen from clean renewable resources. Photo Electrochemical Cells (PECs) offer one means of accomplishing this goal. Currently there are many materials which absorb light with enough energy to split water; however the potentials at which these materials separate the electrons and holes do not match those needed to split water.

The Altair team focused on the development of an iron oxide film as one promising electrode material for use in a water-splitting solar cell system. It is well documented that thin films of the hematite phase of iron oxide are semiconducting and photocatalytically active. Hematite's stability against dissolution at $\text{pH} > 4$ and the fact that over 30% of visible light has energies greater than the accepted band gap of 2.2 eV have prompted numerous investigations into its use as a photoanode for electrochemical hydrogen production. Thin films of oriented needles or platelets on a conducting glass substrate were found to have better photo-current efficiency than thin films of sintered hematite particles. Additionally, the incident photon to current conversion efficiency doubles as electrolyte pH is raised from 6.8 to 12.0. The photocatalytic properties of hematite have been improved by p-type dopants, such as aluminum, gallium, and indium, which introduce additional holes to the semiconductor and thus enhance conductivity.

The ideal photoanode structure has been determined to consist of several layers of iron oxide crystallites, having a platelet morphology, with an individual thickness of 5-10 nm. This embodiment provides at least one short dimension to cope with the very short electron-hole diffusion lengths in Fe_2O_3 ($\approx 4\text{-}5$ nm), which can be further improved with p-type doping. The total film thickness should be less than 60 nm to accommodate the requirements of the tandem cell design. That is, the front cell (photoanode) coatings of hematite must be deposited thin enough to allow the unabsorbed longer wavelengths of light to pass through to a back cell so that an electric current may be generated to drive the hydrogen and oxygen evolving reactions.

Project Tasks

The Altair team was assigned several tasks directed at the development of an iron oxide film suitable for the front electrode of the PEC hydrogen-generating cell. The tasks are listed below:

1. Determination and selection of a synthesis route for nano-scale Fe oxide (20-100nm)
2. Development of a deposition technique for applying the Fe oxide to both conducting glass and conducting polymer substrates
3. Testing of the Fe oxide coating for photocatalytic activity (PCA) using solar simulation test equipment and other characterizations
4. Optimization of the PCA of the Fe oxide coating through doping, coating, particle morphology adjustment, etc.
5. Testing of the Fe oxide coatings for electrolyte compatibility
6. Develop 2 cm x 1 cm ferric oxide-coated glass electrode producing $\sim 3\text{mAcm}^2$ under 1 sun illumination in a suitable electrolyte ($2 < \text{pH} < 12$)
7. Develop flexible conducting substrate materials development for scaled-up electrodes with potential for economical volume production

Completion of Project Tasks

During the time the Altair team was engaged in the Hydrogen Filling Station Project, they completed Tasks 1 through 5. Details of investigative results will be presented below, task by task.

The goal of Task 6 was not achieved, i.e. a photocurrent of 3 mA/cm² under 1 sun illumination was not achieved. Currents of nearly 1 mA/cm² were achieved.

Task 7 was not pursued by the Altair team. The results of basic research (Tasks 1 through 5) on the iron oxide films did not warrant any effort spent on this "downstream" development activity.

Investigative Results for Project Tasks 1 through 5

Task 1. *Determination and selection of a synthesis route for nano-scale Fe oxide (20-100nm)*

The Altair team worked primarily with ultrasonic spray hydrolysis (USP) as a film deposition technique. As noted in Task 2 below, plasma-enhanced chemical vapor deposition (PECVD) was also explored as it afforded a means to deposit iron oxide films on polymer substrates due to this technique's low deposition temperatures. The ultrasonic spray pyrolysis apparatus designed, constructed and used by Altair is depicted in diagrams and photographs below. For the small quantity of depositions by PECVD an outside contractor, Sencera, was employed.

Using the USP technique, metal-organic precursors for both primary iron oxide material and dopants are combined and introduced as an aerosol onto a heated substrate where the precursor is thermally decomposed to iron oxide. The deposition parameters are instrumental in determining the crystallite morphology, which in turn determines the resulting thin film's transparency and its efficiency.

Metal-organic precursors such as iron acetylacetonate have been documented to give crystalline hematite at lower temperatures than inorganic iron salts such as iron chloride. Additionally, the metal organic method does not result in residual chloride ion which is known to decrease electronic performance.

For deposition substrates, fluorine-doped tin oxide coated conductive glass blanks were purchased from Hartford Glass Corp.

The USP nozzle is pictured below in Fig. 1. The design incorporates dual liquid feed (iron oxide precursor and dopant solutions), introduction of a carrier gas, and thermal isolation of the piezo-electric transducer crystals. The nozzle tip is flat for introducing a more disperse aerosol into the reaction chamber pictured in Fig. 2.

Fig. 1. USP Nozzle Schematic

Fig. 2. Integrated USP Reaction Chamber with CVD Capability

This design permits the use of partial vacuum, a controlled atmosphere that may be oxidizing and /or fuel rich, and affords maximum process flexibility. An atomized mist of iron oxide precursor enters from the ultrasonic nozzle that is attached on the left side via a sealing flange. The mist is directed by carrier gas toward the heated substrate that is placed within the quartz glass tube at a 60 degree angle from the horizontal. Thin films of iron oxide are deposited on a 6cm x 6cm conductive glass substrate mounted on the heater. The chamber is sealed and evacuated from the opposite end, where an exhaust valve and vacuum feed-throughs are installed in a larger diameter flange.

Watlow supplied the cast-in substrate heater and PID controller. The heater is designed (Fig. 3) reach temperatures of 600°C to fully decompose the precursor, and the height and angle may be varied to allow for a uniform film deposition.

Fig. 3. Watlow 4" Diameter Cast-in Heater with Variable Angle

The decomposition reaction for iron oxide deposition is shown below.

Iron acetylacetonate, oxygen, and ethanol were used as precursor, oxidizer, and solvent, respectively. The resulting pyrolysis is a combustion synthesis with solvent /fuel and oxidizer contributing to a self-sustained reaction that occurs at a substrate temperature below the documented minimum decomposition temperature of 370°C. (Fig. 4)

Fig. 4 TGA plot of the decomposition of Fe(III) acetylacetonate in air

Figs. 5 and 6 show the actual USP Reaction Chamber.

Fig.5

Fig.6

Altair's process uses pure oxygen carrier gas to ensure the complete oxidation of precursor to Fe_2O_3 . By comparison, the prior art uses compressed air and coatings thus produced contain a significant amount of magnetite impurity as evidenced in Fig.7.

Fig. 7

Taken from: Alexis Duret and Michael Gratzel
J. Phys. Chem. B, Vol. 109, No. 36, 2005

Fig. 8

The X-ray analysis of Altair's $\alpha\text{-Fe}_2\text{O}_3$ thin film electrodes fabricated by ultrasonic spray pyrolysis is shown in Fig. 8. A small amount of the maghemite phase ($\gamma\text{-Fe}_2\text{O}_3$) is evident in the Altair material and is probably due to the relatively low deposition temperature. No magnetite peaks are evident. The preferred platelet nanostructure (Figs.9 & 10) is evident.

Fig. 9

Fig. 10

Task 2. Development of a deposition technique for applying the Fe oxide to both conducting glass and conducting polymer substrates

In an effort to make electrode fabrication commercially feasible and lower the deposition temperature, plasma enhanced chemical vapor deposition (PECVD) of iron pentacarbonyl was explored. Sencera, LLC, a developer of high density plasma sources was contracted to perform the deposition work.

A transmittance spectra of the leading polymer film candidate is shown in Fig. 11. The resin sells for \$5.00/lb and the glass transition temperature (T_g) is 140°C. A 4 mil thick film exhibits excellent spectral transparency, dimensional stability, and chemical resistance. It possesses low moisture absorption, low coefficient of thermal expansion, and is mechanically robust. It is stable in UV light and has recently acquired UL 746 certification – Standard for Polymeric Materials for use in electrical end products.

Fig. 11. Light Transmittance for Topas 5013 Resin

Sencera supplied the iron pentacarbonyl precursor, FSnO coated glass squares, and Topas cyclic olefin copolymer plastic plaques, in order to conduct proof-of-concept coating trials. In return, Altair provided XRD and SEM characterization feedback on the composition, crystallinity, and phase of the metal oxide thin films that Sencera produces. Although the goal is to ultimately deposit photoanode material on plastic, preliminary trials were performed on conductive glass to facilitate SEM imaging.

Figures 12 and 13 illustrate the macroscopic appearance of the low temperature iron oxide coatings deposited by PECVD using iron pentacarbonyl as precursor.

Fig. 12 Fe_2O_3 on glass at 140°C

Fig. 13 Iron Oxide on Topas 5013

Figures 14 and 15 illustrate the nanostructure of the iron oxide films deposited on F-doped SnO glass at 140 deg C by PECVD.

Fig 14.

Fig 15.

The XRD pattern of the iron oxide coating on glass (Fig. 16) shows that the desired phase of α -hematite was achieved at 140°C. The peaks are well aligned with a standard α -hematite made at 500C (center lines). This opens the door to low temperature deposition of any metal oxide (or combination thereof) that ultimately proves to possess the highest PEC activity. Figure 17 shows the α -hematite coating on a plastic substrate.

Fig 16 XRD of α -Hematite Thin Film made at 140C

Fig 17 Platinum coated α -Hematite on UV transparent Cyclic Olefin Copolymer plastic

Task 3. Testing of the Fe oxide coating for photocatalytic activity (PCA) using solar simulation

The current-voltage /photocurrent measurement system and the solar simulator and spectral response / quantum efficiency measurement system used at Altair are shown in Figs. 18 and 19 , respectively.

Fig. 18

Fig. 19

The test configuration for the electrodes in the test chamber for the photo-electrochemical measurements is displayed in Fig. 20. The system consists of a Hg/HgO reference electrode, a platinum gauze counter electrode, and Fe₂O₃ thin film working electrode. The Hg/HgO reference electrode with 1M KOH electrolyte replaces the SCE electrode used in the past. The Hg/HgO reference electrode with 1M KOH electrolyte is selected in particular because it utilized the same 1M KOH electrolyte as the electrolyte in the test PEC cell using Fe₂O₃ photo-anode (Fig. 22). Thus, in this configuration there is no junction potential in the electrolytes between the photo-anode and the reference electrode that may cause confusion in evaluation of the real electrode potential or cause migration of the reference electrode potential with time. The platinum Gauze electrode, shown in Fig. 21, contains two pieces of 1mg/cm² Pt loading, 20 wt.% Pt/Vulcan XC-720 oxygen gas diffusion electrodes to stabilize the potential of the counter electrode in particular during quantum efficiency measurement. The Quantum Efficiency Measurement system – PV Measurement is designed as a two electrode system and stabilization of the counter electrode potential drastically improves the reproducibility of the measurements and increases the signal response.

Fig.20 Fe₂O₃electrode, counter electrode, and reference electrode configuration

Fig. 21 Fe_2O_3 electrode, counter electrode, and reference electrode

Fig. 22. Electrode Testing Mount and Chamber2

The conversion scale between the potentials of the Hg/HgO reference electrode, standard calomel reference electrode (SCE), normal hydrogen electrode (NHE) and the potentials of the hydrogen H^+/H_2 electrode (also called reversible hydrogen electrode - RHE) in the 1M KOH electrolyte and the potential of the $\text{O}_2/\text{H}_2\text{O}$ electrode (also called relative oxygen electrode - ROE) in the same electrolyte is shown in Fig. 23.

Fig. 23. Conversion scale between Hg/HgO, SCE, NHE (normal hydrogen electrode) reference electrodes and related to water decomposition in 1M KOH electrolyte hydrogen (RHE) and oxygen (ROE) electrodes potentials.

Using conversion scale shown in Fig. 23 the data obtained with one of the reference electrodes can be easily converted to data vs. other reference electrodes or converted as defined by electrolyte nature, hydrogen electrodes (RHE) and oxygen electrodes (ROE) potentials. We have spent significant effort to figure out which presentation will be easier to interpret and to compare with other photo-anodes, where different reference electrodes and different electrolytes may be used. Our final decision was based on the fact that when authors compare different photo-electrochemical systems they typically show their data related to the water decomposition of hydrogen and oxygen electrode potentials and plot the data using absolute energy scale vs. normal hydrogen electrode.

Fig. 17. Position of decomposition potentials $E_{n,d}$ and $E_{p,d}$ vs. E_c and E_v of selected semiconducting materials [74].

Fig. 24. Example where oxygen electrode potential, hydrogen electrode potential and normal hydrogen electrode potential are used as a reference.

An example for such a presentation, shown in Fig. 24, is copied from T. Bak et al, International Journal of Hydrogen Energy 27 (2002) 991-1022. This suggests that it will be most convenient if we plot the data vs. hydrogen (RHE) and/or oxygen (ROE) electrodes that describe the water decomposition window of the electrolyte system used and at the same time plot the data vs. normal hydrogen electrode to show their position vs. the absolute energy scale. Furthermore, plotting the photo-anode I-V curves vs. oxygen electrode potential is in fact a comparison between oxygen evolution potentials on the tested photo-anode vs. oxygen evolution potential of the catalytically active anode at zero polarization.

An example of using such a presentation for the performance of a Fe_2O_3 photo-anode is shown in Fig. 25. The chart shows hydrogen and oxygen voltage potentials and the data is plotted against the oxygen electrode potential defined by the electrolyte decomposition window and also plotted against the normal hydrogen electrode potential. As can be seen the graph gives both types of information: Fe_2O_3 photo-anode performance vs. water decomposition potentials of the 1M KOH electrolyte and vs. the absolute energy scale using normal hydrogen reference electrode.

Fig. 25. Current Density vs. O_2 electrode and Normal Hydrogen Electrode Voltage Template

Task 4. *Optimization of the PCA of the Fe oxide coating through doping, coating, particle morphology adjustment, etc.*

The focus of this work was to synthesize and evaluate new materials in the iron oxide phase diagram that improve hole mobility and decrease recombination of the charge carriers. Following the work of other investigators, Altair attempted to develop new photocatalytic materials by inserting p-type dopants into the crystal lattice of iron oxide, without introducing any defects in the $\alpha\text{-M}_2\text{O}_3$ structure, all while maintaining the idealized crystallite morphology and size.

USP deposition of Si Doped Iron Oxide Electrodes

Iron oxide (Fe_2O_3) films deposited by USP were doped with Si by adding 1% and 0.5% tetraethyl orthosilicate (TEOS) to the 0.02M precursor solution of iron acetylacetonate. Films

were deposited at a precursor flow rate of 0.5 ml/min. The film thickness was increased by adding five addition layers of precursor.

Table 1. Deposition Parameters

Substrate angle	55 degrees
Substrate to nozzle distance	6.0 in
Precursor flow rate	0.5 or 1.5 ml/min
O ₂ carrier gas flow rate	7.0 L/min
Substrate temperature	400 °C
Number of Layers (10 ml aliquots of precursor)	9-10

The XRD patterns of 1.0% and 0.5% silicon doped and undoped films are shown in Fig. 26. The 0.5% Si doped films show evidence of Si doping with a small peak on the shoulder on the Fe₂O₃ (110) peak at 36.0 2θ degrees. The 1.0% Si doped films appear to contain an iron iron(III) silicon oxide crystalline structure as indicated by the search match data base results. The undoped films have a preferred (110) orientation as evident by the large (110) peak in the XRD. The intensity of the (110) peak in the XRD pattern of film pg63_5378 is much greater than hematite peaks in films deposited with half the amount of precursor. Figure 27 contains the SEM images of the undoped and doped Fe₂O₃ films. The undoped film contains a large number of vertically oriented platelets, but as the concentration of Si is increased the platelets begin to disappear and are completely gone by the time the concentration reaches 1%.

Fig. 26. XRD pattern for Si doped and undoped Fe₂O₃ thin film electrodes

Fig. 27. SEM of Fe_2O_3 thin films. Top image is undoped, left image is 0.5% doped Si and right image is 1% doped Si.

The spectral transmission of the films decreases with increased film thickness as shown in Fig. 28. The thicker films demonstrate a lower overall transmission intensity as well as a decrease in the transmission in UV, visible, and IR wavelengths. The silicon doped films however demonstrate a higher transmission in the visible and an increased transmission in the IR.

The increased film thickness did not improve the spectral response of the electrodes. Additionally the photocurrent density, Fig. 30, of thicker electrodes when exposed to 1 sun AM light was relatively close to that seen with films half as thick. The quantum efficiency measurements, Fig. 31, resulted in lower incident photon-current conversions for the thicker films; however the thicker films did demonstrate a small bump in efficiency between 550-560 nm when voltage biased (Fig. 32).

Fig. 28. Spectral transmission data for doped and undoped Fe₂O₃ films

Unlike films produced by Gratzel² silicon doping did not improve the total photocurrent density. All of our films have a lower photocurrent density than Gratzel's films. There are some obvious differences between the films in our measurements and the films produced by Gratzel's USP process. The SEM images of films produced by Gratzel's process, Figure 29, contain groups of platelets packed together in vertical clusters with rounded edges. Our doped films contain a dense population of thick platelets with sharp edges. We have not taken profile SEM images of our films thus we cannot directly compare the platelet height of our films and those of Gratzel. The total thickness of Gratzel's films is ~145 nm doped and the immersed and illuminated surface areas are 2.5 cm² and 0.5 cm². The larger surface area of our films may cause some loss of photocurrent density.

Fig. 29. SEM and Photocurrent data for Gratzel groups Si doped Fe₂O₃ electrodes

The incident photon-current conversion efficiency (IPCE) was measured using the Spectral Response / Quantum Efficiency Measurement System (Fig.28). The undoped 125 nm thick film deposited with a 0.5 ml/min precursor flow rate had the highest quantum efficiency. The undoped films have a higher unbiased quantum efficiency which is improved only by a few percent or decreases when a bias voltage is applied. The Si doped films measure low quantum efficiencies when unbiased, however the values increase significantly when a 0.5 V bias is applied to the electrodes. The increased film thickness did not improve the spectral response of the electrodes. Though the quantum efficiency measurements were lower for the thicker films; the films did demonstrate a small bump in efficiency between 550-560 nm when voltage biased.

Fig. 30. Si doped and undoped Fe_2O_3 thin Film electrode photocurrent density vs O_2 and normal hydrogen (NHE) electrodes

Fig. 31. Si doped and undoped Fe_2O_3 thin Film electrode quantum efficiency

Fig. 32. Quantum efficiency of Fe_2O_3 thin film electrode pg63_5378 with voltage bias

USP deposition of In Doped Iron Oxide Electrodes

Iron oxide (Fe_2O_3) films deposited by USP were doped with indium by adding 4% indium acetylacetonate to the 0.02M precursor solution of iron acetylacetonate. Films were deposited using the parameters in Table 2.

Table 2. Deposition Parameters

Substrate angle	55 degrees
Substrate to nozzle distance	6.0–8.0 in
Precursor flow rate	0.5 ml/min
O ₂ carrier gas flow rate	7.0 L/min
Substrate temperature	400 °C
Amount of Precursor	50-80 ml

The XRD patterns of the In doped films both display peaks characteristic of hematite (Fe_2O_3) and magnetite (Fe_3O_4) iron oxide. See Fig. 33. The SEM of the doped and undoped films deposited with the substrate 8 inches from the USP nozzle have platelets with rounded edges, which can be seen in Fig. 34. Fig. 35 displays the SEM images of the In doped film prepared with a substrate to nozzle distance of 6 inches. This sample retained some of the platelet structure that we have seen in the iron oxide films.

Fig. 33. XRD pattern for In doped and undoped Fe_2O_3 thin film electrodes

Fig. 34. SEM of undoped and Indium doped Fe_2O_3 thin film electrodes

Fig. 35 In doped Fe_2O_3 , 6 inches from substrate some platelets present

Fig. 36 demonstrates that the In doping did not improve the spectral response of the electrodes. The photocurrent density of In doped electrodes when exposed to 1 sun AM 1.5, $100\text{mW}/\text{cm}^2$ light was lower than undoped and Si doped films.

The photocurrent density of a smaller Fe_2O_3 thin film electrode, supplied by HNEI over a year ago, was also measured. The plot of the photocurrent data has two peaks one at 0.08 and 0.35 V on the O_2 electrode scale. The validity of this result is suspect. The electrode was rewired to fit our current test configurations, during the process the indium solder was partially removed and wires were reattached using silver epoxy. The resistance of the electrode increased from ~ 10.0 ohms to ~ 135 ohms, after the rewiring.

The quantum efficiency measurements, Fig. 37, resulted in incident photon-current conversions for the In doped films lower than the undoped film deposited under similar conditions.

Fig. 36. Si doped, In doped and undoped Fe_2O_3 thin Film electrode photocurrent density vs O_2 and normal hydrogen (NHE) electrodes

Fig. 37. Si doped, In doped and undoped Fe_2O_3 thin Film electrode quantum efficiency

USP deposition of Iron Oxide Electrodes

Iron oxide (Fe_2O_3) thin films were deposited by varying the amount of precursor. Films were deposited with 10, 20, 30, 40, and 50 ml of precursor. VASE measurements and XRD patterns of each film were taken to track the rate of Fe_2O_3 growth. Over the course of the experiment the number of platelets did increase but their orientation and percentage of surface cover were still fairly low.

Table 3. Deposition Parameters

Substrate angle	55 degrees
Substrate to nozzle distance	6.0 in
Precursor flow rate	0.5 ml/min
O ₂ carrier gas flow rate	7.0 L/min
Substrate temperature	425 °C
Amount of Precursor	10-50 ml

Table 4. Film Thickness from VASE measurements

Precursor Volume (ml)	Film Thickness (nm)	Mean Squared Error (MSE)
10	19.6	8.02
20	53.7	5.08
30	76.1	11.32
40	90.0	9.17
50	86.87	14.88

Fig. 38. XRD pattern for undoped Fe_2O_3 thin film electrodes

Fig. 39. SEM of undoped Fe₂O₃ thin film electrode

Smaller electrodes similar in size to those used by Gretzel were fabricated by cutting films deposited on 16 cm² substrates into smaller pieces. The smaller electrodes did not show any significant improvement in either the photoelectrochemical response, Fig. 40 or the photocurrent density, Fig. 41.

Fig. 40. 9 cm² and 3 cm² Fe₂O₃ thin Film electrode photocurrent density vs O₂ and normal hydrogen (NHE) electrodes

Fig. 41. 9 cm² and 1.5 cm² Fe₂O₃ thin Film electrode photocurrent density vs O₂ and normal hydrogen (NHE) electrodes

Task 5. *Testing of the Fe oxide coatings for electrolyte compatibility*

Although literature reports Fe_2O_3 was considered to be stable in 0.1 M KOH solution ($\sim\text{pH}13$) a more detailed study of the possible paths of Fe_2O_3 degradation suggests that there are at least two mechanisms that may cause fast degradation of the Fe_2O_3 films in this electrolyte.

As can be seen from the voltage-pH diagrams (Fig. 42) the phase Fe_2O_3 and $\text{Fe}(\text{OH})_3$ may coexist in the pH range from pH10 to pH 14, where the phase Fe_2O_3 is thermodynamically favorable at lower $\text{H}_2\text{O}/\text{Fe}$ ratio, while phase $\text{Fe}(\text{OH})_3$ is favorable in very high $\text{H}_2\text{O}/\text{Fe}$ ratio. This means that the interaction of the Fe_2O_3 film with 0.1 M KOH electrolyte will build a thin layer $\text{Fe}(\text{OH})_3$ phase on the Fe_2O_3 film - electrolyte interface. The thickness of this $\text{Fe}(\text{OH})_3$ interface layer most likely will increase with the time. In addition the Fe_2O_3 - $\text{Fe}(\text{OH})_3$ equilibrium is shift to $\text{Fe}(\text{OH})_3$ with increase in temperature and back to Fe_2O_3 with decrease in temperature. As a result the thermal cycles (naturally existing in the solar cells) will cause variation in the thickness of $\text{Fe}(\text{OH})_3$ interface on account of Fe_2O_3 film and because of the significant difference in the structure of these two phase this will accelerate the Fe_2O_3 degradation.

From the other hand the Fe_2O_3 film is expected to be polarized positively to the potentials where significant oxygen evolution can be achieved. This means that the potential of the Fe_2O_3 film have to be shift to potential with several hundred milivolts more positive than the thermodynamically determined potential of the oxygen electrode at the respective pH. As can be seen from the same voltage-pH diagrams (Fig. 42) at these potentials a Fe peroxide phase will be generated on account of Fe_2O_3 film in parallel to oxygen evolution. Six valence state Fe species will be generated as FeO_4^{2-} ions that will migrate all over the cell and because of their insufficient stability will convert to three valence state Fe compound and oxygen.

As a conclusion, in the earlier reports the Fe_2O_3 film have been considered as a stable in 0.1 M KOH solution but more detailed study performed this month suggest that Fe_2O_3 is not stable in direct contact with this electrolyte. In addition, the voltage generated by the solar cell will shift the Fe_2O_3 film potential in a voltage range that will accelerate the Fe_2O_3 film degradation.

Fig. 42 Voltage-pH Pourbaix diagrams of Fe-H₂O system.

ATTACHMENT 7

RESEARCH FOR HIGHER EFFICIENCY PEM TECHNOLOGY

PREPARED BY:

PROTON ENERGY SYSTEMS
July 1, 2008

RESEARCH FOR HIGHER EFFICIENCY PEM TECHNOLOGY

Final Report

Prepared by:

Proton Energy Systems
10 Technology Drive
Wallingford, CT 06492

1 July 2008

Prepared for:

University of Nevada Las Vegas Research Foundation
Under Subcontract No. RF-05-HFS-005-A03

Under U.S. Department of Energy, Golden Field Office
Contract No. DE-FG36-03GO13063

Table of Contents

1	Executive Summary	2
2	Introduction.....	3
3	Approach.....	5
4	Results and Discussion	7
5	Conclusions and Recommendations	11
6	References.....	14
7	Appendices	14

1 Executive Summary

PEM electrolysis for on site generation of hydrogen from water has been shown to be a clean, attractive alternative to delivered hydrogen for certain applications such as generator cooling, metals heat treatment, semiconductor processing and analytical instrumentation. However, to compete long term as a backup power and fueling option, the electrolyzer cost needs to be reduced. One method of decreasing cost is to increase efficiency, so that the production rate is increased for the same quantities of catalyst and membrane. Another method is through decreasing the capital cost of the components. Several areas of opportunity were identified as part of this program. The overall goal of this program was to conduct fundamental research to improve the cost, efficiency, and durability of proton exchange membrane (PEM) electrolysis. Additional activities associated with the design, development, and commissioning of a hydrogen filling station are summarized in a separate report.¹ Significant work was accomplished to advance understanding of PEM electrolysis and provide direction for improved efficiency and durability. A large active area test stand and prototype large active area parts were also fabricated in order to begin proving feasibility of larger units in order to decrease the cost of hydrogen in \$/kg.

One subset of research tasks revolved around optimization of the membrane electrode assembly (MEA) materials. Catalyst and membrane materials were evaluated vs. the baseline construction and optimized combinations were designed. Fundamental characterization was also performed in order to correlate physical properties with stack performance for better predictability of performance in the future and determine which bench tests were important to incorporate into future screening efforts. Strength and brittleness of the membranes were key issues. The ionic resistance of the cell did not correlate as expected with the membrane thickness of some of the membranes, indicating that either 1) the processing caused significant material changes, 2) equivalent weight had a major impact, or 3) there is another parameter that was not accounted for. Electrochemical screening tests were developed for the catalysts which did show good correlation with initial cell stack voltage, and trends were seen for different metals which provide insight for future catalyst development. The optimal membrane generated approximately 9% improvement in efficiency vs. the baseline, while the optimal catalyst showed a 5% efficiency improvement. The optimal membrane/catalyst combination did not yield a linear combination of the two components, providing about a 10% improvement in efficiency.

Another subset of research tasks involved scale up of the cell stack to a larger active area, including a test stand with capability for large cell testing. One aspect of scale up was to optimize the bipolar plate design, including computational fluid dynamics modeling in order to compare flow distribution and thermal profiles in various designs. Modeling of the large active area bipolar plate design demonstrated improved flow characteristics and uniform temperature gradients vs. the baseline bipolar plate. Large active area cell stack parts were procured and prototype MEAs were fabricated. The fabricated parts were tested and found to be within specification. Possible techniques for manufacturing the bipolar plates were also investigated. Alternate techniques for forming the plates which are recommended for further study include chemical milling, stamping, and vertical milling or machining. These techniques had good tolerance control with reasonable removal rates and lower capital cost than techniques such as laser machining.

Key technical issues associated with the renewable energy interface for PEM electrolyzers were also evaluated. The results of the integration simulations showed that power conversion efficiency for electrolysis can be improved to 95% or better for both direct interface with renewable sources or using the grid as an interconnection. At present and into the near future, the off-grid approach to hydrogen generation is not favorable for large scale hydrogen generation due to the capital cost of PEM based hydrogen generation. The RE-Grid Fixed Capacity hydrogen generator is therefore the most economical approach. Other areas of improvement include optimizing the system as a whole to determine the optimum cell stack temperature, pressure, and operating current density.

The final task incorporated the work from all these areas into a newly developed electrochemical model to translate the impact of these studies on cost of hydrogen in \$/kg. The model showed that significant cost savings are achievable through implementation of the recommendations included in previous subtask reports and enables projections for future cell stack and system improvements. Incorporation of the above work into the H2A model projects a cost savings of over 50% in \$/kg hydrogen vs. the baseline cost as all the proposed advancements are further proven out and progressed to commercialization. Based on the work accomplished in this program, additional improvements in catalyst performance are possible by continuing to optimize the synthesis conditions and composition. These improvements could enable lower catalyst loadings, decreasing cost. Optimizing the membrane properties based on the information gained is another area of opportunity. Processing changes and changes in surface treatment of stack parts also show promise. These areas have been proposed for further collaboration with UNLV in a follow-on program.

2 Introduction

PEM electrolysis for on site generation of hydrogen from water has been shown to be a clean, attractive alternative to delivered hydrogen for certain applications such as generator cooling, metals heat treatment, semiconductor processing and analytical instrumentation. However, to compete long term as a backup power and fueling option, the electrolyzer cost needs to be reduced. One method of decreasing cost is to increase efficiency, so that the production rate is increased for the same quantities of catalyst and membrane. Another method is through decreasing the capital cost of the components. Several areas of opportunity were identified as part of this program. The project was divided into the following tasks:

- Development of Advanced Proton Exchange Membranes for Electrolysis

Current commercial electrolysis membranes are relatively thick and operate at low temperatures in comparison to many fuel cells. Historically these parameters have been required due to the increased pressures and potentials experienced in the electrolysis cell, which lead to unacceptably high back diffusion of hydrogen or material degradation with thin membranes. However, the thicker membranes result in high ionic resistance, and cost more than thinner membranes due to the quantity of raw materials required. Under this task, a survey of current state of the art proton exchange membranes was conducted. Candidates went through several stages of screening to look for acceptable alternatives to the present baseline. Membranes which passed all the stages were incorporated into the MEAs for evaluation.

- Development of Advanced Catalysts for Electrolysis

An additional area of high over-potential in the MEA is the activation over-potential for the oxygen evolution reaction. New catalysts which exhibit improved kinetics should result in higher efficiency, reducing electrical costs. Cost can also be reduced by using lower catalyst loadings to achieve the same performance. Catalyst samples were subjected to a similar screening program to the membrane candidates, and catalysts which outperformed the baseline were also incorporated into the MEA evaluation task

- Development of Advanced Membrane Electrode Assemblies

To establish the electrochemical performance vs. the baseline configuration, combinations of candidate catalyst and membrane materials from the development tasks were manufactured into MEAs for testing. Another requirement for practically-sized fueling applications is scale up of the current designs. Under this task, a test stand for prove-in of larger active area MEAs was also designed and built.

- Development of Optimized Bipolar Plates

High efficiency PEM electrolyzers also require optimization of the bipolar plate design. Bipolar plate research focused on fluid flow and thermal characteristics modeled using computational fluid dynamics.

- Scale-up and Manufacturability Assessment

Feasibility of MEA scale up to the larger active area cell discussed in the MEA task was examined and prototypes were made. A secondary part of this task was to evaluate methods of manufacturing the bipolar plate and their applicability to large active area designs. Several techniques were evaluated by UNLV and recommendations were made for future study.

- Renewable Electronics Interface for PEM Electrolysis

Today's commercially available PEM electrolysis systems use DC current for the cell stack but AC current for the system components such as pumps and fans. Significant efficiency losses result when a renewable DC power source must be inverted to AC electricity and when DC-DC power conditioning is performed in order to utilize DC renewable energy sources for electrolysis. Sizing of the electrolyzer and managing the intermittent availability of power when connected to renewable sources are some of the integration issues. Analysis of today's technology, areas for optimization, and tradeoffs are discussed within this task.

- Modeling and Analysis

While the H2A model can be used to calculate \$/kg hydrogen as a function of electricity costs, depreciation, and other financial models, currently the electrolysis system is put in as a single component. There was a need for an electrochemical model to interface with the H2A model in order to determine component performance requirements and estimate the cost impact from implementing improved materials and designs. This task also incorporated results from previous tasks to assess the program impact on \$/kg H₂.

3 Approach

Described below is the general research philosophy used to achieve the deliverables of each subtask. Specific details of the experimental approach for each subtask can be found in the subtask deliverable reports referenced at the end of this report.

3.1 Development of Advanced Proton Exchange Membranes for Electrolysis

Membrane candidates were solicited from a list of suppliers developed through conference interactions, internet searches, and known contacts. The samples obtained were subjected to a series of physical characterization tests in order to establish a database for correlation with processing and electrochemical properties.² This initial testing was not used to screen out any candidates, but provided a database for material selection in the future as correlations are better understood. The first screening criterion was whether the membrane could be successfully processed with catalyst to form the MEA. Milder pressing conditions were investigated to enable more of the membranes to pass. A second test was whether the MEA could withstand the stack assembly and loading conditions to pass the acceptance protocol testing before electrolysis. Finally, assembled stacks had to pass 500 hours of testing at acceptable voltage and without leaking hydrogen.³ Because of the limited sample sizes for some of the membranes, a smaller active area cell design was used, which may have been more sensitive to alignment issues.

3.2 Development of Advanced Catalysts for Electrolysis

A similar solicitation process as described above for membrane materials was followed to obtain candidate catalyst materials. However, little success was achieved in obtaining materials from outside sources, so additional materials were synthesized in house to obtain high surface area, nano-sized particles.⁴ Oxides of noble metals were obtained or synthesized as pure oxides or binary mixtures. As with the membranes, physical characterization was performed on the catalysts but was not used to eliminate any candidates. Properties such as BET surface area and SEM photo-documentation were used to compare the samples.⁵ Samples were then incorporated into MEAs using the standard electrode manufacturing process. The only screening criterion for the catalysts was voltage performance vs. the baseline material on the 500 hour MEA testing. However, in parallel with the in-cell testing, electrochemical bench tests were developed in order to compare the intrinsic kinetic and diffusion properties of the catalyst powders. Results were checked for correlations with the in-cell testing in order to develop improved screening protocol for future studies.⁶

3.3 Development of Advanced Membrane Electrode Assemblies

Membrane and catalyst materials which showed improved performance vs. the baseline materials in earlier tasks were combined together to optimize performance. Combinations were processed into MEAs using the processing conditions developed under the membrane development task for evaluation in the cell configuration used in the catalyst development task. Cell stacks were tested to 500 hours vs. a baseline MEA. Design and fabrication of the large active area cell stack test stand was completed using approaches developed in house.⁷

3.4 Development of Optimized Bipolar Plates

Research was conducted on flow field concepts and methods of verifying bipolar plate flow performance. Design parameters such as flow channel width, height, and length, number of

channels, and configuration were examined for their effect on flow characteristics. From the design parameter studies, several concepts were developed and ranked to select an optimal design for detailed characterization and analysis.⁸ Simulation of single-phase and two-phase flow was modeled for this optimal design vs. the baseline design and results were compared. Important parameters included pressure drop across each channel and flow velocity. Temperature distribution was also modeled. Sensitivity of the baseline design was also studied as a function of oxygen flow rate and bubble diameter in order to determine the origin of disruptive flow behavior seen in the modeling results.

3.5 Scale-up and Manufacturability Assessment

Several methods of metal machining were assessed for applications in manufacturing metal bipolar plates such as those developed in the bipolar plate development task above. Advantages and disadvantages of each approach were evaluated, including parameters such as surface finish, achievable tolerances, tooling wear, and production volumes.⁹ Scale-up feasibility for a large active area cell stack design was also evaluated. Large active area MEAs were manufactured using current baseline materials and tested for acceptable resistance and component registration. Large active area bipolar plates were also manufactured, using a design similar to the model designed for optimal flow.

3.6 Renewable Electronics Interface for PEM Electrolysis

PEM based electrolysis systems with capacities ranging from 2 to 13 kg/day were instrumented to determine the energy losses for each subsystem in order to recommend the most promising areas for future research. Focus was placed on improving overall efficiency of the hydrogen generator by considering the interactions of the different subsystems. The most efficient aspects of each system were combined to estimate the power requirements of a 100 kg/day system based on potential improvements using today's design practices.¹⁰

The second part of this task presented the results of a model that incorporated statistical wind conditions, a fixed wind turbine capacity, and the electrical parameters of a PEM electrolyzer cell. Issues of renewable energy, the electrical network, and hydrogen generation were analyzed. These three entities were then considered together using three basic approaches to integration that yielded hydrogen generation using renewable energy. Power conversion technologies were also discussed for different power levels for hydrogen generators.¹¹

3.7 Modeling and Analysis

This task served as the culmination of the work of the other six research tasks. An electrochemical model was developed to fit the polarization curves for the baseline configuration and materials and validated vs. baseline membrane thickness. An interface with the H2A model was also developed. These models were then adjusted to fit the experimental results and predict performance of the optimal design. From the model and the available data on power consumption rates, over-potential losses, and other assumptions, the impact of the design changes developed in the tasks above on cost of hydrogen in \$/kg were calculated.¹² Projections for future improvements were also estimated.

4 Results and Discussion

4.1 **Development of Advanced Proton Exchange Membranes for Electrolysis**

A range of physical properties was observed in the membranes studied. Water content ranged from 40%-74%, with membrane thicknesses from 0.7 to 7.0 mils. There was also more than an order of magnitude difference in water permeability among the membranes tested.

None of the hydrocarbon-based membranes passed the chemical stability test, although there is some debate about the harshness of the test and whether it is required to pass to guarantee long term durability to electrolysis conditions. The hydrocarbon membranes which were tested in cell stacks failed due to apparent mechanical issues before resistance to chemical damage could be assessed, so further study is needed to determine chemical robustness. Failure elongation of one of the hydrocarbon membranes was low compared to the other membranes measured; this membrane was not able to successfully withstand cell assembly, indicating that this parameter may be important for correlation to membrane durability.

Three membrane candidates were eliminated during attempts to process the material into MEAs. Of the remaining three membrane materials tested in cell stacks, only one experimental membrane successfully completed 500 hours of operation. When the stack was torn down the MEA was found to have a tear along the MEA edge. It is not known whether the tear resulted from alignment issues in the stack, degradation during electrolysis, or physical stresses during tear down. Therefore, this membrane was still included for further evaluation. An alternate membrane identified during the time period of the program was also selected.

In parallel with the membrane evaluation, additional work was completed on the baseline membrane material to examine feasibility of alternate decal application processes. A milder process could enable the use of membranes which cannot withstand the traditional pressing process for decal transfer. Screen printing of catalyst-based inks demonstrated promise as an alternative manufacturing process and should be further studied.

4.2 **Development of Advanced Catalysts for Electrolysis**

SEM analysis of the metal oxide catalyst materials did not show significant differences. All of the powders consist of agglomerates several microns in size. The primary particles which make up the agglomerates are nanometer-sized and too small to resolve with SEM. All of the experimental catalysts had higher surface area than the baseline, with values near 100 m²/g vs. 30 m²/g for the baseline.

Electrochemical characterization tests were developed to gain understanding of the impact of chemical composition on the catalyst kinetics and surface properties. Testing demonstrated trends as a function of the metal and synthesis method in the catalyst. One of the metals tested consistently increased the % electrochemically active surface area, but was also unstable over long electrolysis times. A second metal decreased the % active area significantly as well as increasing the Tafel slope, but did help to stabilize the first metal. It was also found that the catalysts synthesized in house had higher % active area than the catalyst with the corresponding chemical composition obtained from the supplier.

Strong correlation was established between the % active area and the initial stack voltage. A weaker correlation was noted between the current density predicted at 1.5 V from the Tafel slope and the initial stack voltage. While some of the catalysts that showed improved initial voltage vs. the baseline degraded over time, one of the catalyst materials outperformed the baseline even after 500 hours of operation. Based on the trends seen in the metal types, a new catalyst was synthesized and included in the MEA evaluation task along with the improved material tested in the advanced catalyst task.

4.3 Development of Advanced Membrane Electrode Assemblies

The membrane candidate passed from the original membrane development task successfully completed 500 hours of operation with one of the alternate catalysts from catalyst development task, but did not show improvement vs. the baseline MEA. The MEA made with this membrane also continued to show weaknesses along the decal edge.

In contrast, the new membrane added in this task showed improvement with both catalysts. The improvement was slightly larger than the expected difference due solely to the membrane change, but the membrane and catalyst contributions did not seem fully additive. Still, the combination showed substantial improvement vs. the baseline MEA, with approximately 10% improvement in efficiency based on the higher heating value (HHV) for hydrogen generation.

A commercial MEA received during the program was also evaluated in this task. The performance was considerably improved over the baseline MEA, but not to the same magnitude as the optimized membrane/catalyst combination made in house. The efficiency difference for the commercial MEA vs. the baseline was approximately 7%.

4.4 Development of Optimized Bipolar Plates

Single phase flow modeling results showed higher flow velocities at the edges of the baseline bipolar plate design vs. the center channels. A non-uniform temperature distribution profile was also predicted from the model. Qualitative experimental results confirmed these trends, based on ΔP measurements and thermocouple measurements at various points on the plate. In contrast, the large bipolar plate design demonstrated uniform temperature distribution from channel to channel, with a gradient of about 4 degrees C along each channel. This result is consistent with the uniform flow also predicted by the model for this design.

Two phase analysis confirmed the results for the large bipolar plate. However, an unexpected asymmetric flow characteristic in the baseline design led to further investigation to determine the relevant parameters impacting disruptive flow. Bubble size did not have an effect, while the asymmetry and disruption in flow was observed to develop as the oxygen mass flow was increased.

4.5 Scale-up and Manufacturability Assessment

The techniques below were evaluated for manufacturability of metal bipolar plates, with the following conclusions listed in Table 1 below:

Technique	Advantages	Weaknesses	Pursue?
Abrasive milling/ machining	<ul style="list-style-type: none">• Good surface finish• Low material stress	<ul style="list-style-type: none">• Low material removal rates• Tolerance issues• Stray abrasion• Contamination• Cost	
Broaching	<ul style="list-style-type: none">• Close tolerances• High quality surface finish	<ul style="list-style-type: none">• Very low material removal rates• Cost for custom tooling	
Chemical milling/ machining	<ul style="list-style-type: none">• Fine tolerance control• Good surface finish• Lack of tooling wear	<ul style="list-style-type: none">• Low feature sharpness at bottom of wells• Undercutting of masks• Bath monitoring required	Y
Form turning/ Profiling	<i>See vertical milling</i>	<i>See vertical milling</i>	
Laser milling/ machining	<ul style="list-style-type: none">• Very fine tolerances• Suitable for production volumes	<ul style="list-style-type: none">• Edge quality vs. milling• Warping in thin structures• Oxide formation• High capital investment and energy costs	
Stamping/ forming	<ul style="list-style-type: none">• Low cost of high production runs• Good tolerance control• Stronger end product	<ul style="list-style-type: none">• Lubrication required• Cost of initial tooling• Part thickness limitations• Springback/stress in final product	Y
Vertical milling/ machining	<ul style="list-style-type: none">• High material removal rates• High level of accuracy• Good surface finish• Consistent process	<ul style="list-style-type: none">• Working time• Tooling wear• Material waste	Y

Table 1: Bipolar Plate Manufacturing Methods Comparison

The techniques recommended for further study were chemical milling, stamping, and vertical milling or machining. These techniques had good tolerance control with reasonable removal rates and lower capital cost than techniques such as laser machining.

4.6 Renewable Electronics Interface for PEM Electrolysis

Comparing the baseline data for the three commercial hydrogen generators showed that the major electrical balance-of-plant (BOP) losses were in the power conversion subsystem. All of the electrolyzers investigated had BOP losses of 5-8% when the power conversion losses were ignored. When the most efficient subsystem components were considered together and scaled for a 100 kg/day unit, the system power requirement was projected to be 300 kW.

During the BOP investigation, it was shown that a small gain in cell stack efficiency by raising the operating temperature from 50°C to 80°C would result in four times more water vapor that would need to be removed from the hydrogen gas stream to meet current hydrogen purity requirements. It was also shown that doubling the hydrogen generation pressure would reduce

the water vapor content by 50%. This result reinforced the importance of considering the interactions between the individual subsystems and their respective efficiencies.

Efficiency of each subsystem was measured in kWh/kg of hydrogen produced using gross hydrogen production numbers. This metric was useful for projecting the 100 kg/day power consumption using an assumed linear scaling factor. Using gross hydrogen production allowed the electrical subsystems energy use per unit of hydrogen to be quantified regardless of the gas drying subsystem efficiency.

The integration of statistical wind conditions used a Weibull distribution with a shape factor of 2 and a scale parameter of 7. This resulted in a mean wind speed of 6.2 m/s. The wind turbine was rated at 250 kW and the model incorporated the manufacturer's published turbine power curve. The electrolyzer cell stack was based on the characteristics of a prototype PEM cell operating at 50°C and a pressure of 200 psig (14 barg). Minimum and maximum current densities used in the simulation were 0.07 A/cm² and 2.31 A/cm² respectively.

The results of the combined wind, wind turbine, and electrolyzer model showed a significant reduction in capacity factor for hydrogen generation (see Table 1). This is a consequence of the capacity factor for a wind turbine and can be offset by using the electrical grid to support electrolysis at times when the wind speed is too low to harvest energy. The model considered running the PEM hydrogen generator at an arbitrary minimum current density to gauge the effect on efficiency and, in doing so, also modestly raised the capacity factors shown in Table 2.

Maximum Hydrogen Capacity (kg/day)	Ratio of H₂ Generator to Wind Turbine Peak Power	Efficiency (kWh/kg)	Capacity Factor (%)
Baseline	0% Baseline	59.27	100
17	11% Case	56.78	55.7
59	50% Case	53.74	41.5
104	90% Case	50.62	30.4

Table 2: Table of efficiency and capacity factor comparison

As expected, the efficiency of the hydrogen generator was increased when coupled to the wind turbines output power when compared to running continuously at full capacity. This efficiency gain was modest compared to the reduced capacity, as was shown in the table. The probability density curve for hydrogen generation efficiency resulted in a mean efficiency that did not coincide with realized efficiency. This effect was shown graphically as an offset between the probability density curves for hydrogen generation and generation efficiency. This illustrated the relationship between generating hydrogen efficiently most of the time and making most of the hydrogen at lower efficiencies.

Three approaches to electrolytic hydrogen generation using renewable sources were presented: RE-Grid Fixed Capacity, RE-Grid Variable Capacity, and RE Variable Capacity. Each of these three configurations covered whether or not the grid was used to connect renewable energy (RE) to the hydrogen generator and whether or not the power level of the hydrogen generator varied

with availability of power from the RE source. At current PEM electrolyzer capital cost, the RE-Grid Fixed Capacity option is the most economically attractive.

The insulated gate bipolar transistor (IGBT), silicon controlled rectifier (SCR), and metal-oxide semiconductor field-effect transistor (MOSFET) based power converters were briefly categorized by applicable power level. Power converter technologies for large PEM-based hydrogen generators drawing more than 100kW were considered with IEEE519, power factor (PF), and total harmonic distortion (THD) in mind. It was found that SCR and IGBT technologies cost roughly the same when these factors were considered. There are several options for power converter technologies at lower power levels that depend on the characteristics of the power source. Within this range are DC photovoltaic systems, AC wind turbines, and either of these systems coupled directly to the grid.

4.7 Modeling and Analysis

The electrochemical model was validated using experimental polarization data for a range of baseline membrane thicknesses. It was then used to fit the experimental data for the advanced catalyst materials by adjusting kinetic and ohmic parameters. To make the model fit the polarization data for improved catalysts, the ionic diffusion terms had to be adjusted, consistent with differences in the accessible fraction of the catalyst surface. The modeling results therefore provided additional support for the use of the electrochemical bench tests to predict cell stack performance.

Based on the data from the advanced membrane and catalyst tasks, the optimal MEA performance was predicted using the electrochemical model. The resulting efficiency improvements and material cost reductions yielded a predicted cost improvement of about \$0.36/kg H₂ based on \$0.05/kW electricity costs. Incorporating the changes in active area and system improvements studied in other tasks and scaling up to 100 kg/day with this improved MEA result in a predicted decrease in \$/kg H₂ to \$5.03/kg, which is within DOE targets for this generation capacity.

To continue to compete with other hydrogen generation technologies, further improvements are needed. An additional 25% reduction in cell stack cost and 20% reduction in system cost in conjunction with longer cell stack life would bring the generation cost down to \$4.39 kg/H₂. These predictions become highly dependent on the cost of electricity as the capital cost is reduced, so efficiency improvements and advances in renewable energy can also make significant impact on cost. Potential areas of improvement to focus on to meet these goals for the MEA are: 1) reduced catalyst loading, 2) non-noble metal catalysts, 3) surface treatments to reduce plating, and 4) advanced membranes which overcome the brittleness issues seen in the candidates evaluated in this program.

5 Conclusions and Recommendations

During this program, significant work was accomplished to advance understanding of PEM electrolysis and provide direction for improved efficiency and durability. Characterization of membrane and catalyst materials was performed to gain insight into the ranges of material properties that are acceptable for electrolysis at elevated pressure. A large active area test stand and prototype large active area parts were also fabricated in order to begin proving feasibility of

larger units in order to decrease the cost of hydrogen in \$/kg. System analysis was performed to quantify balance-of-plant energy losses, and analyses towards the optimum method of integration of PEM electrolysis with renewable energy sources were completed.

On the materials side, the tests performed were evaluated vs. stack testing results to determine which bench tests were important to incorporate into future screening efforts. Strength and brittleness of the membranes were key issues. The ionic resistance of the cell did not correlate as expected with the membrane thickness for some of the membranes, indicating that either 1) the processing caused significant material changes, 2) equivalent weight had a major impact, or 3) there is another parameter that was not accounted for. Electrochemical screening tests were developed for the catalysts which did show good correlation with initial cell stack voltage, and trends were seen for different metals which provide insight for future catalyst development. The optimal membrane generated approximately 9% improvement in efficiency vs. the baseline, while the optimal catalyst showed a 5% efficiency improvement. The optimal membrane/catalyst combination did not yield a linear combination of the two components, providing about a 10% improvement in efficiency.

During this program, only 50%-50% blends by weight of metal in the catalyst were examined and the synthesis conditions were held constant. It has been suggested in other work that adjusting the processing time and annealing conditions can further increase surface area. Future proposed work therefore includes additional optimization of the catalyst composition and synthesis conditions for further efficiency improvements. In membrane work, it is recommended to survey manufacturers for a second generation of materials, using the information gained in this study to guide parameter selection. Additional processing optimization is also recommended. Further characterization of the three-phase membrane/catalyst/fluid interface is also needed to understand synergies and opposing effects between the membrane and catalyst materials.

Modeling of the large active area bipolar plate design demonstrated improved flow characteristics and uniform temperature gradients vs. the baseline bipolar plate. Two-phase flow also showed that at higher oxygen flow rates, a disruption in flow is predicted in the baseline design. The larger active area design did not show this effect. Large active area cell stack parts were procured and prototype MEAs were fabricated. The fabricated parts were tested and found to be within specification. A new test stand was also completed for future testing of large active area cell stacks. Alternate techniques for forming the plates which are recommended for further study include chemical milling, stamping, and vertical milling or machining. These techniques had good tolerance control with reasonable removal rates and lower capital cost than techniques such as laser machining.

Power conversion efficiency for electrolysis can be improved to 95% or better for both direct interface with renewable sources or using the grid as an interconnection. Other areas of improvement include optimizing the system as a whole to determine the optimum cell stack temperature, pressure, and operating current density.

The results of the integration simulations showed that varying the hydrogen generation rate based on available power from the wind turbine yields poor utilization of capital (low capacity factor for the hydrogen generator). At present and into the near future, the off-grid approach to

hydrogen generation is not favorable for large scale hydrogen generation due to the capital cost of PEM based hydrogen generation. The RE-Grid Fixed Capacity hydrogen generator is therefore the most economical approach a present.

Today's commercially available PEM-based hydrogen generators employ MOSFET-based AC/DC converters up to 40 kW. There are opportunities for SCR-based converters to provide low cost and reliable solutions in the realm of 25 kW to 100 kW if IEEE519 compliance is not required. Above 100 kW power levels, IEEE519 compliance could be a concern. At higher power levels, IGBT-based converters become attractive when compared to adding complexity and costly magnetics to SCR-based approaches.

Using the electrochemical model developed in this program, incorporation of the above work into the H2A model projects a cost savings of over 50% in \$/kg hydrogen vs. the baseline cost as all the proposed advancements are further proven out and progressed to commercialization. Still, further work is needed to meet DOE targets. Based on the work accomplished in this program, additional improvements in catalyst performance are possible by continuing to optimize the synthesis conditions and composition. These improvements could enable lower catalyst loadings, decreasing cost. Optimizing the membrane properties based on the information gained in Task 2 is another area of opportunity. Processing changes and changes in surface treatment of stack parts also show promise. These areas have been proposed for further collaboration with UNLV in a follow on program.

6 References

- ¹ Final Report: Enhance Filling Station at Las Vegas Valley Water District (LVVWD)
- ² Interim Report of PEM Electrolysis Membrane Candidates
- ³ Final Report of PEM Electrolysis Membrane Candidates
- ⁴ Zhang, Y., et al, *Int. J. Hydrogen Energy*, **32**, p. 400-404 (2007).
- ⁵ Interim Report of PEM Electrolysis Catalyst Candidates
- ⁶ Final Report of Experimental Catalyst Characterization Results
- ⁷ Final Report of Experimental MEA Characterization Results
- ⁸ Final Report of Bipolar Plate Designs
- ⁹ Final Report of Cell Stack Scale Up and Manufacturability Assessment
- ¹⁰ Interim Report of Renewable Electronics Interface for PEM Electrolysis: Operation and Data Collection of Phase I system
- ¹¹ Final Report: Renewable Electronics Interface for PEM Electrolysis Subtask: Renewable Energy and PEM Electrolysis: Renewable System Architecture Optimization Study
- ¹² Final Report of the Cell Stack Performance and Cost that Incorporates Advanced Components

7 Appendices

The following referenced task reports are incorporated herein and attached as appendices.

1. Deliverable Report: Interim Report of PEM Electrolysis Membrane Candidates
2. Deliverable Report: Final Report of PEM Electrolysis Membrane Candidates
3. Deliverable Report: Interim Report of PEM Electrolysis Catalyst Candidates
4. Deliverable Report: Final Report of Experimental Catalyst Characterization Results
5. Deliverable Report: Final Report of Experimental MEA Characterization Results
6. Deliverable Report: Final Report of Bipolar Plate Designs
7. Deliverable Report: Final Report of Cell Stack Scale Up and Manufacturability Assessment
8. Deliverable Report: Interim Report of Renewable Electronics Interface for PEM Electrolysis: Operation and Data Collection of Phase I system
9. Deliverable Report: Final Report on Renewable Electronics Interface for PEM Electrolysis: Renewable Energy and PEM Electrolysis: Renewable System Architecture Optimization Study
10. Deliverable Report: Final Report of the Cell Stack Performance and Cost that Incorporates Advanced Components

ATTACHMENT 8

RESEARCH FOR HIGHER EFFICIENCY PEM TECHNOLOGY – FINAL REPORT OF EXPERIMENTAL MEA CHARACTERIZATION TEST RESULTS

PREPARED BY:

**PROTON ENERGY SYSTEMS
February 12, 2008**

RESEARCH FOR HIGHER EFFICIENCY PEM TECHNOLOGY

Final Report of Experimental MEA Characterization Test Results

Prepared by

Proton Energy Systems
10 Technology Drive
Wallingford, CT 06492

February 12, 2008

Prepared for:

University of Nevada Las Vegas Research Foundation
Under Subcontract No. RF-05-HFS-005-A03

Under U.S. Department of Energy, Golden Field Office
Contract No. DE-FG36-03GO13063

Table of Contents

1	Summary	3
2	Introduction.....	3
3	Approach.....	5
4	Results and Discussion	8
5	Conclusions and Recommendations	14
6	References.....	14

Table of Figures

Figure 1: Table of materials used in Screening Tasks	7
Figure 2: Results of pre-electrolysis stack testing	8
Figure 3: Voltage trend at 530 hrs of running operation	9
Figure 4: Voltage trend at 620 hrs of running operation	10
Figure 5: Voltage trend at 510 hours of operation.....	10
Figure 6: Polarization Curve, 500 hours, Membrane G, Catalyst C (Metal 1)	11
Figure 7: Voltage trend at 1085 hrs of running operation	12
Figure 8: Delta voltage of MEAs over baseline.....	12
Figure 9: Polarization curves of 3 MEAs at 500 hours.....	13
Figure 10: Voltages from polarization curves	13

Summary Report of Experimental MEA Characterization Test Results

1 Summary

Previous reports have described the research performed for this program on alternate membrane and catalyst materials to improve efficiency of the PEM cell for water electrolysis. As discussed in those reports, promising candidates were found in each area, based on single component testing within the baseline MEA design. Fundamental understanding was also developed which provides direction for future studies. This report describes the combination of experimental membranes and catalysts within the same MEA structure in order to optimize performance. Also included in this study is evaluation of a commercial MEA vs. the current baseline in-house MEA.

The results showed a slight improvement when both the baseline catalyst and membrane were replaced with optimal alternatives vs. replacing individual components, but the impact was not completely additive. The discrepancies may be due to variation in the process and baseline performance, and further statistical analysis is recommended. The commercial MEA performed at a lower voltage than the baseline but did not show as large an improvement as the optimized catalyst/membrane combination developed in house. The research performed in this task and the previous tasks demonstrate significant efficiency improvements over current commercial production and highlight additional directions for further performance and cost optimization.

2 Introduction

General:

While on-site PEM electrolysis of water to form hydrogen is an attractive alternative to delivered hydrogen for many applications, there are opportunities for efficiency improvements in the current production designs. Most of the overpotential loss within the cell stack arises from two components: 1) the ionic resistance of the membrane and the activation energy at the anode catalyst for production of oxygen.¹

The ionic resistance in the membrane is directly correlated to the membrane thickness for a given membrane material. As discussed in the membrane evaluation reports, membrane candidates for PEM water electrolyzers are typically thicker than those employed in fuel cells due to the higher pressure loadings experienced by the membrane in the electrolysis environment. The membrane must also be able to withstand the higher potentials experienced in the electrolyzer, which exceed 1.5 V. Fluorinated ionomers such as Nafion have been found to be suitable for these applications but are typically more expensive than hydrocarbon-based materials.

On the catalyst side, electrolysis voltage requirements again limit the range of suitable materials, and to date only noble metals have successfully demonstrated the required long term stability for electrolysis. Therefore, the focus of this work was to maximize catalyst efficiency with the goal of reducing catalyst loading in order to reduce cost. An important parameter in enabling lower catalyst loading is high surface area. Nanometer-sized powders for evaluation in this program were obtained from a commercial supplier or made in house.

Work in both of these areas has been discussed in previous reports and is summarized briefly below. This report details the characterization of MEAs made from the optimized material combinations based on the previous studies of membranes and catalysts. A commercial MEA from an alternate supplier was also included in the analysis for comparison.

Summary of Catalyst and Membrane Evaluations:

Membrane candidates were narrowed down through several stages of testing. The first stage was essentially a characterization of the membrane physical and chemical properties; no candidates were eliminated based on these tests alone. In this stage, properties such as thickness, acid capacity, water content, and chemical stability were measured. These results were published in the interim membrane characterization report.² The major differences observed were 1) experimental membranes were substantially thinner than baseline, 2) only one membrane passed the rigorous Fenton's reagent stability test, 3) failure elongation strength of one membrane was much lower than baseline, and 4) water permeation values for the experimental membranes tested were higher than baseline. Some of these results led to concerns about the durability of the materials, but not enough information was known about correlations with processing and stack data to determine whether the membranes would fail without further testing. The results of these studies should enable firmer specification limits in future investigations.

Membranes were then processed into MEAs as discussed in the membrane summary report.³ The elimination process began at this phase. Several of the membrane candidates degraded under normal manufacturing conditions. Before ruling out these materials, a parametric study of processing variables was performed in order to determine whether the membranes could be successfully processed with milder conditions. Three of the original six membranes still could not withstand the minimum temperatures and pressures required to remove the catalyst decals from the manufacturing substrate and were eliminated from further study. A second screening criterion was the ability of the MEA to electrolyze water at production current densities and pressures for at least 500 hours. Only one fluorinated membrane besides the baseline membrane successfully passed the electrolysis testing. The hydrocarbon membranes tested showed durability issues due to the low thickness and high brittleness of these membranes and were not recommended for evaluation. During the evaluation period, an additional fluorinated membrane material was discovered to have promising properties and was incorporated into testing described in this report.

In a separate study, two pure metal oxides and 50%/50% blends with a third metal were tested as anode catalyst materials in this program. Catalyst powders were subjected to physical characterization, but as in the membrane case, none were eliminated solely based on physical properties. All of the anode catalyst candidates had at least three times the surface area of the baseline catalyst. These results as well as SEM documentation of the nanoparticulate structure of the powders were detailed in the interim catalyst characterization report.⁴ The catalysts were all successfully processed into MEAs and tested for 500 hours. A fourth metal was tested as an alternate cathode catalyst material but was deficient to the baseline material, likely due to the very low surface area of the sample received, and was not pursued further in this program.

Electrochemical properties of the catalysts were also measured, as discussed in the catalyst summary report.⁵ The % electrochemically active area was found to correlate well with the

initial cell voltage, with several candidates showing improvement vs. the baseline. However, some of the catalysts were unstable over long periods of electrolysis which resulted in unacceptably high stack voltages by the end of the 500 hour test. Only one of the original compositions exceeded the baseline performance over the whole testing period.

Trends as a function of metal type and synthesis method were noted in the results. For the same metal oxide type, powders made in house outperformed the commercial powders. Metal 2 showed good initial performance vs. Metal 1 but degraded over time. Blending with a third metal helped to stabilize the material, but both blended catalysts showed a decrease in the fraction of electrochemically accessible area which correlated to an increase in cell potential. Based on this knowledge, an additional catalyst composed of a blend of the first two metal oxides was designed and carried forward for evaluation, in the hope that Metal 1 would perform the same stabilization as Metal 3 without the detrimental impact on active area.

3 Approach

The original membrane and catalyst materials tested are summarized below, with the matrix of MEAs manufactured for this task at the bottom.

Membrane Candidates from Screening Task		
Potential Supplier	Samples Supplied	Membrane Type
Dupont	1 (A)	Nafion baseline
A	1 (F)	Composite
H	5 (B, C, D, E, G)	Fluorinated and non-fluorinated
Catalyst compositions from Screening Task		
Source	Composition	
Commercial	A (100% Metal 1) B (100% Metal 2) G (100% Metal 4)	
Fusion	C (100% Metal 1) D (100% Metal 2) E (50% Metal 1, 50% Metal 3) F (50% Metal 2, 50% Metal 3)	
MEA matrix for Evaluation Task		
Catalyst	Demembrations	Description

	i o n		
C	M e t a l 1	H (n e w)	Fluorinated, Dupont membrane
H (new)	5 0 % M e t a l 1 / 5 0 % M e t a l 2	H (n e w)	
C	M e t a l 1	G	Fluorinated, Supplier H membrane
Commercial MEA			From supplier H

Figure 1: Table of materials used in Screening Tasks

Catalyst Synthesis:

As described in the catalyst reports, catalyst powders were synthesized by pyrolyzing a soluble chloride salt of the desired metal. This method has been shown to yield metal oxide powders with high surface area and high purity. The two catalysts carried forward were 1) the pure oxide identical in composition to the baseline, and 2) a blend of this metal with Metal 2 as discussed above.

MEA Processing:

MEAs were manufactured using a decal transfer process. As discussed above, the Membrane G needed milder conditions than the typical production parameters to avoid degradation. This membrane was pressed at significantly lower temperature than the baseline material, but at similar pressure loading over the active area. This procedure had been shown to result in complete transfer of the decal without visible damage to the membrane material during the membrane task research.

Testing:

MEAs were built into multi-cell stacks containing at least 1 experimental MEA and 1 baseline MEA. The stack was subjected to standard acceptance protocol testing before electrolysis, as detailed in earlier reports. Stacks were then tested at a current density of 1720 ASF to 500 hours of operation or until cell failure. Polarization curves and voltage data as a function of time at constant current were collected. A comparison of the results is presented in this report.

4 Results and Discussion

Results of pre-electrolysis testing performed on the cell stacks with the optimized MEA configurations are shown in the table below. Cell 2 in each of the stacks was a baseline MEA composed of typical membrane and catalyst materials used in production. All of the stacks were within specification for the ATP protocols and passed the testing. However, the ATP criteria were developed for safe operation of the stacks rather than performance comparisons. As seen in the table, the MEAs made from membrane G showed higher resistance than the baseline membrane, while the Membrane H MEAs were significantly lower in resistance. These results are expected to translate into differences in cell voltage.

TEST BEFORE ELECTROLYSIS					
Cell Stack		Catalyst C Membrane H	Catalyst H Membrane H	Catalyst C Membrane G	Commercial MEA
<i>Stack Temp, °F</i>		74.0	72.5	74.0	71.5
<i>Diffusion Rate</i>					
<i>@ 200 psid (cc/min/cell)</i>		Pass	Pass	Pass	Pass
<i>@ 100 psid (cc/min/cell)</i>		Pass	Pass	Pass	Pass
<i>Resistance (Temp < 80 F)</i>					
@ Ambient	1	0.6X	0.6X	1.2X	0.8X
	2	Pass	Pass	Pass	Pass
	3	0.6X	0.6X	1.2X	0.8X
@ 200 psid	1	0.6X	0.6X	1.2X	0.8X
	2	Pass	Pass	Pass	Pass
	3	0.6X	0.6X	1.2X	0.8X
<i>Short Check</i>					
Pass/Fail		Pass	Pass	Pass	Pass

Figure 2: Results of pre-electrolysis stack testing

The electrolysis data is summarized in the next several figures. All stacks were run at 160 amps, 50°C, and 200 psid H₂ pressure. The cells containing Catalyst C and Membrane H were run 530 hrs without failure as shown in Figure 3.

Figure 3: Voltage trend at 530 hrs of running operation

The cell voltage of MEAs with Catalyst C and Membrane H was significantly lower (an average of 230 mV as shown in Figure 8) than the cell voltage for the baseline MEA. These results are somewhat consistent with expectations, in that the voltage difference for the combined catalyst/membrane optimization vs. baseline was higher than either of the individual component substitutions, but the voltage differences for these evaluations were not fully additive. This discrepancy could be due to many factors, including differences in the respective baseline cell voltages or variability contributions from the other cell stack parts.

The stack containing Catalyst H and Membrane H was successfully run for 620 hrs as shown in Figure 4. The performance of these cells are very similar to the MEA with catalyst C and Membrane H, but the voltage difference from baseline is slightly higher (an average of 250 mV as shown in figure 8). Note that the baseline voltage was slightly higher in this stack than in the previous figure; it is unknown whether the slight improvement in voltage relative to the baseline for Catalyst H vs. Catalyst C is just due to variation in the baseline cell or whether there is an additional resistance in the overall circuit for the stack containing Catalyst H. A larger cell stack containing multiple cells of each catalyst type would yield a more direct comparison and also provide more statistically significant results. Future work could explore these issues as well as further optimization of the materials.

Figure 4: Voltage trend at 620 hrs of running operation

Figure 5 shows the voltage trends for Catalyst C with Membrane G. While the cell stack successfully lasted through 500 hours of operation, there was no improvement with this membrane vs. the baseline. In addition, the voltage performance for experimental membrane appeared to degrade more than the baseline over the time tested.

Figure 5: Voltage trend at 510 hours of operation

Polarization curves for this stack were obtained at 100 hrs and 500 hrs. The polarization curve shown in Figure 6 below represents the Membrane G and Catalyst C combination versus the baseline MEA configuration.

Figure 6: Polarization Curve, 500 hours, Membrane G, Catalyst C (Metal 1)

While the membrane potentials appear to be equivalent to within 10-20 mV, Membrane G is less than half the thickness of the baseline membrane material for this test and was expected to perform significantly better. It is also known that the equivalent weight for this membrane is higher than that of the baseline material, which likely explains an increase in the ionic resistance, though this value may not be directly comparable to the baseline due to differences in the polymer structure.

After 500 hours of operation, the MEAs were analyzed for degradation. The MEAs passed post test acceptance criteria prior to taking the stack apart. Each membrane was analyzed for defects that could lead to future failure. Both cells made with Membrane G showed signs of significant thinning around a circumferential seal location in the hardware when compared to the baseline. With basic handling, tears easily developed along these thinned areas, similar to the tears observed on post-analysis from the membrane evaluation task.

The commercial MEA stack successfully ran 1085 hrs as shown in Figure 7. The performance of these cells is better than the baseline MEA (an average of 199 mV as shown in Figure 8) but the voltage advantage is lower vs. the two other experimental stacks developed in house. In addition, this stack failed short check testing at the completion of the electrolysis testing.

Figure 7: Voltage trend at 1085 hrs of running operation

The overall performance differences for the 3 MEAs that outperformed the baseline MEA are summarized in Figure 8 below. As discussed above, the MEA with the new catalyst and membrane for this task had the highest change in voltage vs. baseline, but there were some differences between the baselines which confuse interpretation of the results.

Figure 8: Delta voltage of MEAs over baseline

Figure 9 below shows the polarization curve of these MEAs after 500 hours of continuous operation at 1740 Amps/ft².

Figure 9: Polarization curves of 3 MEAs at 500 hours

Note that the voltage data to obtain polarization curves was an average of voltage of two experimental cells in each stack. Also, the cell voltage for the Catalyst H/Membrane H MEA was actually slightly lower than the Catalyst C/Membrane H cell voltage, even though there was a larger ΔV for this MEA vs. the baseline MEA tested in the same stack. Again, a direct comparison of these materials in the same stack under simultaneous testing would be useful in clarifying the relative performance of these two catalysts. The ΔV was also lower than expected when compared to the cell voltages from membrane and catalyst evaluation tasks.

Polarization curve results at two current densities and two times for all of the MEAs evaluated in this report are summarized in Figure 10 below vs. a single baseline MEA. The results for the 100 hour and 500 hour polarization curves were very similar to each other, as expected from the voltage-time plots.

	100 hour polarization curve		500 hour polarization curve	
	1000 ASF	2000 ASF	1000 ASF	2000 ASF
Baseline MEA	1.870	2.177	1.876	2.194
Catalyst C, Membrane H	1.729	1.914	1.740	1.937
Catalyst C, Membrane G	1.855	2.151	1.879	2.201
Catalyst H, Membrane H	1.729	1.920	1.748	1.963
MEA Commercial	1.772	1.993	1.772	1.985

Figure 10: Voltages from polarization curves

The trends were consistent with the ATP results, with the lower resistance values translating to lower electrolysis voltages. Within a class of membrane types, the electrolysis overpotential decreased substantially as the membrane thickness decreased. However, despite being thinner than Membrane H, Membrane G performed similarly to the much thicker baseline material. Additional understanding of the relative impact of polymer chemical structure, membrane thickness, polymer equivalent weight, and processing conditions is needed to better predict performance.

5 Conclusions and Recommendations

Both experimental catalysts with Membrane H showed substantial improvements over the baseline MEA, as expected. The membrane change is likely contributing most of the voltage difference, based on previous measurements. The higher surface area of the catalyst should also provide a voltage benefit. However, there were discrepancies between the cell voltages predicted by adding the voltage differences due to the optimal catalyst and membrane from the membrane and catalyst evaluation tasks independently vs. the actual cell voltage of the optimized MEA. There were also differences in voltages for the baseline cells, which make it difficult to make a direct comparison of experimental cells from different stacks. Relative to the respective baselines, Catalyst H showed the largest improvement, but Catalyst C showed the lowest absolute voltage. The commercial MEA tested also showed significant efficiency advantages over the baseline, but performed at a slightly higher voltage than either of the combinations made in house.

Membrane G showed little improvement when compared to baseline. When evaluated relative to thickness, Membrane G would not pass as a good candidate to substitute with the baseline. However, one disadvantage that should be emphasized is the non-optimized manufacturing process for this membrane. This membrane could not withstand the processing conditions of the baseline membrane; this indicates significant differences in chemical composition that affects the material's physical properties. An optimization of membrane processing parameters should be investigated to determine if the processing conditions impacted the cell performance.

While the work done in this task was successful in that MEA constructions with higher performance than the current baseline were identified, it also identified several areas for future work. There may be interactions between the membrane and catalyst type which impact the overall cell performance. The interface of the catalyst layer and the membrane is critical in optimizing the three-phase boundary between ionic, electronic, and reactant/product domains. The relative importance of membrane thickness and equivalent weight as a function of membrane chemistry is also an important area for study. Better understanding of these areas are likely to make an even more significant impact on MEA performance based on better tailoring of the material properties.

6 References

-
- ¹ Final Report of the Cell Stack Performance and Cost that Incorporates Advanced Components
 - ² Interim Report of PEM Electrolysis Membrane Candidates
 - ³ Final Report of PEM Electrolysis Membrane Candidates

ATTACHMENT 9

RESEARCH FOR HIGHER EFFICIENCY PEM TECHNOLOGY

FINAL REPORT OF EXPERIMENTAL CATALYST CHARACTERIZATION TEST RESULTS

PREPARED BY:

**PROTON ENERGY SYSTEMS
October 15, 2007**

RESEARCH FOR HIGHER EFFICIENCY PEM TECHNOLOGY

Final Report of Experimental Catalyst Characterization Test Results

Prepared by

Proton Energy Systems
10 Technology Drive
Wallingford, CT 06492

15 October 2007

Prepared for:

University of Nevada Las Vegas Research Foundation
Under Subcontract No. RF-05-HFS-005-A03

Under U.S. Department of Energy, Golden Field Office
Contract No. DE-FG36-03GO13063

Table of Contents

1	Summary	3
2	Introduction.....	3
3	Approach.....	4
3.1	Electrode manufacture	5
3.2	Testing protocol	5
4	Results and Discussion	6
5	Conclusions and Recommendations	12
6	References.....	13

Table of Figures

Figure 1: Table of catalysts screened.....	3
Figure 2: Catalyst A: 2500X.....	4
Figure 3: Catalyst C: 2500X.....	4
Figure 4: Catalyst C: 75000X.....	4
Figure 5: Results of pre-electrolysis stack testing.....	7
Figure 6: Voltage vs. time data for MEAs containing experimental catalysts.....	7
Figure 7: 500 hour polarization curve.....	8
Figure 8: Table of voltages for polarization curves.....	8
Figure 9 Table of post-electrolysis testing results.....	9
Figure 10: % Electrochemically accessible area vs. catalyst type.....	9
Figure 11: Tafel slope vs. Catalyst type.....	10
Figure 12: Current density at 1.5 V vs NHE.....	11
Figure 13: % Active Area vs. initial cell stack voltage.....	11
Figure 14: Current density at low overpotential vs. initial cell voltage.....	12

Final Report of Experimental Catalyst Characterization Test Results

1 Summary

The interim report for this task discussed selection of alternate catalyst materials for PEM water electrolysis. Although many suppliers were approached, only one supplier was able to provide suitable materials for evaluation. Therefore, additional catalyst samples were synthesized in house using fusion techniques. Screening focused on noble metals and metal oxides, including some blends of two metals. Detailed results for SEM/EDS and BET surface area were presented in the survey report and are summarized in this report. Based on the results, 7 materials including the baseline material were passed to the electrochemical testing phase, described in this report. Electrochemical evaluation included flooded cell testing as well as full stack testing in MEAs with our baseline membrane. Next steps include combining the best catalyst candidates from this task with the best membrane candidates for MEA evaluation.

2 Introduction

2.1 General:

As discussed in the survey report, the theoretical voltage for water electrolysis is 1.23 volts, but the operating voltage of an electrolyzer is higher due to ohmic losses and kinetic limitations of the system at high current density. Much of the overpotential arises from the anode, due to the complex nature of the 4-electron water oxidation reaction to produce oxygen. In contrast, the cathode overpotential is very low. Therefore, the focus of this study was the anode catalyst, although work on both catalysts is needed to reduce catalyst loading and overall cell cost. While research is ongoing on non-noble metal catalyst materials and carbon-supported catalysts, it is our belief that at the current time this technology is still immature and the required performance and stability for water electrolysis in acid are not yet available. Our strategy was therefore to examine noble metals and noble metal oxides, as pure oxides or binary mixtures, as shown in Figure 1. One cathode catalyst candidate was also included from the supplier that provided the other commercial samples.

Catalyst Type	Catalyst Composition (wt %)			
	Metal 1	Metal 2	Metal 3	Metal 4
Commercial				
A	100%	0	0	0
B	0	100%	0	0
G	0	0	0	100%
In-House				
C	100%	0	0	0
D	0	100%	0	0
E	50%	0	50%	0
F	0	50%	50%	0

Figure 1: Table of catalysts screened

An important parameter in enabling lower catalyst loading is high surface area. This dictates a preference for nanometer-sized powders (“nanopowders”) with irregular surfaces and/or porosity.

The fusion process of pyrolyzing a soluble metal chloride (typically valence (III)) has been shown to form powders of this type. The pure oxide materials made in house will be compared to commercial samples of similar composition.

2.2 Summary of Initial Screening Results:

All powders were characterized by visual inspection/SEM and surface area by single point BET, as discussed in the survey report.¹ No catalysts were eliminated as a result of these tests. Of the metal oxides, the baseline catalyst had the lowest surface area ($32 \text{ m}^2/\text{g}$) while the other samples were all near $100 \text{ m}^2/\text{g}$. EDS showed low oxygen content for all of these catalysts. Oxygen content is difficult to measure in these highly insoluble metal oxides, and EDS is not ideal due to the high molecular weight and resulting signal strength of the metal vs. oxygen which can cause overestimation of the metal content. However, qualitative comparisons can be made, since the catalysts were tested under the same instrument settings.

The Metal 1 oxides were very similar to each other in oxygen content, while the commercial Metal 2 oxide had slightly lower oxygen content than the Metal 2 oxide synthesized in house. In contrast, the metal oxide blends containing Metal 3 were considerably lower in oxygen content than the pure oxides vs. theoretical, indicating lower average oxidation state of the metals. These powders likely either contain the metallic or dicationic form of Metal 3. Catalyst G, a metallic powder, was only available in micron-sized powder and had much lower surface area, just below $1 \text{ m}^2/\text{g}$.

SEM photos of all of the metal oxide catalysts showed them to be highly agglomerated, with primary particle sizes smaller than 100 nm. Examples of typical SEM photos are shown in Figures 2-4 below. At 2500X magnification, the agglomerate size for Catalyst A appears somewhat larger than Catalyst C (Figures 2 and 3), and the agglomerates have a smoother, more rounded appearance, although at high magnification (75000X) the primary particles look very similar to each other (Figure 4).

Figure 2: Catalyst A: 2500X

Figure 3: Catalyst C: 2500X

Figure 4: Catalyst C: 75000X

3 Approach

MEAs were tested vs. the baseline material. In most cases, catalyst activity is discerned from performance of MEAs manufactured with the powder. Of course, this measurement is confounded by MEA manufacturing variables and electrolyzer system variables. There is a clear

need within the industry to measure the electrochemical properties of these materials for more rapid screening, fundamental understanding, and ongoing quality control. Therefore, in parallel with testing of these alternate catalyst materials in MEAs, standard tests were developed for electrochemical screening of the materials, described in further detail below.

3.1 Electrode manufacture

3.1.1 MEA manufacture:

Catalysts were made into MEAs using a standard in-house fabrication method. The catalysts were prepared as electrodes and transferred to Nafion membrane at elevated temperature and pressure. Standard Proton Energy Systems (Proton) catalyst loadings for each electrode (hydrogen and oxygen) were used. The MEAs were then assembled into cell stacks using typical Proton production methods.

3.1.2 Flooded cell electrodes:

Electrodes for flooded cell testing were constructed very similarly to the MEAs above. The catalyst powders were prepared as 2 cm² electrodes and then transferred to Nafion membrane. The Nafion substrate was cut and the electrode was pressed between two layers of platinized screen for conductivity and stability. The contacting tab and the Nafion side of the electrode were encased in epoxy so that only the side of the electrode where catalyst powder could directly access the electrolyte was exposed.

3.2 Testing protocol

3.2.1 Stack Testing:

MEA testing was performed at 50°C and 200 psid hydrogen back pressure. Stacks were operated at 160 A (1720 ASF, 1850 mA/cm²) for at least 500 hours, and polarization curves were obtained at 100 and 500 hours. Before and after the electrolysis testing, high frequency resistance testing at 0 psi and 200 psid and leak/diffusion testing at 100 psid and 200 psid were performed. Each cell stack contained one MEA prepared with the baseline catalyst as a consistent comparison to the experimental catalyst.

3.2.2 Bench cell tests:

Electrochemical testing was performed on a computer-controlled Gamry potentiostat with a maximum current of 750 mA. The test cell was a commercial corrosion cell with 4 electrode ports on the top of the cell. Electrode holders for the working and counter electrodes filled two of the ports, and a third port contained a Luggin capillary which contained an Hg/HgSO₄ reference electrode containing 0.5 M H₂SO₄. The measured potential of this electrode vs. a commercial Ag/AgCl electrode was 0.451 V, corresponding to 0.65 V vs. NHE. The fourth electrode port was left open and a nitrogen bubbler was inserted to purge the solution. The contact tabs or wires for the working and counter electrodes were sealed in ¼ in glass tubing to ensure reproducible placement of the electrodes in the holders, which had an inner diameter of ¼ in. The counter electrode was a large platinum mesh electrode.

Electrochemically active area

Cyclic voltammetry experiments were developed to estimate the electrochemically active area of the catalyst for comparison to the geometric area. Past work on high surface area anhydrous noble metal oxides has shown that cyclic voltammograms in 0.5 M acid are mainly capacitive

due to ion exchange with the solution.². At high scan rates, only the sites near the surface of the electrode are electrochemically accessible. The scan rate dependence is expected to be:

$$q^*(v) = q_{\infty} + \text{const}\left(\frac{1}{\sqrt{v}}\right)$$

Where q_{∞} is the charge at the “outer” surface of the electrode and v is the scan rate. Therefore, the electrochemically active surface area can be estimated by extrapolating to infinite scan rate. At slower scan rates, the protons are able to diffuse farther within the pores of the electrode structure, yielding higher charge values. The total surface area can then be estimated by extrapolating to zero scan rate, with the following equation:

$$\frac{1}{q^*(v)} = \frac{1}{q_0} + \text{const}(\sqrt{v})$$

The ratio of these two numbers gives an indication of how much of the surface area of the powder is accessible for reaction at higher current densities, where diffusion becomes important. Scan rates of 1 mV/s to 20 mV/s were used to calculate the electrochemically accessible area. At higher scan rates, the cyclic voltammograms began to differ substantially from ideal capacitor behavior, most likely due to ohmic resistance losses.

Intrinsic kinetics

Tafel plots at low current density were also collected to estimate the intrinsic kinetics of the catalyst materials in relation to each other. Higher exchange current densities and lower overpotential for oxygen evolution at constant current density (1 mA/cm²) indicate higher catalytic activity. Due to the highly capacitive nature of these materials, polarization data had to be collected by performing a 2 minute potential step experiment for each data point in the Tafel plot, allowing the current to reach a steady-state value. It was found that the results were much more consistent when the electrodes were pre-polarized for 5 minutes to a constant potential of 0.4 V vs. the Hg/HgSO₄ reference electrode (~1.05 V vs. NHE) immediately before the potential step. Potential steps of 0.6 to 0.85V vs. Hg/HgSO₄ were used to construct the Tafel plot.

4 Results and Discussion

4.1 MEA testing

Results of the pre-electrolysis testing performed on the cell stacks are shown in Figure 5 below for each catalyst material. In each stack, the MEA in Cell 2 was manufactured from the baseline catalyst and Cells 1 and 3 contained the experimental material. All of the cell stacks passed the typical criteria for hydrogen diffusion rates and cell resistances, and none failed the short check.

TEST BEFORE ELECTROLYSIS						
Cell Stack	Catalyst A/B	Catalyst A/C	Catalyst A/D	Catalyst A/E	Catalyst A/F	Catalyst A/G
Stack Temp, °F	71	70	75	75	71	73
Diffusion Rate						
@ 200 psid	Pass	Pass	Pass	Pass	Pass	Pass
@ 100 psid	Pass	Pass	Pass	Pass	Pass	Pass
Resistance (Temp < 80 F)						
@ Ambient	1	Pass	Pass	Pass	Pass	Pass
	2	Pass	Pass	Pass	Pass	Pass
	3	Pass	Pass	Pass	Pass	Pass
@ 200 psid	1	Pass	Pass	Pass	Pass	Pass
	2	Pass	Pass	Pass	Pass	Pass
	3	Pass	Pass	Pass	Pass	Pass
Short Check						
Pass/Fail	Pass	Pass	Pass	Pass	Pass	Pass

Figure 5: Results of pre-electrolysis stack testing

The voltage vs. time data for constant current electrolysis is shown in the Figure 6 below. Several of the alternate materials started at lower potentials than the baseline catalyst, but cells containing Catalysts B and D began to increase rapidly in voltage well before 500 hours of operation. The only catalyst powder that consistently maintained a lower voltage than the baseline material was Catalyst C. Catalyst G was consistently high in operating voltage throughout the test, most likely due to the lower surface area.

Figure 6: Voltage vs. time data for MEAs containing experimental catalysts

The polarization curve at 500 hours is shown in Figure 7 below. Consistent with the constant current voltage data, only Catalyst C is significantly below the baseline catalyst over the entire

polarization range. Catalysts B and D showed high overpotential, especially at the higher current densities; these catalysts had already shown considerable voltage increases vs. the initial performance due to degradation of the MEA.

Figure 7: 500 hour polarization curve

The voltages for both the 100 hour and 500 hour polarization curves are summarized in the table below, showing similar trends.

	100 hour polarization curve		500 hour polarization curve	
	1000 ASF	2000 ASF	1000 ASF	2000 ASF
<i>Baseline- Catalyst A</i>	1.868	2.175	1.870	2.186
<i>Catalyst B</i>	-----	-----	2.519	2.978
<i>Catalyst C</i>	1.803	2.058	1.811	2.071
<i>Catalyst D</i>	1.789	2.064	2.147	2.737
<i>Catalyst E</i>	1.872	2.147	1.870	2.157
<i>Catalyst F</i>	1.854	2.136	1.882	2.184
<i>Catalyst G</i>	2.126	2.442	2.116	2.430

Figure 8: Table of voltages for polarization curves

Figure 9 shows the diffusion and resistance measurements for the anode catalyst materials after electrolysis. The cells containing Catalysts B and D showed high resistance after the testing. The resistance may be caused by dissolution of the Metal 2 oxides, reducing the conductivity of the anode catalyst layer, or by a decomposition reaction that causes a resistive layer in the cell. It was noted when storing the MEAs in water prior to building the mesh electrodes for the electrochemical testing, the Nafion darkened in the solutions containing electrodes with Metal 2, and some powder was noticed in the water. This observation supports the dissolution mechanism for increased resistance.

TEST AFTER ELECTROLYSIS						
Cell Stack		Catalyst A/B	Catalyst A/C	Catalyst A/D	Catalyst A/E	Catalyst A/F
<i>Stack Temp, °F</i>		73	71	73	71	73
<i>Diffusion Rate</i>						
@ 200 psid (cc/min/cell)		Pass	Pass	Pass	Pass	Pass
@ 100 psid (cc/min/cell)		Pass	Pass	Pass	Pass	Low
<i>Resistance (Temp < 80 °F)</i>						
@ Ambient	1	5X	Pass	16X	Pass	Pass
	2	Pass	Pass	2X	Pass	Pass
	3	5X	Pass	16X	Pass	Pass
@ 200 psid	1	4X	Pass	14X	Pass	Pass
	2	Pass	Pass	2X	Pass	Pass
	3	4X	Pass	13X	Pass	Pass
<i>Short Check</i>						
Pass/Fail		Pass	Pass	Pass	Pass	Pass

Figure 9 Table of post-electrolysis testing results

4.2 Bench Testing Results

Electrochemically active area:

Calculations of the % active area from the cyclic voltammetry experiments are shown in Figure 10 below.

Figure 10: % Electrochemically accessible area vs. catalyst type

The data showed several points of interest. First, commercial Catalysts A and B showed considerably lower % active area vs. the corresponding in-house catalysts C and D, despite the identical compositions. Second, all of the catalysts containing Metal 2 had higher % active area

than the corresponding catalyst with Metal 1 substituted (B vs. A; D vs. C; F vs. E). Finally, the addition of Metal 3 in the blended metal oxides severely depressed the % active area, compared to the pure metal oxides using the same synthesis methods (Catalysts E and F vs. C and D).

These results are important because they point out fundamental differences in the catalyst materials which may relate to MEA performance. Electrochemical tests which can predict stack performance can save considerable cost and labor by eliminating poor performing candidates with very little catalyst required and none of the rest of the stack assembly. Direct comparison to the stack testing results is discussed further below.

Kinetic data

The Tafel slopes calculated from the potential step experiments are shown in Figure 11. There was little difference in the slope for the different catalysts with the exception of Catalyst E, which was over 20 mV/decade higher than the other powders. All of the other catalysts were near 90-100 mV/decade. These values are high vs. many of the reported values for noble metal catalysts for water oxidation, although the numbers vary depending on the rate-limiting step in water oxidation at specific surface types. It is known that the synthesis method can impact the Tafel slopes of these materials, which may explain some of the difference. These electrodes also contain binder which may impact the accessibility of reactive sites, and the electrode loading and structure was designed to be similar to standard manufacturing conditions, which may not be ideal for this type of measurement. Therefore, the Tafel slopes are used as comparison numbers only rather than for mechanistic understanding.

Figure 11: Tafel slope vs. Catalyst type

More differentiation was noted in the current densities at fixed overpotential, as seen in Figure 12. While there was some variability in the results, the catalysts containing Metal 2 (Catalysts B, D, and F) had significantly higher currents at 1.5 V vs. NHE than the corresponding catalysts containing Metal 1 (Catalysts A, C, and E). These results suggest Metal 2 has inherently higher

activity than Metal 1 for water oxidation. These results are also consistent with the higher electrochemically active area for Metal 2, which would decrease the effective current density.

Figure 12: Current density at 1.5 V vs NHE

Comparison with stack data:

The % active area and current density at 1.5 V were each plotted vs. the initial operating cell voltage at 1720 ASF from the stack testing, in Figures 13 and 14 below. Active area showed a strong correlation with the initial cell voltage, consistent with expectations that accessible surface area plays a large role in catalyst activity.

Figure 13: % Active Area vs. initial cell stack voltage

Figure 14: Current density at low overpotential vs. initial cell voltage

The kinetic data also correlated with the initial cell voltage, but only when Catalyst F was removed from the trendline. As discussed above, Catalysts E and F showed much lower active area than the corresponding catalysts that did not contain Metal 3. Catalyst F also contains Metal 2, which was found to increase the current density at low overpotential, but the benefit was not realized at high current density due to the low active area.

5 Conclusions and Recommendations

Electrochemical screening tests for catalyst powders were successfully developed and were compared to stack results for the five alternate anode catalysts described in the survey report. It was discovered that the in-house synthesis method resulted in powders with higher % active area than powders supplied commercially. The higher active area directly translated to lower initial cell voltages. The screening tests also demonstrated that oxides containing Metal 2 had higher current density at low overpotential than oxides with Metal 1, which also reduced the cell voltage. However, the pure Metal 2 oxide materials were unstable over time and cell voltages increased to unacceptable levels within 500 hours of operation. Metal 3 appeared to stabilize these materials, but addition of this component as a 50-50 mixture resulted in low % active areas which increased the cell voltage at the high current densities experienced during typical electrolysis testing.

Based on these results, Catalyst C will be carried forward for performance testing with alternate membrane materials. In addition, the fusion method will be used to synthesize a 50-50 Metal 1/Metal 2 blend, in hopes that the Metal 1 oxide will sufficiently stabilize Metal 2 without the deleterious effects of Metal 3 on active area. Literature work exists to support the stabilization of Metal 2 by Metal 1. Future work outside the scope of this project could include looking at different metal proportions to optimize performance and stability of these materials.

Catalyst G, an alternate cathode catalyst, did not perform as well as the baseline, most likely due to the large particle size and low surface area. There may still be promise for this material at higher surface areas, but no further testing is planned as part of this project.

6 References

¹ Interim Report of PEM Electrolysis Catalyst Candidates

² S. Ardizzone, G. Fregonara, S. Trasatti, *Electrochimica Acta*, **35** (1), p. 263-267 (1990).

ATTACHMENT 10

RESEARCH FOR HIGHER EFFICIENCY PEM TECHNOLOGY

FINAL REPORT OF PEM ELECTROLYSIS MEMBRANE CANDIDATES

PREPARED BY:

**PROTON ENERGY SYSTEMS
December 12, 2007**

RESEARCH FOR HIGHER EFFICIENCY PEM TECHNOLOGY

Final Report of PEM Electrolysis Membrane Candidates

Prepared by

Proton Energy Systems
10 Technology Drive
Wallingford, CT 06492

12 December 2007

Prepared for:

University of Nevada Las Vegas Research Foundation
Under Subcontract No. RF-05-HFS-005-A03

Under U.S. Department of Energy, Golden Field Office
Contract No. DE-FG36-03GO130

Table of Contents

1	Summary	3
2	Introduction.....	3
3	Approach.....	5
4	Results and Discussion	6
5	Conclusions and Recommendations	9
6	References.....	10

Table of Figures

Figure 1: Table of physical properties measured.....	4
Figure 2: Summary of litmus test results for candidate membranes.....	4
Figure 3: Table of processing results summary	6
Figure 4: Results of pre-electrolysis stack testing	7
Figure 5: Voltages from polarization curves	7
Figure 6: Initial polarization curve	8
Figure 7: 100-hour polarization curve	8
Figure 8: Table of membrane potentials vs. time at two specific current densities.....	9

Final Report of PEM Electrolysis Membrane Candidates

1 Summary

As presented in the membrane survey report, six membranes (five experimental membranes plus the baseline) were selected for screening based on discussions with suppliers. Litmus/screening test results for those membranes that were provided were analyzed in the previous survey report and are summarized in this report.

Attempts to integrate these materials into membrane electrode assemblies (MEAs) for electrolyzers are described in this report, including processing and electrochemical results. Some of the membrane candidates could not be successfully processed and were screened out from further characterization. During the evaluation process, an additional membrane not tested in the initial survey was procured from one of the suppliers and added to the study. Next steps include combining selected membranes with high performing catalysts and characterizing these optimized MEAs.

2 Introduction

2.1 General:

Membranes for current PEM water electrolyzers have to serve several purposes simultaneously. The membrane acts as a separator between the anode and cathode reactants and product gases, while providing a conductive pathway for protons. The membrane must also be able to withstand the electrolyzer environment which includes electrical potential above 1.5 V, aggressive chemicals, high mechanical loads, and temperatures from 40°F to 140°F. The membrane must therefore be thin enough to minimize resistivity to ion flow, while maintaining low back diffusion of gases and high durability. Fluorinated ionomers such as Nafion have been found to be suitable for these applications. Hydrocarbon-based materials also have been receiving significant attention because they are expected to be much less expensive than their fluorinated counterparts. Also, a wide variety of chemical structures and equivalent weights are at least theoretically possible. On the other hand, hydrocarbons are inherently less stable than fluorocarbons, so these materials are expected to be less robust chemically. Mechanical strength and brittleness can also be issues with the thin hydrocarbon materials.

2.2 Summary of Survey Report:

From a combination of sources, 15 membrane suppliers were contacted to discuss potential applications in PEM electrolysis. The interactions with these suppliers were detailed in the previous report.¹ Many suppliers did not provide samples due to various reasons including: (1) concerns about the supplier's manufacturing capabilities, (2) lack of fit between suppliers' products and electrolyzer requirements and (3) issues surrounding the supplier's confidentiality agreements.

Membranes were initially evaluated against the following physical properties:

Parameter	Desired Response	Reason
Thickness	Minimize	Improved ionic conductivity
Chemical stability	Maximize/Pass	Cell durability/reliability
Acid capacity	Maximize	Improved ionic conductivity
Water content	Balance	Higher = Improved ionic conductivity Lower = Improved mechanical strength
Failure Elongation	Maximize	Cell reliability
Tensile Strength	Maximize	Cell reliability
H ₂ diffusion	Minimize	Minimize H ₂ cross-over
N ₂ diffusion	Minimize	Minimize H ₂ cross-over
H ₂ O diffusion	Indeterminate	(see discussion below)

Figure 1: Table of physical properties measured

The initial goal of this testing was not to require a match to the baseline, but to provide a database of material properties to understand the most relevant parameters for predicting performance and reliability in order to guide future screening efforts. There exists some controversy in particular about whether the Fenton's reagent-based chemical stability test is unrealistically harsh for non-fluorinated membranes. For the short term, our plan continued to use this test as a screening tool, though no membrane candidates were ruled out solely on the basis of failing this test. Regardless, similar performance in the above tests to baseline membranes currently used in production MEAs builds confidence the membrane will withstand MEA processing and electrolysis conditions.

None of the experimental membranes showed characteristics deemed to be severe enough to warrant elimination during the screening phase. Results of some of the tests from the survey report are summarized below:

	Dupont	Supplier H				Supplier A
	Baseline N-117	B	C	D	E	F
Membrane Type	Fluorinated	Hydrocarbon	Fluorinated	Hydrocarbon	Hydrocarbon	Fluorinated
Visual Inspection	Passed	Passed	Passed	Passed	Passed	Passed
Thickness (mil)	7.0	1.7	2.5	1.5	1.4	0.7
Acid Capacity (meq/g)	0.95	1.33	0.90	1.52	1.37	0.98
Water Content (% wt)	39.6	73.7	50.2	55.6	46.7	51.1
Chemical Stability (mg F-/g sample)	1.11	Dissolved	1.92	Dissolved	Discolored	Dissolved
Tensile Strength (psi)						
Strong direction	2100 ± 700 (2400 ± 300)	2100 ± 300	N/A	N/A	3200 ± 600	N/A
Weak direction	1930 ± 120	1800 ± 700 (2100 ± 400)	N/A	N/A	3070 ± 400	N/A
Failure Elongation (%)						
Strong direction	120 ± 60 (140 ± 30)	190 ± 40	N/A	N/A	40 ± 30	N/A
Weak direction	160 ± 10	150 ± 80 (180 ± 50)	N/A	N/A	30 ± 20	N/A

**Figure 2: Summary of litmus test results for candidate membranes
(Error bars represent one standard deviation)**

All of the advanced membrane candidates were significantly thinner than the baseline membrane. However, the tensile strength measurements were equal or equivalent to the baseline for the membranes measured, which was encouraging from a durability standpoint. Still, failure elongation % was low for Membrane E and only one fluorinated membrane and the baseline membrane passed the Fenton's reagent test. While this test may be overly severe, failing the test still raises potential issues of long term stability and ability to withstand MEA processing conditions when compared to the baseline material, which does pass this test. Based on these results and the processing evaluation discussed below, Supplier H provided an additional sample designated Membrane G, which had a higher thickness of 3.9 mil.

The hydrogen, nitrogen, and water permeation rates through the membranes were also presented in the survey report and showed a range of performance. One concern with the thinner membranes was that the lower thickness could result in high back diffusion of hydrogen, which ultimately results in higher overpotential required to reach the same net current density. However, the hydrogen permeation rates tested were actually lower for the membranes from Supplier H, despite the lower thickness of these membranes. As expected, the nitrogen data follows the same trend as the hydrogen.

The water permeation values were much higher than the baseline for the membranes tested, particularly Membrane F. As discussed in the survey report, the water content in the hydrogen gas product stream impacts cost and efficiency because of the drying costs. However, it is not clear how water permeation in the membrane correlates with the product hydrogen water content and arguments can be made for trends in either direction. More water transport in the membrane could lead to more water in the hydrogen stream, but higher permeation can also result in easier backflow across the membrane due to the pressure differential in the cell. In addition, the experimental membranes are all more hydrated than Nafion 117, which also could result in higher water transport. Experimental measurements of the water in the hydrogen stream are needed in order to better understand these competing effects.

3 Approach

3.1 Processing:

Typical MEA preparation at Proton Energy Systems involves a decal transfer process of the catalysts onto the membrane at elevated temperature and pressure. Several of the membrane materials could not withstand the typical production conditions used for 7 mil Nafion. Based on these results, a parametric study was performed at milder conditions to determine whether an effective decal transfer could be achieved. Some of the MEAs were then manufactured into MEAs using the modified conditions.

3.2 Testing:

Membranes which could be successfully manufactured into MEAs were tested for lateral and cross cell resistance. Due to the small quantities of some of the membrane samples, a smaller active area stack design was chosen as the testing vehicle. This design is intended to accommodate a single MEA; therefore, all the experimental membranes were compared to a single-cell stack containing a baseline MEA. The MEAs were built into these single-cell stacks using typical production methods and acceptance test protocols before electrolysis testing. Stacks were tested at 1237 mA/cm² current density for 500 hours of operation or until cell failure.

Polarization curves and voltage data as a function of time at constant current were also collected. A comparison of the results is presented in this report.

4 Results and Discussion

4.1 Processing

Initial attempts to process some of the membrane candidates resulted in degradation of the membrane during decal transfer. Degradation characteristics ranged from complete disintegration of the material to discoloration and/or adhesion to the decal substrate. Therefore, a study of reduced temperatures and/or pressures was performed vs. pressing time with the baseline membrane to determine alternate conditions which would result in sufficient transfer of catalyst to the membrane surface. Test cases also involved evaluating the duration of the pressing cycle, though to a lesser extent. The milder conditions were then applied to the alternate membranes.

Processing results for each membrane vs. varying parameters are tabulated below. Bold text denotes the parameters used to effectively transfer the catalyst to the membrane. Membranes which were pressed under reduced temperature conditions had to be pressed for longer times to transfer the catalyst. Membranes in italics were ruled out at this stage because the highest temperatures and pressures that the membrane could withstand resulted in significant catalyst material failing to transfer. Based on the results, membrane candidates B, E and G were passed to the MEA evaluation phase for comparison with the baseline.

Membrane	Supplier	Production Time/ Temperature	Reduced Temperature/ Extended Time
A	Dupont	Pass	Pass
B	H	Fail	Pass
<i>C</i>	H	Fail	Fail
<i>D</i>	H	Fail	Fail
E	H	Pass	N/A
<i>F</i>	A	Fail	Fail
G	H	Fail	Pass

Figure 3: Table of processing results summary

4.2 Electrolysis Cell Results

Results of pre-electrolysis testing performed on cell stacks containing the different membrane candidates are shown in the table below. Three of four cell stacks passed acceptance test criteria for nitrogen diffusion rates and cell resistances, and none failed the electrical short check. The stack containing Membrane E failed to meet the criteria for nitrogen diffusion. It was hypothesized that the relative stiffness of the membrane material was creating a cross cell leak path through a fluid port. A thermal “soaking” cycle was employed to help allow seal materials to creep. After twenty four hours, the stack was taken off thermal soak and the sealing bolts re-torqued. The nitrogen diffusion test was redone. The cell failed the diffusion test for the second time. It is therefore probable that this cell failed due to small tears or pinholes in the membrane. This failure could have been due to the relative thinness of this membrane for electrolysis

applications or caused by alignment issues in the cell hardware design which put excessive stress on the membrane. Cause has not been unequivocally determined at this time.

ACCEPTANCE TESTING BEFORE ELECTROLYSIS				
Cell Stack	Membrane A	Membrane B	Membrane E	Membrane G
<i>Stack Temp, °F</i>	68	70	69	71
<i>Diffusion Rate</i>				
@ 250 psid (cc/min/cell)	Pass	Pass	Fail High	Pass
@ 375 psid (cc/min/cell)	Pass	Pass	NA	Pass
<i>Resistance (Temp < 80 F)</i>				
@ Ambient	Pass	Pass	Pass	Pass
@ 250 psid	Pass	Pass	NA	Pass
<i>Electrical Short Check</i>				
Pass/Fail	Pass	Pass	Pass	Pass

Figure 4: Results of pre-electrolysis stack testing

Polarization curves were taken both immediately after getting the cell to the desired operating temperature and pressure and at 100 hours of operation. Results at two current densities are shown in the table below.

	Initial polarization curve		100 hour polarization curve	
	1000 mA/cm ²	2000 mA/cm ²	1000 mA/cm ²	2000 mA/cm ²
<i>Membrane A</i>	1.86	2.06	1.86	2.54
<i>Membrane B</i>	2.14	2.47	NA	NA
<i>Membrane E</i>	NA	NA	NA	NA
<i>Membrane G</i>	2.22	2.67	2.07	2.67

Figure 5: Voltages from polarization curves

The data shows that during the initial few hours of operation there is a significant amount of change in the electrode performance. The experimental membranes showed higher overpotential vs. the baseline, especially in the initial curve. However, by 100 hours, the baseline cell potential at 2000 mA/cm² was almost identical to Membrane G and below the initial value for Membrane B, indicating potential for improved operation after break-in. The full initial and 100 hour polarization curves are shown in Figures 5 and 6 below, respectively. During the initial polarization curve, Membrane A (the baseline material) showed the best performance followed by Membrane B and then Membrane G.

Figure 6: Initial polarization curve

After approximately 55 hours of operation, Membrane B failed due to high combustible gas sensor readings in the water reservoir, indicating a leak through the membrane. At 100 hours of operation the cell stacks with Membranes A and G continued to operate well, and both cells approached the same potential at low current density. The polarization curves at 100 hours are shown in Figure 6.

Figure 7: 100-hour polarization curve

The non-linear response at high current density is not typical and may be due to mass transport limitations in this cell hardware. This test cell design was chosen due to the smaller amounts of membrane required to assemble the cell, but is not optimized for high current density. Still, Membrane G appears to perform more consistently as the current density increases, with the two cell potentials reaching similar values as the current reaches 1800 to 2000 mA/cm².

From experience with baseline electrodes, there appears to be a break-in period of about 100 hours for these materials, followed by more stable performance. Due to the expectation that Membrane A would not show significant voltage change after 100 hours, the Membrane A stack was taken off test to open the test station position for other stacks. Membrane G was allowed to continue to operate through 500 hours. The table below summarizes the cell potentials observed for Membrane G vs. time at two specific current densities.

Cell Potential (volts)		
Hours Operating	2000 mA/cm ²	1000 mA/cm ²
Initial	2.67	2.22
100	2.67	2.12
200	2.71	2.12
300	2.68	2.12
400	2.67	2.10
500	2.68	2.09

Figure 8: Table of membrane potentials vs. time at two specific current densities

Although Membrane G did not outperform the baseline during constant current operation over 500 hours, it showed sufficient promise to be carried forward for evaluation with the experimental catalyst materials. At 2000 mA/cm², the performance converged with the baseline, particularly after the break-in period, indicating possible improved performance at the higher current densities. The MEA with Membrane G was also found to have a tear along the edge of the decal when the cell was torn down for analysis, which may have been due to the smaller cell design used in order to maximize testing capabilities on small membrane samples. It is unclear how much the performance was impacted by the cell design. In the evaluation task, the larger active area cell design used to test the catalyst materials will be utilized for all of the MEAs in order to eliminate this issue as a variable.

5 Conclusions and Recommendations

Of the membranes which passed the processing evaluation and progressed to the electrochemical evaluation against the baseline membrane, two were non-fluorinated hydrocarbon-based materials and one was a fluorinated membrane. Ideally, in terms of ionic resistance, thinner materials are expected to perform better, but this factor must be combined with low gas diffusion and durability under relevant stack conditions to assess the viability of new membranes.

Membrane E did not withstand stack manufacturing conditions. The handling of this membrane was not difficult, but it failed either as a result of the design of the testing hardware or due to the thinness of the membrane. There could also be a chemical degradation mechanism for these membranes that is causing them to fail. Membrane B is approximately 25% thicker than Membrane E and only lasted for ~57 hours of operation. This cell failed for high combustible gas readings, indicating a cross cell leak. While adjustments in the cell design could potentially enable these membranes to maintain reliability for longer periods, these cells did not reach even a 100 hour milestone. From the testing performed, it is recommended that Membranes B and E be removed from the evaluation plan. A better understanding of degradation mechanisms is required for these hydrocarbon type membranes which should be pursued in future programs.

Membrane G showed the most promise in terms of duration of operation. However, the cell potential that this membrane was able to maintain at constant current was greater than the baseline voltage for the duration of the testing. This is an undesirable result when measured against the milestones of cost reduction and increased efficiency prescribed in the Department of Energy's H2A model for hydrogen. This membrane showed some of the same signs of degradation that Membranes B and E showed, but it is believed that the comparatively high thickness of this membrane allowed prolonged life. It is recommended to consider this membrane since it did show some promise with its length of operation and should have good ion transport properties due to the lower thickness which may have been partially masked by the small active area cell design. In the next stage, this membrane should be utilized in standard production hardware in order to investigate the effects of cell design on material life and operating voltage.

6 References

¹Interim Report of PEM Electrolysis Membrane Candidates, submitted to UNLVRF Sept. 2007.